




For the most powerful, scalable video solutions – connect with IDIS

TECHNOLOGY LINE UP 2026



One Solution. One Company.

- 
1. Network Video Recorders & Servers
 2. Network Cameras
 3. I-Mobile Solutions
 4. HD Analogue Recorders
 5. HD Analogue Cameras
 6. Network Accessories
 7. Software Solutions
 8. Configuration Tree

IDIS Product Nomenclature

Network Cameras



① Product

DC : IP Camera
TC : Analog Camera

② Type

D : Dome
T : Bullet
B : Box
S : PTZ
Y : Fisheye
V : Covert
Z : Zoom
M : Mobile
G : Parking
U : Multi-imager
 Multi-directional
 Stitching
 Dual dome
TH : Thermal
SP : Specialty

③ Series

1,3 : Legacy Model
2 : Lite Series Model
4 : Quality Model
6 : Expert Model
8 : Flagship Model

④ Resolution

IP Camera, Analog Camera
0 : Lower than 1MP
1~9 : 1MP ~9MP
A~F : 10MP ~ 15MP

IP Camera > Thermal Camera
0 : Lower than CIF
1 : CIF
2 : VGA
3 : 1MP

⑤ Lens

0 : No Lens
1 : Fixed Lens
2 : Vari-focal Lens
3 : Motorized focus Lens 2.8mm ~ 12mm
4 : Motorized focus Lens 9mm ~ 22mm
5 : Motorized focus Lens 20mm ~ 50mm
6 : Zoom Lens x10~x19
7 : Zoom Lens x20~x29
8 : Zoom Lens x30~x40
9 : Zoom Lens Reserved
A : Stitching

⑥ Version

0 : Reserved
1~9, A~Z

⑦ Extension

IP Camera	
Stainless	S
Weather Proof	W
Vandal Resistance	V
Flush	F
Compact	C
Turret	E
ReactGuard	G
IR LED	R
Wireless Network	N
PSE Support	P
Motorized PanTilt	M
Modular Jack Type	J
AI Embedded	A

Analog Camera	
Stainless	S
Weather Proof	W
Vandal Resistance	V
Flush	F
Compact	C
IR LED	R
PoC	P

IP Camera > Specialty		
Explosion Proof	EX	
Flame Detection	FL	
Camera Type	Dome	D
	Positioner	P
	Bullet	T
	PTZ	S

⑧ Renewal Version

Network Video Recorder



① Product

DR : NVR
TR : DVR

② Type

M : Mobile (Mobile)
1 : Entry
2 : Quality
4 : Standard
6 : Expert
8 : Flagship

③ Generation

1~9

④ Channel


01~99 : 01~99Ch

⑤ Extension

NVR	
PSE Support	P
Failover	F
Redundant Power	D
Wireless Network	W
Hybrid	H
Compact	C
DVR	
PoC	P
RAID	R
Hybrid	H
Compact	C

⑥ Renewal Version

Pre-Installed VMS



① Product

IR : Pre-installed VMS
(Installed with IDIS Solution Suite)

② Series

1~9

③ Version

0 : Reserved
1~9

④ Channel

[PC-Grade Models]
Use 0 to ensure a three-digit model number

[Server-Grade Models]
Use 00 to ensure a four-digit model number

⑤ Renewal Version

About IDIS



IDIS Tower Pangyo, South Korea

IDIS is a global security company that designs and manufactures a comprehensive offering of video surveillance solutions to meet the specific needs of users in virtually every market sector.

IDIS designs, develops, manufactures, and supports its products and software all under one roof. For customers and partners, this means they can build a complete surveillance solution using products that seamlessly integrate from just one vendor. This simplifies the buying chain and provides local sales and technical support from a single vendor. Whether a large corporate enterprise, a retail chain, or single site, IDIS has a surveillance solution that meets the needs of an extensive range of businesses. With a broad range of high- and ultra-definition IP cameras, four to 64 channel NVRs, monitors, network accessories, a choice of VMS, and our DirectCX line-up for customers looking to leverage existing coax cabling, IDIS has a solution that fits.



IDIS specializes in creating, producing, and providing surveillance solutions for commercial and public sector markets.



42nd National Productivity Awards - Industrial Innovation Leader Category

IDIS SMART FACTORY

In 2018, IDIS was honored with a presidential citation in the 42nd National Productivity Competition (sponsored by the South Korean Ministry of Trade, Industry and Energy) for the company's custom designed IDIS Smart Factory.



6σ



IDIS Smart Factory Daejeon, South Korea

The IDIS Group: The Intelligent Video Surveillance Leader





IDIS AI Solutions

IDIS Deep Learning Analytics (IDLA) Artificial Intelligence optimized for video surveillance

IDLA represents a new paradigm for video surveillance, leveraging artificial intelligence and deep learning algorithms to perform previously labor-intensive tasks with up to 98% accurate alarms and notifications.





For the most powerful, scalable video solutions

IDIS AI Solutions

IDIS end-to-end video solutions give systems integrators and end-users everything they need for Middle East applications, from multi-branch retail to oil and gas sites, from luxury casinos to hospitality. With over 20 years' proven expertise, IDIS offers an extensive video tech line-up that includes proprietary IP cameras, recorders, and VMS, providing exceptional reliability and high performance with open platform compatibility for seamless integration with other systems.



IDLA Pro: IDIS Deep Learning Analytics Pro



Our existing IDLA engine has evolved into a next-generation neural network, going beyond basic detection to include advanced behavioral analysis such as crowd detection, alerts for abandoned or removed objects, and fall detection. These strengthen real-time situational awareness and allow faster responses to potential security and safety risks. From preventing accidents and ensuring public safety to securing highly populated, busy environments, IDLA Pro allows intelligent monitoring with less manual oversight and greater efficiency.


Crowd Detection

Crowd detection is vital for safety and efficiency. Automating crowd density monitoring in real time with an overlaid density map supports public safety in a range of settings, optimizing pedestrian flow, preventing bottlenecks, and enhancing domain awareness.



Abandoned Object Detection

Unattended items, particularly in busy public spaces, pose significant risks. Abandoned object detection automatically identifies suspicious items left unattended, enabling faster responses to potential threats.



Removed Object Detection

Alerts when valuable items or safety equipment are removed from designated areas provide critical oversight to prevent theft without requiring continuous monitoring, while supporting health and safety standards, and helping staff locate specialist equipment.



Fall Detection

Fall detection can play a vital role in a range of applications. It identifies incidents where individuals collapse or lose consciousness, enabling immediate alerts and rapid intervention, which significantly improves safety and patient care through faster first aid.



IDIS Cybersecurity

Ensuring information system security
and data confidentiality

More information available at

www.idisglobal.com/index/cybersecurity?lang=EN&country=IDIS




DirectIP[®] 2.0

Network security through a powerful mutual
authentication system

DirectIP[®] is a proprietary mutual authentication system supported by all IDIS IP products. When IDIS IP cameras are connected to an IDIS NVR, both devices mutually authenticate each other automatically through DirectIP[®]. When a DirectIP v2.0 Network camera is paired with a DirectIP v2.0 recorder, they exchange and store certificates, which are subsequently used in authentication processes during communication sessions.

Firewalls On NVRs

IDIS NVR products have their own firewalls installed that uses IP, MAC address, port and ICMP authentication. The firewalls on IDIS NVR products are designed and configured to prevent unauthorized access.



Two-Factor Authentication

The user must be certified by the IDIS Mobile App in addition to going through the usual login process by typing in a user ID and password. All IDIS NVRs safely protect user accounts utilizing Two-Factor Authentication.




Transport Layer Security (TLS)

Transport Layer Security (TLS) is a cryptographic protocol ensuring communication security and data integrity over networks, preventing malicious activities like data snooping, alteration, or destruction during transmission.



FEN Security


FEN is access and data transmission security system independently developed by IDIS using P2P technology. FEN is an automatic network access system. Expert knowledge of routers or NAT devices isn't needed to set up the system.



iBank


iBANK is IDIS own multimedia file system and database architecture for robust and effective data recording and searching even though multimedia data are overwritten or deleted frequently. Optimised to record and search the multimedia data.

* Patent No.: 10-0440783 (Jul. 2004. KOR)



Chained Fingerprint

Chained Fingerprint extracts unique video features as "Digital Fingerprint" and embeds them into subsequent frames, forming a chain-like blockchain. This technology ensures data integrity, making it suitable for court evidence.



IDIS Intelligent Codec

Delivers up to 90% savings on storage and bandwidth, providing faster, better searching of clearer images


More information available at

www.idisglobal.com/index/codec?lang=EN&country=IDIS



Lower your Cost of Ownership

IDIS Intelligent Codec revolutionizes surveillance with faster, smoother searching and clearer images while offering up to 90% savings on storage and bandwidth. IDIS Intelligent Codec delivers up to 30~50% bit rate reduction on top of H.265, achieving a total up to 65~75% reduction for users. Leveraging IDIS motion adaptive transmission (MAT) technology further reduces bit rates during idle surveillance, leading to up to 90% savings compared to H.264, depending on scene complexity and movement.




High Quality

with Identical image size to H.264

1/2 Bit Rate

with Identical image quality to H.264



IDIS Critical Failover

Strengthen fault tolerance with multi-layered protection

More information available at

www.idisglobal.com/index/critical?country=IDIS



Temporary Failover In Case of an Unstable Network

When the camera's network status is unstable, it starts to save to an internal recording session buffer (NLTSrec, up to 60MB). Therefore there is no disruption to the data stream or loss of data.



Smart Failover In Case of Network Failure

When the NVR and IP camera are disconnected, the camera's SD card instantly begins recording and automatically transfers the data to the NVR after recovery, leaving no incident unrecorded.



Uninterrupted Minimum 24-Hour Data Retention during Network Failure

SD card will record using the configured recording settings until the card is 50% full, then it will adjust the recording settings to provide as much backup as possible. * SD Card is not included.



Storage Redundancy In Case of Storage Failure

With native RAID 1 support, the NVR saves two identical copies of the data. So if one disk fails, the data is retrieved from the second one.



NVR Failover In Case of Hardware failure of the NVR

Primary and standby NVRs are monitored constantly. If a primary fails, the standby takes over, minimizing data loss and ensuring swift failover.



Native Dual Power Supply In Case of Power Supply Failure

When a failed power supply unit (PSU) is replaced, the spare PSU reverts back to redundant operation.

IDIS Smart UX Controls

An innovative user-centric, intuitive interface that revolutionizes PTZ control

More information available at

www.idisglobal.com/index/smartcontrol?country=IDIS



Groundbreaking Agility, Ease, and Accuracy

To combat the challenges of IP PTZ controls, IDIS has developed the game changing Smart UX Controls software to provide unparalleled accuracy and ease of use featuring intuitive “Slingshot” and “Rubberband” style controls, creating an experience unlike any other available on the market.



Slingshot and Rubberband


These smooth and seamless controls allow users to easily follow moving objects in real-time with ground breaking accuracy by panning images at different speeds and in different directions literally without lifting a finger.






Quick Dewarping

Direct access to fisheye camera dewarping.




Ctrl + Scroll Up




Quick Zoom

Direct access to digital zoom



Ctrl + Left Click & Hold
+ Scroll Up & Down



Quick PTZ

Direct access to IDIS camera Rubberband and Slingshot.



Slingshot

Aim and click any part of the image to quickly view a specific object, person, or area.



Ctrl + Shift + Left Click & Hold



Rubberband

Simply draw a Rubberband anywhere for easy and smooth PTZ control.




Ctrl + Left Click & Hold



Quick Save

Save the current images in a structured format.



Ctrl + S



Quick Find

Instantly go to the recorded video.




Drag & Drop



Direct IP[®]

A Next-Gen Video Surveillance Solution Based On An IP Framework

DirectIP[®] is an advanced video solution that seamlessly connects IP cameras, NVRs, and network devices to deliver rich functionality, while eliminating complex configuration.





NETWORK VIDEO RECORDERS

Make Your Surveillance Future Proof

Providing quality products and individualized
services at competitive rates and more PoE Capacity.



DR-8000 SERIES

Model Name	DirectIP 8500 Series H.265 4K Recorder	
	DR-8564	DR-8564D
		
VIDEO		
Video Inputs	64 IP Channels	64 IP Channels
Max. Incoming Throughput	540Mbps	540Mbps
Supported Camera	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF
Video Outputs	2 HDMI	2 HDMI
Display Resolution	HDMI: 3840x2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	HDMI: 3840x2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 1080ips	Up to 1080ips
RECORDING		
Max. Throughput	400Mbps, 1920ips @ UHD	400Mbps, 1920ips @ UHD
Recording Resolution	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)
Video Compression	H.265, H.264	H.265, H.264
Intelligent Codec	Supported	Supported
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Event	IDLA (Object Detection, Intrusion, Loitering, Line Crossing, Face Detection), BI (Exceed Occupancy Limit, Social Distancing, Mask Rule Violation, Queue Congestion), Motion, Trip-Zone, Tampering, Video Loss, Audio Detection, Alarm In, Network Alarm, Text-In, System, Etc.	
PLAYBACK		
Performance	64ch Synchronous Playback	64ch Synchronous Playback
Search Mode	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)
STORAGE		
HDD	SATA x 8, eSATA x 4, RAID 1, 5, 10 Supported	SATA x 8, eSATA x 4, RAID 1, 5, 10 Supported
NETWORK		
Client Connection	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1
Video In Connection	Gigabit Ethernet (Video In) x 3, SFP (Video In) x 2	Gigabit Ethernet (Video In) x 3, SFP (Video In) x 2
Transmission Speed	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)
PSE Power	-	-
Two-way Audio	Yes	Yes
INTERFACE		
Audio In / Out	Local (NVR): 1 RCA / 1 RCA + 2 HDMI IP Camera: 64 / 64 (Depending on IP Camera)	Local (NVR): 1 RCA / 1 RCA + 2 HDMI IP Camera: 64 / 64 (Depending on IP Camera)
Alarm In / Out	Local (NVR): 4 / 1 IP Camera: 64 / 64 (Depending on IP Camera)	Local (NVR): 4 / 1 IP Camera: 64 / 64 (Depending on IP Camera)
Alarm Reset In	Yes	Yes
Serial Interface	RS232 (Terminal Block), RS485 (Terminal Block)	RS232 (Terminal Block), RS485 (Terminal Block)
USB	USB 2.0 x 2, USB 3.0 x 1	USB 2.0 x 2, USB 3.0 x 1
GENERAL		
Operating System	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	482.6 x 88 x 529.5mm (19" x 3.5" x 20.8")	482.6 x 88 x 529.5mm (19" x 3.5" x 20.8")
Unit Weight	11.16kg (24.60lb) (with 2 HDDs)	12.24kg (26.98lb) (with 2 HDDs)
Power Input	100 ~ 240V~, 50/60Hz, 6.0 ~ 3.0A	100 ~ 240V~, 50/60Hz, 8.0 ~ 4.0A
Power Consumption	100 ~ 240V~, 50/60Hz, 6.0 ~ 3.0A, 145W	100 ~ 240V~, 50/60Hz, 8.0 ~ 4.0A, 145W x 2
Approvals	FCC, UL, CE, CB, KC, PSE	FCC, UL, CE, CB, KC, PSE

* Establish NVR Failover system with standby DR-8364F(D)

* Maximum HDD capacity Will be updated as new HDD models become available.
For the most recent information, please check http://designtool.idisglobal.com/design_tool/product_compatibility.php

DR-8000 SERIES

Model Name	DirectIP 8500 Series H.265 4K Recorder		
	DR-8532	DR-8532D	DR-8516
			
VIDEO			
Video Inputs	32 IP Channels	32 IP Channels	16 IP Channels
Max. Incoming Throughput	370Mbps	370Mbps	320Mbps
Supported Camera	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF
Video Outputs	2 HDMI	2 HDMI	2 HDMI
Display Resolution	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 960ips	Up to 960ips	Up to 480ips
RECORDING			
Max. Throughput	230Mbps, 960ips @ UHD	230Mbps, 960ips @ UHD	180Mbps, 480ips @ UHD
Recording Resolution	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)
Video Compression	H.265, H.264	H.265, H.264	H.265, H.264
Intelligent Codec	Supported	Supported	Supported
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Event	IDLA(Object Detection, Intrusion, Loitering, Line Crossing, Face Detection), BI (Exceed Occupancy Limit, Social Distancing, Mask Rule Violation, Queue Congestion), Motion, Trip-zone, Tampering, Video Loss, Audio Detection, Alarm In, Network Alarm, Text-In, System, Etc.		
PLAYBACK			
Performance	32ch Synchronous Playback	32ch Synchronous Playback	16 ch Synchronous Playback
Search Mode	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)		
STORAGE			
HDD	SATA x 8, eSATA x 4, RAID 1, 5, 6, 10 Supported	SATA x 8, eSATA x 4, RAID 1, 5, 6, 10 Supported	SATA x 8, eSATA x 4, RAID 1, 5, 6, 10 Supported
NETWORK			
Client Connection	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1
Video In Connection	Gigabit Ethernet (Video In) x 3, SFP (Video In) x 2	Gigabit Ethernet (Video In) x 3, SFP (Video In) x 2	Gigabit Ethernet (Video In) x 3, SFP (Video In) x 2
Transmission Speed	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)
PSE Power	-	-	-
Two-way Audio	Yes	Yes	Yes
INTERFACE			
Audio In / Out	Local (NVR): 1 RCA / 1RCA + 2HDMI IP Camera: 32 / 32 (Depending on IP Camera)	Local (NVR): 1 RCA / 1RCA + 2HDMI IP Camera: 32 / 32 (Depending on IP Camera)	Local (NVR): 1 RCA / 1RCA + 2HDMI IP Camera: 16 / 16 (Depending on IP Camera)
Alarm In / Out	Local (NVR): 16 / 4 IP Camera: 32 / 32 (Depending on IP Camera)	Local (NVR): 16 / 4 IP Camera: 32 / 32 (Depending on IP Camera)	Local (NVR): 16 / 4 IP Camera: 16 / 16 (Depending on IP Camera)
Alarm Reset In	Yes	Yes	Yes
Serial Interface	RS232 (Terminal Block), RS485 (Terminal Block)	RS232 (Terminal Block), RS485 (Terminal Block)	RS232 (Terminal Block), RS485 (Terminal Block)
USB	USB 2.0 x 2, USB 3.0 x 1	USB 2.0 x 2, USB 3.0 x 1	USB 2.0 x 2, USB 3.0 x 1
GENERAL			
Operating System	Embedded Linux	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	482.6 x 88 x 529.5mm (19" x 3.5" x 20.8")	482.6 x 88 x 529.5mm (19" x 3.5" x 20.8")	482.6 x 88 x 529.5mm (19" x 3.5" x 20.8")
Unit Weight	11.25kg (24.8lb) (with 2 HDDs)	12.63kg (27.84lb) (with 2 HDDs)	11.3kg (24.8lb) (with 2 HDDs)
Power Input	AC100 ~ 240V, 50/60Hz, 6.0 ~ 3.0A	AC100 ~ 240V, 50/60Hz, 8.0 ~ 4.0A	100 ~ 240V~, 50/60Hz, 6.0 ~ 3.0A
Power Consumption	100 ~ 240V~, 50/60Hz, 6.0 ~ 3.0A, 130W	100 ~ 240 V~, 50/60Hz, 8.0 ~ 4.0A, 100W x 2	100 ~ 240 V~, 50/60Hz, 6.0 ~ 3.0A, 130W
Approvals	FCC, UL, CE, CB, KC, PSE	FCC, UL, CE, CB, KC, PSE	FCC, UL, CE, CB, KC, PSE

* Maximum HDD capacity Will be updated as new HDD models become available.
For the most recent information, please check http://designtool.idisglobal.com/design_tool/product_compatibility.php

IDIS AND NDAA COMPLIANT

The National Defense Authorization Act

NDAA Summary

The John S. McCain National Defense Authorization Act (NDAA) for Fiscal Year 2019 was signed into law on August 13, 2018 and effective from August 2020. The law, specifically Section 889, prohibits federal agencies, their contractors and grant or loan recipients from procuring or using “telecommunications and video surveillance equipment or services” from specific Chinese companies as a “substantial or essential component of any system, or as critical technology as part of any system.” The NDAA ban includes telecommunications equipment produced by Huawei Technologies Company or ZTE Corporation, as well as video surveillance and telecommunications equipment produced by Hytera Communications Corporation, Hangzhou Hikvision Digital Technology Company, or Dahua Technology Company.

IDIS Equipment

IDIS provides NDAA compliant products, which includes solutions marketed to the US federal government, Department of Defense (DoD), and associated contractors. The following IDIS cameras and network video recorders (NVRs) do not use or deploy critical components or System-on-a-Chip (SOC) circuits produced by NDAA banned component vendors, making them compliant with the NDAA.

Made in **KOREA** | **NDAA**
Compliant



DR-6000 SERIES

Model Name	DirectIP 6500 Series H.265 4K Recorder		
	DR-6532P-A	DR-6516P-A	DR-6508P
	 	 	 
VIDEO			
Video Inputs	32 IP Channels	16 IP Channels	8 IP Channels
Max. Incoming Throughput	370Mbps	320Mbps	270Mbps
Supported Camera	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF
Video Outputs	2 HDMI	2 HDMI	2 HDMI
Display Resolution	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 960ips	Up to 480ips	Up to 240ips
RECORDING			
Max. Throughput	230Mbps, 960ips @ UHD	180Mbps, 480ips @ UHD	140Mbps, 240ips @ UHD
Recording Resolution	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)
Video Compression	H.265, H.264	H.265, H.264	H.265, H.264
Intelligent Codec	Supported	Supported	Supported
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Event	IDLA (Object Detection, Intrusion, Loitering, Line Crossing, Face Detection), BI (Exceed Occupancy Limit, Social Distancing, Mask Rule Violation, Queue Congestion), Motion, Trip-Zone, Tampering, Video Loss, Audio Detection, Alarm In, Network Alarm, Text-In, System, Etc.		
PLAYBACK			
Performance	32ch Synchronous Playback	16ch Synchronous Playback	8ch Synchronous Playback
Search Mode	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)
STORAGE			
HDD	SATA x 6, eSATA x 4, RAID 1 Supported	SATA x 6, eSATA x 4, RAID 1 Supported	WSATA x 6, eSATA x 4, RAID 1 Supported
NETWORK			
Client Connection	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1
Video In Connection	Gigabit Ethernet (IP Camera) x 16 + Gigabit Ethernet (Ext) x 1	Gigabit Ethernet (IP Camera) x 16 + Gigabit Ethernet (Ext) x 1	Gigabit Ethernet (IP Camera) x 8 + Gigabit Ethernet (Ext) x1
Transmission Speed	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)
PSE Power	PoE, IEEE 802.3at (Class 4) Supported 16Ports, 200W	PoE, IEEE 802.3at (Class 4) Supported 16Ports, 200W	PoE, IEEE 802.3at (Class 4) Supported 8Ports, 120 W
INTERFACE			
Audio In / Out	Local (NVR): 1 RCA / 1RCA + 2 HDMI IP Camera: 32 / 32 (Depending on IP Camera)	Local (NVR): 1 RCA / 1RCA + 2HDMI IP Camera :16 / 16 (Depending on IP Camera)	Local (NVR): 1 RCA / 1 RCA + 2 HDMI IP Camera: 8 / 8 (Depending on IP Camera)
Alarm In / Out	Local (NVR): 4 / 1 IP Camera: 32 / 32 (Depending on IP Camera)	Local (NVR): 4 / 1 IP Camera: 16 / 16 (Depending on IP Camera)	Local (NVR): 4 / 1 IP Camera: 8 / 8 (Depending on IP Camera)
Alarm Reset In	Yes	Yes	Yes
Serial Interface	RS232 (Terminal Block), RS485 (Terminal Block)	RS232 (Terminal Block), RS485 (Terminal Block)	RS232 (Terminal Block), RS485 (Terminal Block)
USB	USB 2.0 x 2, USB 3.0 x 1	USB 2.0 x 2, USB 3.0 x 1	USB 2.0 x 2, USB 3.0 x 1
GENERAL			
Operating System	Embedded Linux	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	430 x 88 x 420mm (16.9" x 3.5" x 16.5")	430 x 88 x 412.8mm (16.9" x 3.5" x 16.25")	430 x 88 x 420mm (16.9" x 3.5" x 16.5")
Unit Weight	6.75kg (14.88lb) (with 1 HDD)	6.75kg (14.88lb) (with 1 HDD)	6.75kg (14.88lb) (with 1 HDD)
Power Input	100 ~ 240V~, 50/60Hz, 4.0 ~ 2.0A	100 ~ 240V~, 50/60Hz, 4.0 ~ 2.0A	100 ~ 240V~, 50/60Hz, 3.0 ~ 1.5 A
Power Consumption	100 ~ 240V~, 50/60Hz, 4.0 ~ 2.0A, 360W	100 ~ 240V~, 50/60Hz, 4.0 ~ 2.0A, 360W	100 ~ 240V~, 50/60Hz, 3.0 ~ 1.5 A, 250 W
Approvals	FCC, UL, CE, CB	FCC, UL, CE, CB	FCC, UL, CE, CB

* Maximum HDD capacity Will be updated as new HDD models become available.
For the most recent information, please check http://designtool.idisglobal.com/design_tool/product_compatibility.php

DR-2000 SERIES

Model Name	DirectIP 2500 Series H.265 4K Recorder			
	DR-2516P-A	DR-2508P-A	DR-2504P-B	DR-2504P-C
	 	 	 	 
VIDEO				
Video Inputs	16 IP Channels	8 IP Channels	4 IP channels	4 IP channels
Max. Incoming Throughput	320Mbps	270Mbps	160Mbps	160Mbps
Supported Camera	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF	DirectIP, AXIS, PANASONIC, ONVIF
Video Outputs	1 HDMI, 1 VGA	1 HDMI, 1 VGA	1 HDMI, 1 VGA	1 HDMI, 1 VGA
Display Resolution	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200 / VGA: 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200			
Display Speed	Up to 480 ips	Up to 240ips	Up to 120ips	Up to 120ips
RECORDING				
Max. Throughput	180Mbps, 480ips @ UHD	140Mbps, 240ips @ UHD	70Mbps, 120ips @ UHD	70Mbps, 120ips @ UHD
Recording Resolution	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)
Compression	H.265, H.264	H.265, H.264	H.265, H.264	H.265, H.264
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Event	IDLA (Object Detection, Intrusion, Loitering, Line Crossing, Face Detection), BI (Exceed Occupancy Limit, Social Distancing, Mask Rule Violation, Queue Congestion), Motion, Trip-Zone, Tampering, Video Loss, Audio Detection, Alarm In, Network Alarm, Text-In, System, Etc.			
PLAYBACK				
Performance	16ch Synchronous Playback 8ch 4K Playback	8ch Synchronous Playback 8ch 4K Playback	4ch Synchronous Playback 4ch 4K Playback	4ch Synchronous Playback 4ch 4K Playback
Search Mode	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)	Time-Lapse, Event Log, Text-In, Thumbnail, Metadata (via IDIS Center, IDIS Solution Suite)
STORAGE				
HDD	SATA x 2, eSATA x 1	SATA x 2, eSATA x 1	SATA x 2, eSATA x 1	SATA x 2, eSATA x 1, RAID 1 Supported
NETWORK				
Client Connection	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1	Gigabit Ethernet (Client) x 1
Video In Connection	Fast Ethernet (IP Camera) x 8 + Gigabit Ethernet (Ext) x 1	Fast Ethernet (IP Camera) x 8 + Gigabit Ethernet (Ext) x 1	Fast Ethernet (IP Camera) x 4	Fast Ethernet (IP Camera) x 4
Transmission Speed	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)	50Mbps / 100Mbps (BRP Mode)
PSE Power	PoE, IEEE 802.3at (class 4) supported 8ports, 100W	PoE, IEEE 802.3at (Class 4) supported 8ports, 100W	PoE, IEEE 802.3at (Class 4) supported 4ports, 50W	PoE, IEEE 802.3at (Class 4) supported 4ports, 50W
INTERFACE				
Audio In / Out	Local (NVR): - / 1RCA + 1HDMI IP Camera: 16 / 16 (Depending on IP Camera)	Local (NVR): - / 1RCA + 1HDMI IP Camera: 8 / 8 (Depending on IP Camera)	Local(NVR): - / 1RCA + 1HDMI IP Camera: 4 / 4 (Depending on IP Camera)	Local (NVR): - / 1RCA + 1HDMI IP Camera: 4 / 4 (Depending on IP Camera)
Alarm In / Out	Local (NVR): 4 / 1 IP Camera: 16 / 16 (Depending on IP Camera)	Local (NVR): 4 / 1 IP Camera: 8 / 8 (Depending on IP Camera)	Local (NVR): 4 / 1 IP Camera: 4 / 4 (Depending on IP Camera)	Local (NVR): 4 / 1 IP Camera: 4 / 4 (Depending on IP Camera)
Alarm Reset In	-	-	-	-
Serial Interface	RS232 (Terminal Block)	RS232 (Terminal Block)	RS232 (Terminal Block)	RS232 (Terminal Block)
USB	USB 2.0 x 1, USB 3.0 x 1	USB 2.0 x 1, USB 3.0 x 1	USB 2.0 x 1, USB 3.0 x 1	USB 2.0 x 1, USB 3.0 x 1
GENERAL				
Operating System	Embedded Linux	Embedded Linux	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	300 x 62 x 231mm (11.8" x 2.4" x 9.1")	300 x 62 x 231mm (11.8" x 2.4" x 9.1")	300 x 62 x 231mm (11.8" x 2.4" x 9.1")	300 x 62 x 231mm (11.8" x 2.4" x 9.1")
Unit Weight	2.3kg (5.1lb) (with 1 HDD)	2.3kg (5.1lb) (with 1 HDD)	2.2kg (4.9lb) (with 1 HDD)	2.2kg (4.9lb) (with 1 HDD)
Power Input	NVR Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 1.5A, Output: 12VDC, 5A) PSE Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 2.5A, Output: 54VDC, 2.33A)	NVR Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 1.5A, Output: 12VDC, 5A) PSE Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 2.5A, Output: 54VDC, 2.33A)	NVR Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 1.5A, Output: 12VDC, 5A) PSE Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 1.2A, Output: 48VDC, 1.35A)	NVR Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 1.5A, Output: 12VDC, 5A) PSE Adaptor (Input: 100 ~ 240VAC, 50/60Hz, 1.2A, Output: 48VDC, 1.35A)
Power Consumption	NVR: 12V=, 2.2A, 26.4W PSE: 54V=, 1.85A, 100W MAX	NVR: 12V=, 2.2A, 26.4W PSE: 54V=, 1.85A, 100W MAX	NVR: 12V=, 2.2A, 26.4W PSE: 48V=, 1.04A, 50W MAX	NVR: 12V=, 2.2A, 26.4W PSE: 48V=, 1.04A, 50W MAX
Approvals	FCC, CE, KC	FCC, CE, KC	FCC, CE, KC	FCC, CE, KC

* Maximum HDD capacity Will be updated as new HDD models become available.
For the most recent information, please check http://designtool.idisglobal.com/design_tool/product_compatibility.php

IDIS COMPACT SOLUTION & SPECIALTY

Complete security, simplified for small and mid-sized businesses

Ensure peace of mind with our high-performance, compact 4-channel recorders, designed for desktop or wall-mount installation. Perfect for retail stores, cafes, and restaurants, our recorders deliver the trusted IDIS quality and reliability you expect—without the complexity or high cost.



DR-1000 SERIES

Model Name	DirectIP 1500 Series Full HD Recorder		
	DR-1508P	DR-1508P-A	DR-1504P-A
			
VIDEO			
Video Inputs	8 IP Channels	8 IP Channels	4 IP Channels
Max. Incoming Throughput	100Mbps	100Mbps	60Mbps
Supported Camera	DirectIP	DirectIP	DirectIP
Video Outputs	1 HDMI, 1 VGA	1 HDMI, 1 VGA	1 HDMI, 1 VGA
Display Resolution	1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
Display Speed	Up to 240ips	Up to 240ips	Up to 120ips
RECORDING			
Max. Throughput	40Mbps, 240ips @ 8MP	40Mbps, 240ips @ 8MP	20Mbps, 120ips @ 8MP
Recording Resolution	Up to 8MP (Depending on IP Camera)	Up to 8MP (Depending on IP Camera)	Up to 8MP (Depending on IP Camera)
Video Compression	H.265, H.264	H.265, H.264	H.265, H.264
Intelligent Codec	Supported	Supported	Supported
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Event	Motion, Trip-Zone, Tampering, Video Loss, System, Etc.	Motion, Trip-Zone, Tampering, Video Loss, System, Etc.	Motion, Trip-Zone, Tampering, Video Loss, System, Etc.
PLAYBACK			
Performance	4ch Full HD Synchronous Playback	4ch Full HD Synchronous Playback	4ch Full HD Synchronous Playback
Search Mode	Time-Lapse, Event Log	Time-Lapse, Event Log	Time-Lapse, Event Log
STORAGE			
HDD	SATA x 1	SATA x 1	SATA x 1
NETWORK			
Client Connection	Fast Ethernet (Client) x 1	Fast Ethernet (Client) x 1	Fast Ethernet (Client) x 1
Video In Connection	Fast Ethernet (IP Camera) x 8	Fast Ethernet (IP Camera) x 8	Fast Ethernet (IP Camera) x 4
Transmission Speed	20Mbps	20Mbps	20Mbps
PSE Power	PoE, IEEE 802.3at (Class 4) Supported 8Ports, 50W	PoE, IEEE 802.3at (Class 4) Supported 8Ports, 70W	PoE, IEEE 802.3at (Class 4) Supported 4Ports, 35W
Two-way Audio	-	-	-
INTERFACE			
Audio In / Out	-	-	-
Alarm In / Out	-	-	-
Alarm Reset In	-	-	-
Serial Interface	-	-	-
USB	USB 2.0 x 2	USB 2.0 x 2	USB 2.0 x 2
GENERAL			
Operating System	Embedded Linux	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	205 x 44.5 x 216.4mm (8.07" x 1.75" x 8.52")	205 x 44.5 x 216.4mm (8.07" x 1.75" x 8.52")	205 x 44.5 x 216.4mm (8.07" x 1.75" x 8.52")
Unit Weight	1.2kg (2.65 lb) (with 1 HDD)	1.2kg (2.65 lb) (with 1 HDD)	1.2kg (2.65 lb) (with 1 HDD)
Power Input	NVR Adaptor (Input: 100 ~ 240V~, 50/60Hz, 2A, Output: 56V, 1.28A) - In countries using 200 ~ 240V such as UK NVR Adaptor (Input: 100 ~ 240V~, 50/60Hz, 1.2A, Output: 54V, 1.67A) - In countries using 100 ~ 127V such as US	NVR Adaptor (Input: 100 ~ 240V~, 50/60Hz, 2.5A, Output: 54V, 1.86A) - In countries using 200 ~ 240V such as UK NVR Adaptor (Input: 100 ~ 240V~, 50/60Hz, 2.5A, Output: 54V, 2.33A) - In countries using 100 ~ 127V such as US	NVR Adaptor (Input: 100 ~ 240V~, 50/60Hz, 1.5A, Output: 48V, 1.35A)
Power Consumption	54 ~ 56V~, 1.28 ~ 1.24A, 69W MAX	54V~, 1.65A, 89W MAX	48V, 1A, Max. 48W
Approvals	KC, CE, FCC	KC, CE, FCC	KC, CE, FCC

* Maximum HDD capacity Will be updated as new HDD models become available.
For the most recent information, please check http://designtool.idisglobal.com/design_tool/product_compatibility.php

ENTERPRISE NETWORK VIDEO RECORDERS

IR-310D

NDAA
Compliant

IDIS SOLUTION
SUITE®



IDIS Ready to Install VMS Workstation
NDAA-Compliant



The IDIS Enterprise NVR, IR-310D, allows users to establish a reliable, high performance surveillance system in minutes while providing exceptional manageability. The IR-310D operating system(OS), powered by SSD and IDIS Solution Suite VMS, is perfect for large-scale systems and ensures mission-critical data retention through RAID and redundant power. IR-310D is ideal for building a powerful and economical surveillance system to meet enterprise level needs.

- Ready to Install VMS with Workstation
- Tested and validated with IDIS Solution Suite up to 64 Full HD H.264/265 IP cameras
- Storage configuration: 8 SATA + 3 eSATA Ports
- Supports up to 64 Full HD cameras in real-time for enterprise-level surveillance systems
- 400Mbps maximum recording bandwidth per server
- Complete compatibility with IDIS components: IP cameras, Analogue DVR, DirectCX HD Analogue, DirectIP NVR, and encoders
- 2U rack mount chassis
- Supports H.264, H.265 compression, and Intelligent Codec
- Supports Onvif Profile S, Axis, Panasonic, etc.

DIMENSIONS



SPECIFICATIONS

IR-310D	
	
Model Name	
VIDEO	
Video Inputs	64ch Recommended
Video Outputs	2 HDMI 2.0
RECORDING	
Max. Throughput	Up to 400Mbps
STORAGE	
HDD	SATA x 8, eSATA x 3, RAID 1, 5, 10 Supported, Hot-swappable
SSD	240G SSD for Operating System (M.2 type)
NETWORK	
Network Connection	2 GbE RJ45 Ports (1000 Base-T)
INTERFACE	
USB	6 (2 Front USB 2.0 + 3 Back USB 3.0 Type-A + 1 Back USB 3.0 Type-C)
Serial Interface	-
GENERAL	
Supported Service	IDIS Solution Suite Expert and Federation Service
Supported Version	Version 3.6.0 or Higher
Operating System	Microsoft® Windows 10 IoT Enterprise
Processor	Intel® i5-10500, 3.1GHz
Memory	DDR4 PC-25600, 16GB
ENVIRONMENTAL	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%
ELECTRICAL	
Power Input	100 ~ 240V~, 50/60Hz, 8.0 ~ 4.0A (Redundant)
Power Consumption	120W x 2
Approval	FCC, CE, CB, UL, PSE, KC
MECHANICAL	
Unit Dimensions (W x H x D)	482.6 x 88 x 537mm (19" x 3.5" x 21.1")
Unit Weight	12.6kg (27.8lb)

ENTERPRISE NETWORK VIDEO RECORDERS

IR-1200

NDAA
Compliant



IDIS SOLUTION
SUITE®

IDIS Ready to Install VMS Workstation
NDAA-Compliant



- Pre-installed with IDIS Solution Suite VMS
- Tested and validated with IDIS Solution Suite up to 256 Full HD H.264/H.265 IP cameras
- Supports up to 256 Full HD cameras in real-time for enterprise-level surveillance systems
- 1,024Mbps (128MBps) maximum recording bandwidth per server
- Redundancy of power for mission-critical reliability
- Complete compatibility with IDIS components: IP cameras, Analogue DVR, DirectCX TVR, DirectIP NVR, and encoders
- Equipped with RAID 5, RAID 6 recording, Hot swappable
- Supports H.264, H.265 compression, and Intelligent Codec
- Supports Onvif Profile S, Axis, Panasonic, etc.

DIMENSIONS



SPECIFICATIONS

Model Name	IR-1200
GENERAL	
Supported Service	IDIS Solution Suite Expert and Federation Service
Supported Version	Version 2.6.0 or Higher
Operating System	Microsoft® Embedded Windows Server 2022 IoT Std
Network Connection	6 GbE RJ45 Ports (1000 Base-T)
OS Storage	2 x M.2 480GB (RAID 1 configured)
Recording Storage	8 Bay
Hard Disk Drive Configuration	Up to 8 x Large Form Factor Near-line SATA Hard Disk Drives, Hot-swappable, RAID 5, RAID 6
Processor	Intel® Xeon® Processor silver 4410Y 2G, 12C/24T
Memory	16GB RAM (1 x 16GB DDR5-4800MT/s RDIMM)
Video Out	2 VGA
Approval	FCC Rating Class A, CISPR 22, EN55022, EN55024, FCC CFR 47, Pt 15, ICES-003, CvvS14336-1, CNS13438, GB4943, GB9254, EN 61000-3-2, EN61000-3-3, RoHS, Reach(SVHC), WEEE
RECORDING	
Max. Throughput	Up to 1024Mbps (128MBps)
Number of Cameras	Up to 256
MECHANICAL	
Unit Dimensions (W x H x D)	482.0 x 86.8 x 721.62mm (18.97" x 3.41" x 28.4")
Unit Weight	Max 28.6kg (63.0lbs)
ELECTRICAL	
Power Input	100 ~ 240VAC, 50/60Hz
Power Supply	Redundant, Hot Swappable
Power Capacity	800W
ENVIRONMENTAL	
Operating Temperature	10° ~ 35°C (50°F ~ 95°F)
Operating Humidity	0% ~ 80%
FOR MARKETING MATERIAL ONLY	
Key Feature	- 12Gb SAS offering unmatched I/O performance - RAID levels: 0, 1, 5, 6, 10, 50, 60 - Hot-swappable drives, fans and power supplies

ENTERPRISE NETWORK VIDEO RECORDERS


IS-1200 | **NDAA**
Compliant

Direct Attached Storage with IR-1200
NDAA-Compliant



- 12Gbps SAS offering unmatched I/O performance
- Hot-swappable drives, fans and power supplies
- Complete compatibility with IDIS components: IP cameras, Analogue DVR, DirectCX TVR, DirectIP NVR, and encoders
- Equipped with RAID 5, RAID 6 recording, Hot swappable
- Supports H.264, H.265 compression, and Intelligent Codec

DIMENSIONS



SPECIFICATIONS

Model Name	IS-1200
GENERAL	
Hard Disk Drive Configuration	Up to 12 x SAS Hard Disk Drives, Hot-swappable, RAID 5, RAID 6
Recording Storage	12 Bay
Interface	Enclosure Management Module, dual
Approval	FCC Rating Class A, CISPR 22, EN55022, EN55024, FCC CFR 47, Pt 15, ICES-003, CvvNS14336-1, CNS13438, GB4943, GB9254, EN 61000-3-2, EN61000-3-3, RoHS, Reach (SVHC), WEEE
MECHANICAL	
Unit Dimensions (W x H x D)	444.0 x 545 x 86.8mm (17.5" x 21.5" x 3.4")
Unit Weight	Max 25.58kg (56.39lbs)
ELECTRICAL	
Power Input	100 ~ 127, 200 ~ 240VAC, 50/60Hz
Power Supply	Redundant, Hot Swappable
Power Capacity	800W
ENVIRONMENTAL	
Operating Temperature	0° ~ 40°C (32°F ~ 104°F)
Operating Humidity	5% ~ 85%
FOR MARKETING MATERIAL ONLY	
Key Feature	- 12Gb SAS offering unmatched I/O performance - RAID levels: 0, 1, 5, 6, 10, 50, 60 - Hot-swappable drives, fans and power supplies

AI IN THE BOX WITH **IDIS SOLUTION SUITE**

DV-3200(B)

NDAA
Compliant

IDIS SOLUTION
SUITE®

Enterprise-class AI in the Box Server

- AI in the Box with IDIS Solution Suite
- Compatible with IDIS Deep Learning Analytics (IDLA)
- 2U rack mount chassis



IDIS Deep Learning Analytics (IDLA)

Powered by the
IDIS Deep Learning Engine

- Industry-leading accurate deep learning engine
- Object classification suitable for surveillance applications
- Simple configuration and zero calibration





	DV-3200	DV-3200-B
Model Name		
SYSTEM		
Supported Service	IDIS Solution Suite IDLA VA Service	IDIS Solution Suite IDLA VA Service
Supported Version	Version 3.6.4 or Higher	Version 3.6.4 or Higher
Operating System	Microsoft® Windows 10 IoT Enterprise	Microsoft® Windows 10 IoT Enterprise
Processor	Intel® I5-10500, 3.1GHz	Intel® I5-10500, 3.1GHz
Memory	DDR4 PC-25600, 16GB	DDR4 PC-25600, 16GB
Processor	Intel® I5-10500, 3.1GHz	Intel® I5-10500, 3.1GHz
Channels available for Analytics	Up to 64ch in condition of 640 x 360 @ 5ips video input	Up to 64ch in condition of 640 x 360 @ 5ips video input
IDLA Processing Unit	NVIDIA A2000, 12GB	NVIDIA A2000, 6GB
Network Connection	2 GbE RJ45 Ports (1000 Base-T)	2 GbE RJ45 Ports (1000 Base-T)
Video Outputs	2 HDMI 2.0	2 HDMI 2.0
USB	6 (2 Front USB 2.0 + 4 Back (3 USB 3.0 TYPE-A + 1 TYPE-C))	6 (2 Front USB 2.0 + 4 Back (3 USB 3.0 TYPE-A + 1 TYPE-C))
MECHANICAL		
Unit Dimensions (W x D x H)	482.6 x 88 x 523.3mm (19" x 3.5" x 20.6")	482.6 x 88 x 523.3mm (19" x 3.5" x 20.6")
Unit Weight	11.8kg (26.01lb)	11.8kg (26.01lb)
ELECTRICAL		
Power Input	100 ~ 240V~, 50/60Hz, 6.0 ~ 3.0A	100 ~ 240V~, 50/60Hz, 6.0 ~ 3.0A
Power Consumption	270W	270W
Approval	FCC, CE, CB, UL, PSE, KC	FCC, CE, CB, UL, PSE, KC
ENVIRONMENTAL		
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90%	0% ~ 90%

AI IN THE BOX

ALL-IN-ONE 4-CHANNEL AI BOX FOR RETAIL

DV-1304 | **NDA**
Compliant

Stay Competitive with Affordable Store and Customer Intelligence

Handled by an all-in-one AI Box, DV-1304 delivers actionable customer and store insights to increase sales with the ability to meet any existing COVID or future healthcare guidelines. The AI Box for Retail is a simple add-on appliance compatible with existing IDIS network cameras without AI analytics and DirectIP® NVRs, eliminating the need for complex analytics software and upgrades to edge VA devices.

Users can advantage from an industry-first and cost-free dashboard that integrates up to 32-channels of data. The DV-1304 comes with built-in power sourcing equipment (PSE) so there is no need to add Power over Ethernet (PoE) switches, which can impact on the aesthetics of retail environments and saves on installation costs.





COVID-19 Compliance




Social Distancing
Violation Detection



Crowd Detection



Face Mask Detection



People Counting
Occupancy Monitoring

Business Intelligence



People Counting Count, Track and Analyse

Know exactly how many people come and go. You can find the difference between the estimated and actual floating population. The management and administration through People Counting is essential for places requiring high-level security, such as an airport. Expected number of visitors can be predicted by accumulated data and appropriate action can be made in advance.



Queue Management Line Management and Analysis

Manage your lines and enhance customer satisfaction. Open and close the appropriate amount of counters necessary based on how many customers are in line. Operated by an alarm, this function allows employees to provide quick and accurate service to their waiting customers as well as an efficient internal shift-change system.



Heat Map Visualise Visitor Footfall and Behavior

Highlight where people spend time and what they interact with. This is utilized to determine the best location where exposure needs to be maximised, such as new product zones or areas with sluggish sales. It can also be used to select the best locations for advertisements and promotional materials.

DV-1304	
Model Name	
Key Features	• Powered by the most advanced IDIS Deep-Learning Analytics (IDLA) • People Counting and Occupancy Control • Queue Monitoring • Heatmap • Social Distancing Violation • Mask Rule Violation • Generates real-time event notifications with high accuracy • Live Occupancy Dashboard to maintain capacity limits • Dashboard Reporting for visitor flow, checkout traffic, and compliance adherence • Rapid DirectIP plug-and-play installation • A specialized NDAA-Compliant DirectIP NVR • Supports 4ch IP cameras
SYSTEM	
Video Compression	H.264, H.265
Video Inputs	4 IP Channels
Supported Device	DirectIP NVR
Network Connection	100M Ethernet x 1 (100 Base-TX) with PD 100M Ethernet x 1 (100 Base-TX) with PSE (PSE need Adaptor)
VA Support	People Counting, Occupancy Control, Queue Monitoring, Heatmap, Social Distancing Violation, Mask Rule Violation
MECHANICAL	
Unit Dimension (W x H x D)	200 x 44 x 157.6mm (7.9" x 1.7" x 6.2")
Unit Weight	0.88kg (1.94lb)
ENVIRONMENTAL	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90 %
ELECTRICAL	
Power Input	48V=, PoE
Power Consumption	48V=, 0.8A, 38.4W PoE, IEEE 802.3at (Class 4), 25W DC Output: 48V=, 0.35A MAX
GENERAL	
Approvals	FCC, CE, KC

AI IN THE BOX

ADD-ON 4-CHANNEL SURVEILLANCE AI BOX

DV-1304-A


NDAA
Compliant



Packed with highly accurate, in-house developed AI-powered analytics

The IDIS all-in-one AI Box, DV-1304-A is license free and comes pre-installed with the IDIS Deep Learning Engine that delivers up to 98% accuracy. It packs a punch with all the AI-powered functionality that users need to reduce false alarms and take a proactive approach to strengthening security and safety.

It comes as a simple add-on device compatible with existing IDIS network cameras and recorders, eliminating the need to implement complex analytics software or upgrade to costly edge cameras. Users can leverage their investments in various IDIS camera models by simply connecting the DV-1304-A box to existing NVRs or adopt it as part of a next-gen IDIS end-to-end surveillance solution.



Business Intelligence



In-house developed AI engine (IDIS Deep Learning Engine)

Developed by our own R&D team, the IDIS AI engine is designed to specifically tackle the challenges of security and surveillance operations. By training the IDIS Deep Learning Engine on vast data sets, the AI Box delivers up to 98% accurate alerts and notifications compared to conventional video analytics. This also means that users have the flexibility to configure AI around their own specific security, safety, and other operational needs.



Free yet feature-rich video management

Users can benefit from the industry's only full-featured, free VMS, IDIS Center, that gives users live monitoring, playback, and highly efficient forensic search to speed up investigations.



Low Total Cost of Ownership

No upfront or recurring licenses

Users can take advantage of industry-leading accurate video analytics without any license fees or device connection costs.

Empower your existing cameras

There's no need to buy new AI edge cameras, expensive AI NVRs, or hardware. Reap all the benefits of industry-leading AI functionality, by simply adding the AI Box to your existing IDIS system.

Proactive monitoring and less human error

AI-powered analytics reduce false alarms and eliminate the need to continually monitor multiple video streams that lead to operator fatigue, and events being missed.

DV-1304-A	
Model Name	
Key Features	• Simply connect to a compatible IDIS NVR • Supports 4-channel IP cameras • Supports the most advanced IDIS Deep-Learning Analytics (IDLA) • Supports Object Detection • Supports Intrusion • Supports Loitering • Supports Line Crossing • Supports Face Detection • Supports object detection, intrusion, loitering, line crossing, and face detection rules • Generates real-time event notifications with high accuracy
Video	
Video Inputs	4 IP Channels
Supported Device	DirectIP NVR
VA Support	Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Network	
Video Compression	H.265, H.264
Network Connection	100M Ethernet x 1 (100 Base-TX) with PD 100M Ethernet x 1 (100 Base-TX) with PSE (PSE need Adaptor)
Environmental	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Operating Humidity	0% ~ 90 %
ELECTRICAL	
Power Input	48V=, PoE
Power Consumption	48V=, 0.8A, 38.4W PoE, IEEE 802.3at (Class 4), 25W DC Output: 48V=, 0.35A MAX
MECHANICAL	
Unit Dimension (W x H x D)	200 x 44 x 157.6mm (7.9" x 1.7" x 6.2")
Unit Weight	0.88 kg (1.94lb)
GENERAL	
Approvals	FCC, CE, KC

NETWORK CAMERAS

IDIS Extends Edge AI Camera Lineup for Highly Accurate, Targeted Video Analytics for a Wide Range of Markets

Together these new cameras, powered by the up to 98% accurate IDIS Deep Learning Engine, make it easy for systems integrators and end-users to add transformative video analytics capabilities to any surveillance operation to improve response times to critical events and increase operational efficiency.





NETWORK BOX CAMERA

IDIS LightMaster 2M LightMaster Box Camera

Featuring 2MP LightMaster technology and True WDR, this camera delivers crystal-clear images even in extreme low-light conditions while ensuring robust security reliability through full NDAA compliance.



BOX CAMERAS

Model Name	Box Camera, 5MP	Box Camera, 2MP
	DC-B4501X	DC-B6206XL
	 	 
	IDIS LightMaster NIR	
VIDEO		
Image Sensor	1/2.8" CMOS	1/2" CMOS
Max. Resolution	2592 x 1944	1920 x 1080
Lens Type	C/CS Mount	C/CS Mount
Iris Control	P-iris / DC Auto Iris / Manual Iris	P-iris / DC Auto Iris / Manual Iris
Min. Illumination	Colour: 0.15 lux @ F1.6 B/W: 0.015 lux @ F1.6	Colour: 0.02 lux @ F1.5 B/W: 0.002 lux @ F1.5
Dynamic Range	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)
De-fog	-	-
Video Out	-	-
NETWORK		
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes	Yes
Max. Frame Rate	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	30ips : 1920 x 1080 (WDR)
Supported Resolution	4:3 mode: 2592 x 1944, 1920 x 1440, 1280 x 960, 640 x 480 16:9 mode: 2592 x 1456, 1920 x 1080, 1280 x 720, 640 x 360	1920 x 1080, 1280 x 720, 640 x 360, 352 x 240
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
ALARM AND EVENT		
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	1 (Built In MIC) + 1 / 1	1 (Built In MIC) + 1 / 1
Alarm In / Out	2 / 2	2 / 2
ENVIRONMENTAL		
Vandal Proof Casing	-	-
Outdoor Ready	-	-
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	78 x 63.5 x 150.1mm (3.07" x 2.5" x 5.91")	78 x 63.5 x 142.5mm (3.07" x 2.5" x 5.61")
Weight	0.3kg (0.661lb)	0.4kg (0.891lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 2)	12VDC, PoE, IEEE 802.3af (Class 2)
Power Consumption	12V=, 0.5A, 6W PoE, IEEE 802.3af (Class 2), 5.6W	12V=, 0.43A, 5.16W PoE, IEEE 802.3af (Class 2), 5W
Approval	FCC, CE, KC	FCC, CE, KC, UL

Edge AI Plus Camera Capabilities



The Edge AI Camera Plus Series delivers next-level intelligence that redefines video surveillance efficiency. As part of this new lineup, IDIS introduces three powerful features developed in-house: A-Cut, AI Search, and IDLA Pro — all newly integrated into the Edge AI Camera Plus models.

Together, these innovations dramatically reduce footage review time and elevate situational awareness — enabling operators to concentrate on critical events instead of sorting through endless video. Whether monitoring high-traffic areas or managing large-scale operations, this advanced AI integration provides a clear operational advantage.



DOME CAMERAS

Model Name	AI MFZ, 8MP	AI MFZ, 6MP
	NEW DC-D6831WRA	NEW DC-D6631WRA
	 	 
Image Sensor	1/1.8" CMOS	1/1.8" CMOS
Max. Resolution	3840 x 2160	3328 x 1872
Lens Type	Motorised Vari-focal	Motorised Vari-focal
Focal Length	f = 4.3 ~ 9.8mm	f = 4.3 ~ 9.8mm
Aperture	F1.6 ~ F2.6	F1.6 ~ F2.6
Iris Control	P-Iris	P-Iris
Angular Field of View	Wide: 110.4° (H), 57.8° (V), 133.8° (D) Tele: 45.0° (H), 25.2° (V), 51.8° (D)	Wide: 110.4° (H), 57.8° (V), 133.8° (D) Tele: 45.0° (H), 25.2° (V), 51.8° (D)
Pan / Tilt Range	Pan: -180° ~ 180°, Tilt: -45° ~ 80°, Rotate: -143° ~ 203°	Pan: -180° ~ 180°, Tilt: -45° ~ 80°, Rotate: -143° ~ 203°
Min. Illumination	Colour: 0.13 lux @ F1.6, B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.6, B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	60m / 196.9ft (6ea)	60m / 196.9ft (6ea)
Image Stabilizer	Yes (EIS)	Yes (EIS)
De-fog	Yes	Yes
Video Out	1 CVBS	1 CVBS
Video Compression	H.265, H.264 (MP), MJPEG	H.265, H.264 (MP), MJPEG
Intelligent Video	A-cut Support Object Metadata: Human, Vehicle, Face Object Attribute: Human [Gender, Age, Bag, Hat, Colors], Vehicle [Car, Truck, Bus, Bike (Bicycle, Motorcycle), ETC, Colors], Face [Gender, Age, Glasses, Hat, Mask] IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection IDLA Pro: Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection ETC: Video Motion Detection, Active Tampering Alarm	A-cut Support Object Metadata: Human, Vehicle, Face Object Attribute: Human [Gender, Age, Bag, Hat, Colors], Vehicle [Car, Truck, Bus, Bike (Bicycle, Motorcycle), ETC, Colors], Face [Gender, Age, Glasses, Hat, Mask] IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection IDLA Pro: Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection ETC: Video Motion Detection, Active Tampering Alarm
Audio Compression	Opus, ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	Opus, ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 3840 x 2160 (WDR)	30ips: 3328 x 1872 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection, Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection, Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection
Audio In / Out	1 / 1	1 / 1
Alarm In / Out	1 / 1	1 / 1
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP67	IP67
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	Ø160 x 120mm (Ø6.3" x 4.72")	Ø160 x 120mm (Ø6.3" x 4.72")
Weight	1.1kg (2.4lb)	1.1kg (2.4lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)
Power Consumption	12VDC, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 57VDC, 12W	12VDC, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 57VDC, 12W

DOME CAMERAS

Model Name	MFZ, 8MP	FIXED, 8MP	AI MFZ, 5MP		
	DC-D4831HRX	DC-D4811WRX (3.3mm)	DC-D4548WRA	DC-D4538WRA	DC-D4538RA
	 	 	  IDIS LightMaster NIR	  IDIS LightMaster NIR	  IDIS LightMaster NIR
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	3840 x 2160	3840 x 2160	2592 x 1944	2592 x 1944	2592 x 1944
Lens Type	Motorised Vari-focal	Fixed-focal	Motorised Vari-focal	Motorised Vari-focal	Motorised Vari-focal
Focal Length	f = 2.7 ~ 13.5mm	f = 3.3mm	f = 7 ~ 22mm	f=2.7 ~ 13.5mm	f = 2.7 ~ 13.5mm
Aperture	F1.8 ~ 3F.32	F2.0	F1.4 ~ F2.8	F1.4 ~ F3.2	F1.4 ~ F3.2
Iris Control	DC Iris	Fixed Iris	DC Iris	DC Iris	DC Iris
Angular Field of View	Wide: 110.6° (H), 57.3° (V), 134.1° (D) Tele: 32.6° (H), 18.3° (V), 37.4° (D)	101.3° (H), 54.5° (V), 119.7° (D)	[4:3 mode] Wide: 37.4° (H), 27.5° (V), 48.2° (D) Tele: 15.7° (H), 11.8° (V), 19.6° (D) [16:9 mode] Wide: 37.4° (H), 20.4° (V), 43.6° (D) Tele: 15.7° (H), 8.8° (V), 18° (D)	[4:3 mode] Wide: 101.2° (H), 72.5° (V), 137.4° (D) Tele: 30.4° (H), 22.8° (V), 38° (D) [16:9 mode] Wide: 101.2° (H), 53.3° (V), 121.6° (D) Tele: 30.4° (H), 17° (V), 34.7° (D)	[4:3 mode] Wide: 101.2° (H), 72.5° (V), 137.4° (D) Tele: 30.4° (H), 22.8° (V), 38° (D) [16:9 mode] Wide: 101.2° (H), 53.3° (V), 121.6° (D) Tele: 30.4° (H), 17° (V), 34.7° (D)
Min. Illumination	Colour: 0.2 lux @ F1.8 B/W: 0 lux (IR LED On)	Colour: 0.2 lux @ F2.0 B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.4 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	40m / 131.2ft (6ea)	30m / 98.4ft (4ea)	40m / 131.2ft (6ea)	40m / 131.2ft (6ea)	40m / 131.2ft (6ea)
Image Stabilizer	-	-	-	-	-
De-fog	Yes	Yes	Yes	Yes	Yes
Video Out	-	-	-	-	-
Video Compression	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16 K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 3840 x 2160 15ips: 3840 x 2160 (WDR)	30ips: 3840 x 2160 15ips: 3840 x 2160 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Audio In / Out	1 / 1	1 / 1	1 / 1	1 / 1	1 (Built In MIC)+1 / 1
Alarm In / Out	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Vandal Proof Casing	IK10	IK10	IK10	IK10	IK10
Outdoor Ready	IP67, Heater	IP67	IP67, Heater	IP67, Heater	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø155 x 104.4mm (Ø6.10" x 4.11")	Ø120.6 x 92.9 mm (Ø4.75" x 3.66")	Ø155 x 104.4mm (Ø6.1" x 4.11")	Ø155 x 104.4mm (Ø6.1" x 4.11")	Ø122 x 103.4mm (Ø4.8" x 4.07")
Weight	1.02kg (2.25lb)	0.48kg (1.06lb)	1kg (2.2lb)	1kg (2.2lb)	0.35kg (0.77lb)
Power Source	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)
Power Consumption	12V=, 1.2A, 14.4W PoE, IEEE 802.3af (Class 3), 12.4W	PoE, IEEE 802.3af (Class 3), 9.0W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 10W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 10W	12V=, 1A, 12W PoE, IEEE 802.3af (Class 3), 9.5W

DOME CAMERAS

Model Name	MFZ, 5MP		IR PoE Extender FIXED, 5MP	FIXED, 5MP	
	DC-D4536RX	DC-D4536HRX	DC-D4517RXP (2.8mm, 4.3mm)	DC-D4517RX (2.8mm, 4.3mm)	DC-D4516WRX (2.8mm, 4.0mm)
	 5MP NDAA Compliant	 5MP NDAA Compliant	 IDIS PoE Extender 5MP NDAA Compliant	 5MP NDAA Compliant	 5MP NDAA Compliant
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	2592 x 1944	2592 x 1944	2592 x 1944	2592 x 1944	2592 x 1944
Lens Type	Motorised Vari-focal	Motorised Vari-focal	Fixed-focal	Fixed-focal	Fixed-focal
Focal Length	f = 3.0 ~ 13.5mm	f = 3.0 ~ 13.5mm	f = 2.8mm, f = 4.3mm	f = 2.8mm, f = 4.3mm	f = 2.8mm, f = 4.0mm
Aperture	F1.4 ~ F3.2	F1.4 ~ F3.2	F2.0 (2.8mm), F1.6 (4.3mm)	F2.0 (2.8mm), F1.6 (4.3mm)	F2.0 (2.8mm), F2.15 (4.0mm)
Iris Control	DC Iris	DC Iris	Fixed Iris	Fixed Iris	Fixed Iris
Angular Field of View	[4:3 mode] Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D) [16:9 mode] Wide: 91° (H), 49° (V), 107° (D) Tele: 31° (H), 17° (V), 35° (D)	[4:3 mode] Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D) [16:9 mode] Wide: 91° (H), 49° (V), 107° (D) Tele: 31° (H), 17° (V), 35° (D)	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.2° (V), 123° (D) [4.3mm] 4:3 mode: 80° (H), 56.7° (V), 106.9° (D) 16:9 mode: 80° (H), 41.1° (V), 95.4° (D)	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.2° (V), 123° (D) [4.3mm] 4:3 mode: 80° (H), 56.7° (V), 106.9° (D) 16:9 mode: 80° (H), 41.1° (V), 95.4° (D)	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.1° (V), 122.9° (D) [4.0mm] 4:3 mode: 92° (H), 56.6° (V), 103° (D) 16:9 mode: 79.2° (H), 41.4° (V), 95.1° (D)
Min. Illumination	Colour: 0.15 lux @ F1.4 B/W: 0 lux (IR LED On)	0.15 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.15 lux @ F2.0 B/W: 0 lux (IR LED On) (2.8mm) Colour: 0.15 lux @ F1.6 B/W: 0 lux (IR LED On) (4.3mm)	Colour: 0.15 lux @ F2.0 B/W: 0 lux (IR LED On) (2.8mm) Colour: 0.15 lux @ F1.6 B/W: 0 lux (IR LED On) (4.3mm)	Colour: 0.15 lux @ F2.0 B/W: 0 lux (IR LED On) (2.8mm) Colour: 0.15 lux @ F2.15 B/W: 0 lux (IR LED On) (4.0mm)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	30m / 98.4ft (6ea)	30m / 98.4ft (6ea)	20m / 65.6ft (4ea)	[2.8mm] 20m / 65.6ft (4ea) [4.3mm] 20m / 65.6ft (2ea)	30m / 98.4ft (4ea)
Image Stabilizer	-	-	-	-	-
De-fog	Yes	Yes	Yes	Yes	Yes
Video Out	-	-	-	-	-
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported	Supported	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	-	[2.8mm] ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law [4.3mm] -	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	1 RJ45 (10/100 BASE-T), 1 Additional RJ45 (10/100 BASE-T) for PoE Extender	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	-	-	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Tampering, Trip Zone	Motion Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	1 (Built In MIC) + 1 / 1	1 / 1	-	-	1 / 1
Alarm In / Out	1 / 1	1 / 1	-	-	1 / 1
Vandal Resistance	-	IK10	-	-	IK10
Outdoor Ready	-	IP67, Heater	-	-	IP67
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-10°C ~ 50°C (+14°F ~ 122°F) *Starting up at above 0°C (32°F)	-10°C ~ 50°C (+14°F ~ 122°F) *Starting up at above 0°C (32°F)	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø122.4 x 103.4mm (Ø4.82" x 4.07")	Ø155 x 104.4mm (Ø6.10" x 4.11")	Ø110 x 88mm (Ø4.33" x 3.46")	Ø110 x 88mm (Ø4.33" x 3.46")	Ø120.6 x 92.9mm (Ø4.75" x 3.66")
Weight	0.4kg (0.88lb)	1kg (2.20lb)	0.22kg (0.48lb)	0.22kg (0.44lb)	0.48kg (1.06lb)
Power Source	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3at (Class 4)	PoE IEEE 802.3af (Class 3),	PoE, IEEE 802.3af (Class 3)
Power Consumption	12V=, 1A, 12W PoE, IEEE 802.3af (Class 3), 9.5W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 11W	PoE, IEEE 802.3at (Class 4), 25.5W (DC Out: 42.5 ~ 57V=, 0.3A MAX)	PoE, IEEE 802.3af (Class 3), 7.5W	PoE, IEEE 802.3af (Class 3), 7.6W

TURRET / DOME CAMERAS

Model Name	AI IR FIXED TURRET, 5MP	AI IR TURRET MFZ, 5MP	AI MFZ, 2MP	MFZ, 2MP	AI MFZ, 2MP
	DC-D4512WERA (2.8mm, 4.3mm)	DC-D4532WERA	DC-D4248HRA	DC-D4246WX	DC-D4238HRA
	 IDIS LightMaster NIR   	 IDIS LightMaster NIR   	 IDIS LightMaster NIR   	  	 IDIS LightMaster NIR   
Image Sensor	1/2.8" CMOS	1/2.7" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	2592 x 1944	2592 x 1944	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	Fixed-focal	Motorised Vari-focal	Motorised Vari-focal	Motorised Vari-focal	Motorised Vari-focal
Focal Length	f = 2.8mm, f = 4.3mm	f = 3.2 ~ 10.5mm	f = 7 ~ 22mm	f = 7 ~ 22mm	f = 2.8 ~ 12mm
Aperture	F2.0 (2.8mm), F1.6 (4.3mm)	F1.6 ~ F3.3	F1.4 ~ F2.8	F1.4 ~ F2.8	F1.4 ~ F3.1
Iris Control	Fixed Iris	P-Iris	DC Iris	DC Iris	DC Iris
Angular Field of View	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.2° (V), 123° (D) [4.3mm] 4:3 mode: 80° (H), 56.7° (V), 106.9° (D) 16:9 mode: 80° (H), 41.1° (V), 95.4° (D)	[4:3 mode] Wide: 98.9° (H), 71.1° (V), 133.8° (D) Tele: 28.2° (H), 21.2° (V), 35.3° (D) [16:9 mode] Wide: 98.9° (H), 52.2° (V), 117.9° (D) Tele: 28.2° (H), 15.9° (V), 32.4° (D)	Wide: 40.5° (H), 22° (V), 47.3° (D) Tele: 16.8° (H), 9.5° (V), 19.3° (D)	Wide: 40.5° (H), 22° (V), 47.3° (D) Tele: 16.8° (H), 9.5° (V), 19.3° (D)	Wide: 105.7° (H), 55.3° (V), 126.4° (D) Tele: 34° (H), 19.1° (V), 39.1° (D)
Min. Illumination	Colour: 0.13 lux @ F2.0, B/W: 0 lux (IR LED On) (2.8mm) Colour: 0.13 lux @ F1.6, B/W: 0 lux (IR LED On) (4.3mm)	Colour: 0.13 lux @ F1.6 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0.01 lux @ F1.4	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	30m / 98.4ft (4ea)	50m / 164ft (6ea)	50m / 164ft (6ea)	-	50m / 164ft (6ea)
Image Stabilizer	-	-	-	-	-
De-fog	Yes	Yes	Yes	Yes	Yes
Video Out	-	-	-	-	-
Video Compression	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16 K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	60ips: 1920 x 1080 30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	60ips: 1920 x 1080 30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Audio In / Out	1 (Built In MIC) + 1 / 1	1 (Built In MIC) + 1 / 1	1 / 1	1 / 1	1 / 1
Alarm In / Out	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Vandal Proof Casing	IK10	IK10	IK10	IK10	IK10
Outdoor Ready	IP67	IP67, Heater	IP67, Heater	IP67	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	Ø121 x 78.7mm (Ø4.76" x 3.1")	Ø135 x 98.5mm (Ø5.31" x 3.88")	Ø155 x 104.4mm (Ø6.1" x 4.11")	Ø155 x 105mm (Ø6.1" x 4.13")	Ø155 x 104.4mm (Ø6.1" x 4.11")
Weight	605g (1.3lb)	830g (1.83lb)	0.985kg (2.17lb)	0.985kg (2.17lb)	0.985kg (2.17lb)
Power Source	PoE, IEEE 802.3af (Class 3)	PoE (IEEE 802.3af Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE IEEE 802.3af (Class 3)
Power Consumption	PoE, IEEE 802.3af (Class 3), 7.6W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 11.5W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 8.3W	12V=, 0.64A, 7.7W PoE, IEEE 802.3af (Class 3), 7.8W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 8.3W

DOME CAMERAS

Model Name	MFZ, 2MP				AI FIXED, 2MP
	DC-D4237RX	DC-D4236HRX	DC-D4236WRX	DC-D4236RX	DC-D4218WRA (2.8mm, 4.0mm)
	 Full HD 2MP NDA Compliant	 Full HD 2MP NDA Compliant	 Full HD 2MP NDA Compliant	 Full HD 2MP NDA Compliant	 Full HD 2MP NDA Compliant IDIS LightMaster NIR
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	Motorised Vari-focal	Motorised Vari-focal	Motorised Vari-focal	Motorised Vari-focal	Fixed-focal
Focal Length	f = 2.8 ~ 12mm	f = 2.8 ~ 12mm	f = 2.8 ~ 12mm	f = 2.8 ~ 12mm	f = 2.8mm, f = 4.0mm
Aperture	F1.4 ~ F2.8	F1.4 ~ F2.8	F1.4 ~ F2.8	F1.4 ~ F2.8	F1.6
Iris Control	DC Iris	DC Iris	DC Iris	DC Iris	Fixed Iris
Angular Field of View	Wide: 98° (H), 51° (V), 116° (D) Tele: 33° (H), 19° (V), 38° (D)	Wide: 98° (H), 51° (V), 116° (D) Tele: 33° (H), 19° (V), 38° (D)	Wide: 98° (H), 51° (V), 116° (D) Tele: 33° (H), 19° (V), 38° (D)	Wide: 98° (H), 51° (V), 116° (D) Tele: 33° (H), 19° (V), 38° (D)	[2.8mm] 105.8° (H), 56.4° (V), 121.2° (D) [4.0mm] 87.5° (H), 44.4° (V), 104.9° (D)
Min. Illumination	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.6 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	30m / 98.4ft (6ea)	30m / 98.4ft (6ea)	30m / 98.4ft (6ea)	30m / 98.4ft (6ea)	30m / 98.4ft (4ea)
Image Stabilizer	-	-	-	-	-
De-fog	Yes	Yes	Yes	Yes	Yes
Video Out	-	-	-	1-CVBS	-
Video Compression	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	60ips: 1920 x 1080 30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60 MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD / SDHC / SDXC, Smart Failover (Up to 512 GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Audio In / Out	1 (Built In MIC) + 1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Alarm In / Out	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Vandal Resistance	-	IK10	IK10	-	IK10
Outdoor Ready	-	IP67, Heater	IP67	-	IP67
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-30°C ~ +60°C (-22°F ~ +140°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø122 x 103.4mm (Ø4.8" x 4.07")	Ø155 x 105 mm (Ø6.1" x 4.13")	Ø155 x 105mm (Ø6.1" x 4.13")	Ø122 x 103.4mm (Ø4.8" x 4.07")	Ø120.6 x 92.9mm (Ø4.75" x 3.65")
Weight	0.37kg (0.82lb)	0.99 kg (2.18 lb)	0.985kg (2.17lb)	0.37kg (0.81lb)	0.490kg (1.08lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	12 VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)
Power Consumption	12V=, 0.64A, 7.7W PoE, IEEE 802.3af (Class 3), 7.6W	12V=, 0.95A, 11.4W PoE, IEEE 802.3 af (Class 3), 10.3W	12V=, 0.64A, 7.7W PoE, IEEE 802.3af (Class 3), 7.8W	12 V=, 0.64A, 7.7W PoE, IEEE 802.3af (Class 3), 7.6W	PoE, IEEE 802.3af (Class 3), 8W

DOME CAMERAS

Model Name	FIXED, 2MP			Micro Dome, FIXED, 2MP
	DC-D4217RX (2.8mm, 4.0mm)	DC-D4216WRX (2.8mm)	DC-D4216RX (2.8mm, 4.0mm)	DC-D4211CRX
	 	 	 	 
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	Fixed-focal	Fixed-focal	Fixed-focal	Fixed-focal
Focal Length	f = 2.8mm, f = 4.0mm	f = 2.0	f = 2.8mm, f = 4.0mm	f = 2.8
Aperture	F2.0 (2.8 mm), F1.6 (4.0mm)	F2.0 (2.8mm), F1.6 (4.0mm)	F2.0 (2.8mm), F1.6 (4.0mm)	F2.0
Iris Control	Fixed Iris	Fixed Iris	Fixed Iris	Fixed Iris
Angular Field of View	[2.8mm] 111.6° (H), 61.45° (V), 127.3° (D) [4.0mm] 87.4° (H), 46.9° (V), 103.5° (D)	111.6° (H), 61.45° (V), 127.3° (D)	[2.8mm] 111.6° (H), 61.45° (V), 127.3° (D) [4.0mm] 87.4° (H), 46.9° (V), 103.5° (D)	113.74° (H), 61.5° (V), 134.5° (D)
Min. Illumination	Colour: 0.1 lux @ F2.0 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F2.0 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F2.0 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F2.0 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	[2.8mm] 20m / 65.6ft (4ea) [4.0mm] 20m / 65.6ft (2ea)	30m / 98.4ft (4ea)	30m / 98.4ft (4ea)	15m / 49.2ft (1ea)
Image Stabilizer	-	-	-	-
De-fog	Yes	Yes	Yes	-
Video Out	-	-	-	-
Video Compression	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported	Supported	Supported	Supported
Audio Compression	-	-	-	-
Max. Frame Rate	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	-	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	-
Trigger Event	Motion Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Tampering, Trip Zone
Audio In / Out	-	1 / 1	1 (Built In MIC)+1 / 1	-
Alarm In / Out	-	1 / 1	1 / 1	-
Vandal Proof Casing	-	IK10	-	-
Outdoor Ready	-	IP67	-	-
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø130 x 81.4mm (5.2"x 3.2")	Ø120.6 x 92.9mm (Ø4.75" x 3.65")	Ø110 x 88mm (Ø4.33" x 3.46")	Ø86 x 59mm (Ø3.39" x 2.32")
Weight	0.242kg (0.53lb)	0.465kg (1.02lb)	0.26kg (0.57lb)	0.10kg (0.1lb)
Power Source	PoE, IEEE 802.3af (Class 2)	PoE, IEEE 802.3af (Class 2)	PoE, IEEE 802.3af (Class 2)	PoE, IEEE 802.3af (Class 2)
Power Consumption	PoE, IEEE 802.3af (Class 2), 3.8W	PoE, IEEE 802.3af (Class 2), 4.6 W	PoE, IEEE 802.3af (Class 2), 4.6W	PoE, IEEE 802.3af (Class 2), 3.6W

Model Name	AI MICRO VANDAL FIXED, 5MP	
	DC-D2511FCR	
	 5MP	
Image Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor	
Max. Resolution	2704 x 2104	
Scanning Mode	Progressive Scan	
Lens Type	Fixed Lens	
Focal Length	f = 4.0mm (Optional 2.8mm)	
Aperture	F1.6	
Iris Control	Fixed	
Angular Field of View	[2.8mm] 134.45° (D), 113.74° (H), 61.5° (V)	
	[4.0mm] 104.9° (D), 87.5° (H), 44.4° (V)	
Electronic Shutter Speed	Min. 1/100,000 sec ~ Max. 1/2 sec	
Day and Night Mode	Auto / Day (Colour) / Night (BW) / External	
IR Distance	20m	
Auto White Balance Mode	Automatic, Manual	
Noise Reduction	2DNR / 3DNR	
Backlight Correction	True WDR	
Video Compression	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	
SDK Support	API, ONVIF Profile S/T Compliant	
Video Frame Rate	Up to 30fps @ 2592 x 1944p	
Video Resolution	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 800 x 600, 640 x 480, 480 x 360	
Video Streaming (3 Streaming)	Simultaneously H.265 and MJPEG (Multi Streaming) or Simultaneously H.264 and MJPEG (Multi Streaming) Independent Frame Rate and Bandwidth Control, VBR/CBR Mode	
Protocols	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	
Security	Multi User Authority, IP Filtering, HTTPS	
Ethernet	RJ45 (10/100 BASE-T)	
Trigger Event	Onboot, Trigger, Network Loss, Motion, AI Event	
Event Out Notification	Network	
Audio In/Out	Line-In / Line-Out	
Alarm In/Out	Alarm in 1 / Alarm Out 1	
AI	Motion, Human Detection, Vehicle Detection	
Vandal Proof Casing	IK08	
Outdoor Ready	IP67	
Operating Temperature	-20°C ~ +50°C	
Dimensions (W x H x D)	Ø94 x 25mm (Ø3.77" x 0.98")	
Power Source	PoE, IEEE, 802.3af (Class 2), DC12V	
Power Consumption	Max 4.0W	



IDIS Micro Vandal


5MP AI Micro Vandal Dome Camera

The combination of 5MP high resolution and a SONY Starvis sensor ensures superior image quality and visibility, day or night. Specialized AI object detection for humans and vehicles minimizes false alarms and enhances surveillance precision.

A-Cut: Smart Cropped Images Through Object Tracking



To address these issue, IDIS has developed an AI-powered technology called A-Cut, which tracks detected objects in video footage. It automatically extracts the most representative scenes for each object and provides them as cropped images. A-Cut transforms how you monitor and review video footage. For every detected object in the video stream, a representative cropped image is automatically generated—making it easy to identify object types and characteristics at a glance. Clicking on any image instantly navigates you to the precise moment that object appeared, giving you fast, intuitive access to key events.



BULLET CAMERAS

Model Name	AI MFZ, 8MP	AI MFZ, 6MP
	NEW DC-T6831WRA	NEW DC-T6631WRA
	 	 
Image Sensor	1/1.8" CMOS	1/1.8" CMOS
Max. Resolution	3840 x 2160	3328 x 1872
Lens Type	Motorised Vari-focal	Motorised Vari-focal
Focal Length	f = 4.3 ~ 9.8mm	f = 4.3 ~ 9.8mm
Aperture	F1.6 ~ F2.6	F1.6 ~ F2.6
Iris Control	P-Iris	P-Iris
Angular Field of View	Wide: 110.4° (H), 57.7° (V), 133.8° (D) Tele: 45° (H), 25.2° (V), 51.8° (D)	Wide: 110.4° (H), 57.7° (V), 133.8° (D) Tele: 45° (H), 25.2° (V), 51.8° (D)
Min. Illumination	Colour: 0.13 lux @ F1.6 B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.6 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	60m / 196.9ft (6ea)	60m / 196.9ft (6ea)
Image Stabilizer	Yes (EIS)	Yes (EIS)
De-fog	Yes	Yes
Intelligent Video	A-cut Support Object Metadata: Human, Vehicle, Face Object Attribute: Human [Gender, Age, Bag, Hat, Colors], Vehicle [Car, Truck, Bus, Bike (Bicycle, Motorcycle), ETC, Colors], Face [Gender, Age, Glasses, Hat, Mask] IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection IDLA Pro: Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection ETC: Video Motion Detection, Active Tampering Alarm	A-cut Support Object Metadata: Human, Vehicle, Face Object Attribute: Human [Gender, Age, Bag, Hat, Colors], Vehicle [Car, Truck, Bus, Bike (Bicycle, Motorcycle), ETC, Colors], Face [Gender, Age, Glasses, Hat, Mask] IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection IDLA Pro: Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection ETC: Video Motion Detection, Active Tampering Alarm
Video Out	1 CVBS	1 CVBS
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported	Supported
Audio Compression	Opus, ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	Opus, ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 3328 x 1872(WDR)	30ips: 3840 x 2160 (WDR)
Ethernet	RJ45 (10/100BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection, Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection, Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection
Audio In / Out	1 / 1	1 / 1
Alarm In / Out	1 / 1	1 / 1
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP67, Heater	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	89.3 x 89.3 x 311.2mm (3.52" x 3.52" x 12.25")	89.3 x 89.3 x 311.2mm (3.52" x 3.52" x 12.25")
Weight	1.95kg (4.30lb)	1.95kg (4.30lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)
Power Consumption	12VDC, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 57VDC, 12W	12VDC, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 57VDC, 12W

BULLET CAMERAS

Model Name	MFZ, 8MP	FIXED, 8MP	MFZ, 5MP	MFZ, 5MP
	DC-T4831HRX	DC-T4811WRX (3.3mm)	DC-T4538WRA	DC-T4536HRX
	 	 	  IDIS LightMaster NIR	 
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	3840 x 2160	3840 x 2160	2592 x 1944	2592 x 1944
Lens Type	Motorised Vari-focal	Fixed-focal	Motorised Vari-focal	Motorised Vari-focal
Focal Length	f = 2.7 ~ 13.5mm	f = 3.3mm	f = 2.7 ~ 13.5mm	f = 3.0 ~ 13.5mm
Aperture	F1.8 ~ F3.32	F2.0	F1.4 ~ F3.2	F1.4 ~ F3.2
Iris Control	DC Iris	Fixed Iris	DC Iris	DC Iris
Angular Field of View	Wide: 110.6° (H), 57.3° (V), 134.1° (D) Tele: 32.6° (H), 18.3° (V), 37.4° (D)	101.3° (H), 54.5° (V), 119.7° (D)	[4:3 mode] Wide: 101.2° (H), 72.6° (V), 137.4° (D) Tele: 30.4° (H), 22.8° (V), 38° (D) [16:9 mode] Wide: 101.7° (H), 53.3° (V), 121.6° (D) Tele: 30.2° (H), 17° (V), 34.7° (D)	[4:3 mode] Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D) [16:9 mode] Wide: 91° (H), 49° (V), 107° (D) Tele: 31° (H), 17° (V), 35° (D)
Min. Illumination	Colour: 0.2 lux @ F1.8 B/W: 0 lux (IR LED On)	Colour: 0.2 lux @ F2.0 B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.15 lux @ F2.0 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	40m / 131.2ft (6ea)	30m / 98.4ft (4ea)	40m / 131.2ft (6ea)	30m / 98.4ft (6ea)
Image Stabilizer	-	-	-	-
De-Fog	Yes	Yes	Yes	Yes
Video Out	-	-	-	-
Video Compression	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG
Intelligent Codec	Supported	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 3840 x 2160 15ips: 3840 x 2160 (WDR)	30ips: 3840 x 2160 15ips: 3840 x 2160 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm /in, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	1 / 1	1 / 1	1 / 1	1 / 1
Alarm In / Out	1 / 1	1 / 1	1 / 1	1 / 1
Vandal Proof Casing	IK10	IK10	IK10	IK10
Outdoor Ready	IP67, Heater	IP67	IP67, Heater	IP67, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-20°C ~ +55°C (-22°F ~ +131°F) *Starting up at above 0°C (32°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	80 x 75 x 237 mm (3.15" x 2.95" x 9.33")	75 x 70 x 195.8mm (2.95" x 2.75" x 7.7")	89.3 x 89.3 x 277.6mm (3.52" x 3.52" x 10.93")	80 x 75 x 237mm (3.15" x 2.95" x 9.33")
Weight	1.01kg (2.22lb)	0.66kg (1.46lb)	1.293kg (2.85lb)	1.01kg (2.22lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)
Power Consumption	12V= 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 11.7W	PoE, IEEE 802.3af (Class 3), 9.0W	12V=, 1A, 12W PoE, IEEE 802.3af (Class 3), 9.7W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 11W

BULLET CAMERAS

Model Name	FIXED, 5MP		
	DC-T4517WRXP-A (2.8mm, 4.3mm, 6.2mm)	DC-T4517WRX-A (2.8mm, 4.3mm, 6.2mm)	DC-T4516WRX (2.8mm, 4.0mm, 6.0mm)
	 5MP NDA Compliant IDIS PoE Extender	 5MP NDA Compliant	 5MP NDA Compliant
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	2592 x 1944	2592 x 1944	2592 x 1944
Lens Type	Fixed-focal	Fixed-focal	Fixed-focal
Focal Length	f = 2.8mm, f = 4.3mm, f = 6.2mm	f = 2.8mm, f = 4.3mm, f = 6.2mm	f = 2.8mm, f = 4.0mm, f = 6.0mm
Aperture	F1.6	F1.6	F2.0 (2.8mm), F2.15 (4.0mm), F1.6 (6.0mm)
Iris Control	Fixed Iris	Fixed Iris	Fixed Iris
Angular Field of View	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.2° (V), 123° (D) [4.3mm] 4:3 mode: 80° (H), 56.7° (V), 106.9° (D) 16:9 mode: 80° (H), 41.1° (V), 95.4° (D) [6.2mm] 4:3 mode: 49.9° (H), 36.7° (V), 64° (D) 16:9 mode: 49.9° (H), 27.2° (V), 58.1° (D)	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.2° (V), 123° (D) [4.3mm] 4:3 mode: 80° (H), 56.7° (V), 106.9° (D) 16:9 mode: 80° (H), 41.1° (V), 95.4° (D) [6.2mm] 4:3 mode: 49.9° (H), 36.7° (V), 64° (D) 16:9 mode: 49.9° (H), 27.2° (V), 58.1° (D)	[2.8mm] 4:3 mode: 104.8° (H), 76.9° (V), 130° (D) 16:9 mode: 104.8° (H), 57.1° (V), 122.9° (D) [4.0mm] 4:3 mode: 79.2° (H), 56.6° (V), 103° (D) 16:9 mode: 79.2° (H), 41.4° (V), 95.1° (D) [6.0mm] 4:3 mode: 49.9° (H), 37° (V), 63.6° (D) 16:9 mode: 49.9° (H), 27.6° (V), 57.8° (D)
Min. Illumination	Colour: 0.15 lux @ F2.0, B/W: 0 lux (IR LED On)	[2.8mm] Colour: 0.15 lux @ F2.0 B/W: 0 lux (IR LED On) [4.3mm] Colour: 0.15 lux @ F1.6 B/W: 0 lux (IR LED On) [6.2mm] Colour: 0.15 lux @ F1.6 B/W: 0 lux (IR LED On)	[2.8mm] Colour: 0.15 lux @ F2.0, B/W: 0 lux (IR LED On) [4.0mm] Colour: 0.15 lux @ F2.15, B/W: 0 lux (IR LED On) [6.0mm] Colour: 0.15 lux @ F2.15, B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	20m / 65.6ft (2ea)	20m / 65.6ft (2ea)	30m / 98.4ft (4ea)
Image Stabilizer	-	-	-
De-Fog	Yes	Yes	Yes
Video Out	-	-	-
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP) M-JPEG,
Intelligent Codec	Supported	Supported	Supported
Audio Compression	-	-	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)
Ethernet	1 RJ45 (10/100 BASE-T), 1 Additional RJ45 (10/100 BASE-T) for PoE Extender	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	-	-	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Tampering, Trip Zone	Motion Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	-	-	1 / 1
Alarm In / Out	-	-	1 / 1
Vandal Proof Casing	IK10	IK10	IK10
Outdoor Ready	IP66	IP 66	IP67
Operating Temperature	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	70 x 65 x 197.5mm (2.76" x 2.56" x 7.78")	70 x 65 x 197.5mm (2.76" x 2.56" x 7.78")	75 x 70 x 195.8mm (2.95" x 2.75" x 7.71")
Weight	0.44kg (0.97lb)	0.4kg (0.88lb)	0.66kg (1.46lb)
Power Source	PoE, IEEE 802.3at (Class 4)	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)
Power Consumption	PoE, IEEE 802.3at (Class 4), 6.5W	PoE, IEEE 802.3af (Class 3), 25.5W	PoE, IEEE 802.3af (Class 3), 7.9W

BULLET CAMERAS

Model Name	AI MFZ, 2MP		AI Fixed Focal, 2MP
	DC-T4238HRA	DC-T4248HRA	DC-T4218WRA (2.8mm, 4.0mm)
	   	   	   
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	Motorised Vari-focal	Motorised Vari-focal	Fixed-focal
Focal Length	f = 2.8 ~ 12mm	f = 7 ~ 22mm	f = 2.8mm, f = 4.0mm
Aperture	F1.4 ~ F3.1	F1.4 ~ F2.8	F1.6
Iris Control	DC Iris	DC Iris	Fixed Iris
Angular Field of View	Wide: 105.7° (H), 55.3° (V), 126.4° (D) Tele: 34° (H), 19.1° (V), 39.1° (D)	Wide: 40.5° (H), 22° (V), 47.3° (D) Tele: 16.8° (H), 9.5° (V), 19.3° (D)	[2.8mm] 105.8° (H), 56.4° (V), 121.2° (D) [4.0mm] 87.5° (H), 44.4° (V), 104.9° (D)
Min. Illumination	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.6 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	50m / 164ft (6ea)	50m / 164ft (6ea)	30m / 98.4ft (4ea)
Image Stabilizer	-	-	-
De-Fog	Yes	Yes	Yes
Video Out	-	-	-
Video Compression	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP) M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	60ips: 1920 x 1080 30ips: 1920 x 1080 (WDR)	60ips: 1920 x 1080 30ips: 1920 x 1080 (WDR)	60ips: 1920 x 1080 30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Audio In / Out	1 / 1	1 / 1	1 / 1
Alarm In / Out	1 / 1	1 / 1	1 / 1
Vandal Proof Casing	IK10	IK10	IK10
Outdoor Ready	IP67, Heater	IP67, Heater	IP67
Operating Temperature	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	89.3 x 89.3 x 277.6mm (3.52" x 3.52" x 10.93")	89.3 x 89.3 x 277.6mm (3.52" x 3.52" x 10.93")	81.5 x 75 x 200.5mm (3.21" x 2.95" x 7.89")
Weight	1.293kg (2.85lb)	1.293kg (2.85lb)	0.75kg (1.65lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)
Power Consumption	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 8.3W	12V=, 1.1A, 13.2W PoE, IEEE 802.3af (Class 3), 8.3W	PoE, IEEE 802.3af (Class 3), 8.2W

BULLET CAMERAS

Model Name	MFZ, 2MP		FIXED, 2MP	
	DC-T4236HRX	DC-T4236WRX	DC-E4216WRX (2.8mm)	DC-T4217WRX (2.8mm, 4.0mm, 6.0mm)
	 	 	 	 
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	Motorised Vari-focal	Motorised Vari-focal	Fixed-focal	Fixed-focal
Focal Length	f = 2.8 ~ 12mm	f = 2.8 ~ 12mm	f = 2.8mm	f = 2.8mm, f = 4.0mm, f = 6.0mm
Aperture	F1.4 ~ F2.8	F1.4 ~ F2.8	F2.0	F2.0 (2.8mm), F1.6 (4.0mm), F1.6 (6.0mm)
Iris Control	DC Iris	DC Iris	Fixed Iris	Fixed Iris
Angular Field of View	Wide: 98° (H), 51° (V), 116° (D) Tele: 33° (H), 19° (V), 38° (D)	Wide: 98° (H), 51° (V), 116° (D) Tele: 33° (H), 19° (V), 38° (D)	111.6° (H), 61.5° (V), 127.3° (D)	[2.8mm] 111.6° (H), 61.45° (V), 127.3° (D) [4.0mm] 87.4° (H), 46.9° (V), 103.5° (D) [6.0mm] 53.5°(H), 29.5°(V), 62.1°(D)
Min. Illumination	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F1.4 B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F2.0 B/W: 0 lux (IR LED On)	[2.8mm] Colour: 0.1 lux @ F2.0, B/W: 0 lux (IR LED On) [4.0mm] Colour: 0.07 lux @ F1.6, B/W: 0 lux (IR LED On) [6.0mm] Colour: 0.07 lux @ F1.6, B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	30m / 98.4ft (6ea)	30m / 98.4ft (6ea)	30m / 98.4ft (4ea)	20m / 65.6ft (2ea)
Image Stabilizer	-	-	-	-
De-Fog	Yes	Yes	Yes	Yes
Video Out	-	-	-	-
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP) M-JPEG,	H.265, H.264 (MP) M-JPEG,
Intelligent Codec	Supported	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	-
Max. Frame Rate	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	-
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Tampering, Trip Zone
Audio In / Out	1 / 1	1 / 1	1 / 1	-
Alarm In / Out	1 / 1	1 / 1	1 / 1	-
Vandal Proof Casing	IK10	IK10	IK10	IK 10
Outdoor Ready	IP67, Heater	IP67	IP67	IP 66
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)	-20°C ~ +55°C (-4°F ~ +131°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø77 x 244.1mm (Ø3" x 9.61")	Ø77 x 244.1mm (Ø3.0" x 9.61")	75 x 70 x 195.8mm (2.95" x 2.75" x 7.7")	70 x 65 x 182.7mm (2.75" x 2.56" x 7.2")
Weight	0.84kg (1.85lb)	0.84kg (1.85lb)	0.655kg (1.44lb)	0.340kg (0.75lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 2)	PoE, IEEE 802.3af (Class 2)
Power Consumption	12V=, 0.78A, 9.3W PoE, IEEE 802.3af (Class 3), 8.5W	12V=, 0.78A, 9.3W PoE, IEEE 802.3af (Class 3), 8.5W	PoE, IEEE 802.3af (Class 2), 6.1W	PoE, IEEE 802.3af (Class 2), 5.4W

IDIS SUPER FISHEYE CAMERA

Dual Side Dewarping
Mobile Dewarping
Smooth Dewarping

Introducing the IDIS Super Fisheye, featuring groundbreaking dual side dewarping, outstanding panoramic image quality and fast, simple plug-and-play installation to deliver the ultimate in surveillance efficiency and performance.



Model Name	Fixed Focal, 12MP	Fixed Focal, 5MP	
	DC-Y6C16WRX	DC-Y6516WRX	DC-Y6516X
	 	 	 
Image Sensor	1/2.3" 12MP CMOS	1/1.8" CMOS	1/1.8" CMOS
Max. Resolution	2944 x 2944	2560 x 2048	2560 x 2048
Lens Type	Fixed-focal	Fixed-focal	Fixed-focal
Focal Length	f = 1.6mm	f = 1.5mm	f = 1.5mm
Aperture	F 2.0	F1.8	F1.8
Iris Control	Fixed Iris	Fixed Iris	Fixed Iris
Angular Field of View	180° (H), 180° (V), 180° (D)	180° (H), 180° (V), 180° (D)	180° (H), 180° (V), 180° (D)
Min. Illumination	Colour: 0.3 lux @ F2.0 B/W: 0 lux (IR LED On)	Colour: 0.15 lux @ F1.8 B/W: 0 lux (IR LED On)	Colour: 0.15 lux @ F1.8 B/W: 0.015 lux @ F1.8
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	15m / 49.2ft (4ea)	20m / 65.6ft (4ea)	-
De-fog	Yes	Yes	Yes
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone, Heatmap	Video Motion Detection, Active Tampering Alarm, Trip Zone, Heatmap	Video Motion Detection, Active Tampering Alarm, Trip Zone, Heatmap
Viewing Composition	1O, 1P, 1P2R, 2P, 4R, 1O7R	1O, 1P, 1P2R, 2P, 4R, 1O7R	1O
Video Out	-	-	-
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 2944 x 2944 15ips: 2944 x 2944 (WDR)	30ips: 2560 x 2048 (WDR)	30ips: 2560 x 2048 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone, Heatmap	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone, Heatmap	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone, Heatmap
Audio In / Out	1 (Built In MIC) +1 / 1	1 (Built In MIC) +1 / 1	1 (Built In MIC) +1 / 1
Alarm In / Out	1 / 1	1 / 1	1 / 1
Vandal Resistance	IK10	IK10	-
Outdoor Ready	IP67	IP67	-
Operating Temperature	-30°C ~ 50°C (22°F ~ 122°F) *Starting up at above 0°C (32°F)	-30°C ~ 50°C (-22°F ~ 122°F) *Starting up at above 0°C (32°F)	-10°C ~ 50°C (-22°F ~ 122°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø135 x 56.9mm (Ø5.31" x 2.24")	Ø135 x 56.9mm (Ø5.31" x 2.24")	Ø122 x 35.8mm (Ø4.80" x 1.40")
Weight	0.67kg (1.47lb)	0.67kg (1.47lb)	0.280kg (0.62lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	12VDC, PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3 af (Class 2)
Power Consumption	12V=, 0.94A, 11.3W PoE, IEEE 802.3af (Class 3), 10.6W	12V=, 0.92A, 11W PoE, IEEE 802.3af (Class 3), 10.3W	PoE, IEEE 802.3af (Class 2), 5.6W

EDGE AI PLUS PTZ CAMERA

AI Detect. Auto-Follow. Stay Assured.

EDGE AI PLUS PTZ cameras detect critical events as they happen, accurately classify objects, and automatically track real threats across the scene without interruption.



SPEED DOME CAMERAS

Model Name	AI AF Zoom, 8MP, 40x	AI AF Zoom, 6MP, 40x
	NEW DC-S6883WRA	NEW DC-S6683WRA
	  	  
Image Sensor	1/1.8" CMOS	1/1.8" CMOS
Max. Resolution	3840 x 2160	3328 x 1872
Lens Type	AF Zoom Lens	AF Zoom Lens
Focal Length	f = 6.5 ~ 260mm	f = 6.5 ~ 260mm
Aperture	F1.69 ~ F4.92	F1.69 ~ F4.92
Iris Control	P-Iris	P-Iris
Angular Field of View	Wide: 64.6° (H), 38.4° (V), 72.2° (D) Tele: 1.79° (H), 1.00° (V), 2.08° (D)	Wide: 64.6° (H), 38.4° (V), 72.2° (D) Tele: 1.79° (H), 1.00° (V), 2.08° (D)
Min. Illumination	Colour: 0.13 lux @ F1.69 B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.69 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)
IR Distance (LEDs)	400m / 1,312.3ft (2ea)	400m / 1,312.3ft (2ea)
Image Stabilizer	Yes (EIS)	Yes (EIS)
De-fog	Yes	Yes
Intelligent Video	AI Auto Tracking A-cut Support Object Metadata: Human, Vehicle, Face Object Attribute: Human [Gender, Age, Bag, Hat, Colors], Vehicle [Car, Truck, Bus, Bike (Bicycle, Motorcycle), ETC, Colors], Face [Gender, Age, Glasses, Hat, Mask] IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection IDLA Pro: Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection ETC: Video Motion Detection, Active Tampering Alarm	AI Auto Tracking A-cut Support Object Metadata: Human, Vehicle, Face Object Attribute: Human [Gender, Age, Bag, Hat, Colors], Vehicle [Car, Truck, Bus, Bike (Bicycle, Motorcycle), ETC, Colors], Face [Gender, Age, Glasses, Hat, Mask] IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection IDLA Pro: Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection ETC: Video Motion Detection, Active Tampering Alarm
Video Out	1 Terminal Block	1 Terminal Block
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes	Yes
Audio Compression	Opus, ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	RJ45 (10/100 BASE-T)
Max. Frame Rate	30ips: 3840 x 2160 (WDR)	30ips: 3328 x 1872 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection, Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection, Crowd Detection, Abandoned Object Detection, Removed Object Detection, Fall Detection
Audio In / Out	1 / 1	1 / 1
Alarm In / Out	8 / 2	8 / 2
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP66, NEMA4X	IP66, NEMA4X
Operating Temperature	IR LED OFF: -40°C ~ +55°C (-40°F ~ +131°F) IR LED ON: -40°C ~ +40°C (-40°F ~ +104°F) *Starting up at above -20°C (-4°F)	IR LED OFF: -40°C ~ +55°C (-40°F ~ +131°F) IR LED ON: -40°C ~ +40°C (-40°F ~ +104°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	Ø242 x 401.8mm (Ø9.52" x 15.82")	Ø242 x 401.8mm (Ø9.52" x 15.82")
Weight	7.46kg (16.44lb)	7.46kg (16.44lb)
Power Source	24VAC, PoE, IEEE 802.3bt (Class 8)	24VAC, PoE, IEEE 802.3bt (Class 8)
Power Consumption	HEATER, IR OFF: 24V~, 2.0A, 36.4W, 50/60Hz, PoE, IEEE 802.3bt (Class 8), 34.8W HEATER, IR ON: 24V~, 3.0A, 55.9W, 50/60Hz, PoE, IEEE 802.3bt (Class 8), 55.7W	HEATER, IR OFF: 24V~, 2.0A, 36.4W, 50/60Hz, PoE, IEEE 802.3bt (Class 8), 34.8W HEATER, IR ON: 24V~, 3.0A, 55.9W, 50/60Hz, PoE, IEEE 802.3bt (Class 8), 55.7W

SPEED DOME CAMERAS

	AF Zoom, 8MP, 31x	AF Zoom, 6MP, 31x
	DC-S6882WR	DC-S6682WR
Model Name	 	 
Image Sensor	1/1.8" CMOS	1/1.8" CMOS
Max. Resolution	3840 x 2160	3328 x 1872
Lens Type	AF Zoom Lens	AF Zoom Lens
Focal Length	f = 6.91 ~ 214.64mm	f = 6.91 ~ 214.64mm
Aperture	F1.36 ~ F4.6	F1.36 ~ F4.6
Iris Control	P-Iris	P-Iris
Angular Field of View	Wide: 61.8° (H), 36.3° (V), 70.3° (D) Tele: 2.3° (H), 1.3° (V), 2.6° (D)	Wide : 61.8°(H), 36.3°(V), 70.3°(D) Tele : 2.3°(H), 1.3°(V), 2.6°(D)
Min. Illumination	Colour : 0.13 lux @ F1.36 B/W : 0 lux (IR LED On)	Colour: 0.13 lux @ F1.36 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)
IR Distance (LEDs)	300m / 984.3ft (2 ea)	300m / 984.3ft (2ea)
Image Stabilizer	Yes (EIS)	Yes (EIS)
De-fog	Yes	Yes
Auto Tracking	-	-
Video Out	1 Terminal Block	1 Terminal Block
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 3840 x 2160 (WDR)	30ips: 3328 x 1872 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD / SDHC / SDXC, Smart Failover (Up to 512 GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone, System Status	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone, System Status
Audio In / Out	1 / 1	1 / 1
Alarm In / Out	8 / 2	8 / 2
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP66, Heater	IP66, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	Ø242.0 x 401.8mm (Ø9.52" x 15.82")	Ø242 x 401.8mm (Ø9.52" x 15.82")
Weight	7.4kg (16.31lb)	7.4kg (16.31lb)
Power Source	24VAC, PoE, IEEE 802.3bt (Class 8)	24VAC, PoE, IEEE 802.3bt (Class 8)
Power Consumption	HEATER, IR LED OFF 24VAC, 1.6A, 28.0W, 50/60Hz PoE, IEEE 802.3bt (Class 8), 28.4W HEATER, IR LED ON 24VAC, 2.8A, 52.9W, 50/60Hz PoE, IEEE 802.3bt (Class 8), 53.1W	HEATER, IR LED OFF 24VAC, 1.6A, 28.0W, 50/60Hz PoE, IEEE 802.3bt (Class 8), 28.4W HEATER, IR LED ON 24VAC, 2.8A, 52.9W, 50/60Hz PoE, IEEE 802.3bt (Class 8), 53.1W

SPEED DOME CAMERAS

Model Name	AF Zoom, 4MP, 36x	AF Zoom, 2MP, 36x
	DC-S6481HRA	DC-S6286HRL
	   	  
Image Sensor	1/1.8" CMOS	1/2" CMOS
Max. Resolution	2688 X 1520	1920 x 1080
Lens Type	AF Zoom Lens	AF Zoom Lens
Focal Length	f = 6.91 ~ 248.76mm	f = 6 ~ 216mm
Aperture	F1.35 ~ F4.6	F1.36 ~ F4.6
Iris Control	P-Iris	DC Iris (Hall Sensor)
Angular Field of View	Wide: 61.8° (H), 36.3° (V), 70.3° (D) Tele: 2.4° (H), 1.3° (V), 2.7° (D)	Wide: 57.36° (H), 33.12° (V), 65.18° (D) Tele: 1.92° (H), 1.08° (V), 2.2° (D)
Min. Illumination	Colour: 0.06 lux @ F1.35 B/W: 0 lux (IR LED On)	Colour: 0.02 lux @ F1.36 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)
IR Distance (LEDs)	400m / 1,312.3ft (2ea)	350m / 1,148.2ft (2ea)
Image Stabilizer	Yes (EIS)	Yes (EIS)
De-fog	Yes	Yes
Auto Tracking	Yes	-
Video Out	1 Terminal Block	1 Terminal Block
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 2688 x 1520 (WDR)	30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLT5rec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	1 / 1	1 / 1
Alarm In / Out	8 / 2	8 / 2
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP66, Heater	IP66, Heater
Operating Temperature	-40°C ~ +55°C (-40°F ~ +140°F) *Starting up at above -20°C (-4°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)
Dimensions (W x H x D)	Ø242 x 401.8mm (Ø9.52" x 15.82")	Ø242 x 401.8mm (Ø9.52" x 15.82")
Weight	7.2kg (15.87lbs)	6.7kg (14.77lb)
Power Source	24VAC, PoE, IEEE 802.3bt (Class 8)	24VAC, High-PoE (75W)
Power Consumption	HEATER, IR OFF 24V~, 1.5A, 27.1W, PoE, IEEE 802.3bt (Class 8), 26.4W HEATER, IR ON 24V~, 2.8A, 52.9W, PoE, IEEE 802.3bt (Class 8), 54.2W	HEATER, IR OFF 24V~, 1.6A, 26.2W, 50/60Hz, High-PoE, 50 ~ 57V, 23.6W HEATER, IR ON 24V~, 2.3A, 39.6W, 50/60Hz, High-PoE, 50 ~ 57V, 35.6W

IDIS Edge AI Cameras



4MP

AI Speed Dome Camera DC-S6481HRA

IDIS LightMaster NIR



PTZ AI Tracking

PTZ AI Tracking Events introduces innovative technology to seamlessly track individuals or manually selected targets across predefined lines.

SPEED DOME CAMERAS

	Mini AF Zoom, 2MP, 12x	MFZ, 2MP, 30x	MFZ, 2MP, 30x Flush
	DC-S6261X	DC-S6281HX	DC-S6281FX
Model Name	 	 	 
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	AF Zoom Lens	AF Zoom Lens	AF Zoom Lens
Focal Length	f = 5.3 ~ 64mm	f = 5.2 ~ 156mm	f = 5.2 mm ~ 156 mm
Aperture	F1.6 ~ F2.8	F1.33 ~ F4.95	F1.33 ~ F4.95
Iris Control	DC Auto Iris (Hall Sensor)	DC Auto Iris (Hall Sensor)	DC Auto Iris (Hall Sensor)
Angular Field of View	Wide: 58.2° (H), 34° (V), 65.3° (D) Tele: 4.83° (H), 2.8° (V), 5.7° (D)	Wide: 58.9° (H), 34.4° (V), 66.3° (D) Tele: 2.7° (H), 1.5° (V), 3.1° (D)	Wide: 58.9° (H), 34.4° (V), 66.3° (D) Tele: 2.7° (H), 1.5° (V), 3.1° (D)
Min. Illumination	Colour: 0.1 lux @ F1.6 B/W: 0.01 lux @ F1.6	Colour: 0.1 lux @ F1.33 B/W: 0.01 lux @ F1.33	Colour: 0.1 lux @ F1.33 B/W: 0.01 lux @ F1.33
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
IR Distance (LEDs)	-	-	-
Image Stabilizer	Yes (EIS)	Yes (EIS)	Yes (EIS)
De-fog	Yes	Yes	Yes
Auto Tracking	-	-	-
Video Out	-	1 Terminal Block	-
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law
Max. Frame Rate	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	1 / 1	1 / 1	1 / 1
Alarm In / Out	1 / 1	4 / 2	4 / 2
Vandal Proof Casing	-	IK10	-
Outdoor Ready	-	IP67, Heater	-
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø155 x 158.1mm (Ø6.1" x 6.22")	Ø200 x 201mm (Ø7.88" x 7.91")	Ø226.5 x 203.5mm (Ø8.92" x 8.01")
Weight	1.0kg (2.20lb)	2.54kg (5.60lb)	1.82kg (4.01lb)
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)	24VAC, PoE, IEEE 802.3at (Class 4)	24VAC, PoE, IEEE 802.3at (Class 4)
Power Consumption	12VDC, 9.2W PoE, IEEE 802.3af (Class 3), 10W	HEATER OFF 24V~, 0.8A, 13.8W, 50/60Hz PoE, IEEE 802.3at (Class 4), 13.6W HEATER ON 24V~, 1.0A, 17.6W, 50/60Hz PoE, IEEE 802.3at (Class 4), 17.2W	24V~, 0.8A, 13.8W, 50/60Hz PoE, IEEE 802.3at (Class 4), 13.6W

SPEED DOME CAMERAS

Model Name	Mini AI AF Zoom, 5MP, 21x
	DC-S4561WRA
  5MP NDAACompliant	
Image Sensor	1/2.8" CMOS
Max. Resolution	2592 x 1944
Lens Type	AF Zoom Lens
Focal Length	f = 5.33 ~ 111.93mm
Aperture	F1.67 ~ F3.69
Iris Control	DC Iris (Hall Sensor)
Angular Field of View	Wide: 54.8° (H), 41.7° (V), 67.2° (D) Tele: 3.3° (H), 2.5° (V), 4.1° (D)
Min. Illumination	Colour: 0.13 lux @ F1.67 B/W: 0 lux @ F1.67
Dynamic Range	120dB (True WDR)
IR Distance (LEDs)	100m / 328.1ft (6ea)
Image Stabilizer	Yes (EIS)
De-fog	Yes
Auto Tracking	Yes
Video Out	-
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law, OPUS 16K
Max. Frame Rate	4:3 mode: 30ips: 2592 x 1944 (WDR) 16:9 mode: 30ips: 2592 x 1456 (WDR)
Ethernet	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTSec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection
Audio In / Out	1 / 1
Alarm In / Out	1 / 1
Vandal Proof Casing	-
Outdoor Ready	IP66
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	Ø173.65 x 173.5mm (Ø6.83" x 6.83")
Weight	2.37kg (5.22lb)
Power Source	PoE, IEEE 802.3at (Class 4)
Power Consumption	PoE, IEEE 802.3at (Class 4), 57V~, 16.8W

IDIS Mini AI PTZ Camera

5MP

Compact Design & Easy Installation
DC-S4561WRA

The Mini 5MP AI PTZ (DC-S4561WRA) has an NIR range of up to 100 meters, and its compact, sleek design makes it easy to install in limited-space locations, making it ideal for high-end environments with challenging lighting conditions, enabling discreet yet high-performance AI-powered pan, tilt, and zoom functionality.



IDIS COVERT MODULAR CAMERA

High-performance surveillance for branches and ATMs

True plug-and-play technology really becomes a force-multiplier when it comes to saving time and money during both installation and maintenance when solutions involve hundreds and even thousands of ATMs.



	Modular Covert Camera, 2MP	
	DC-V4212XJ (4.3mm)	DC-V4212XJ (2.4mm)
Model Name	 	 
Image Sensor	1/2.8" CMOS Sensor	1/2.8" CMOS Sensor
Max. Resolution	1920 x 1080	1920 x 1080
Scanning Mode	Progressive Scan	Progressive Scan
Lens Type	Fixed-focal	Fixed-focal
Focal Length	f = 4.3mm	f = 2.4mm
Aperture	F2.0	F2.0
Iris Control	Fixed Iris	Fixed Iris
Angular Field of View	81.6° (H), 42.3° (V), 99° (D)	132.5° (H), 72.7° (V), 154.7° (D)
Min. Illumination	Colour: 0.1 lux B/W: 0.01 lux	Colour: 0.1 lux B/W: 0.01 lux
Dynamic Range	More than 70dB	More than 70dB
Day and Night	Electrical	Electrical
IR Distance (LEDs)	-	-
Video Out	-	-
Video Compression	H.264 (MP), M-JPEG, H.265	H.264 (MP), M-JPEG, H.265
Intelligent Codec	Yes	Yes
Audio Compression	G.726, G.711 u-Law, G.711 a-Law	G.726, G.711 u-Law, G.711 a-Law
Two-way Audio	Yes	Yes
Max. Frame Rate	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTsrec)	Yes (Up to 60MB)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	Line-In 1ea / Line-Out 1ea	Line-In 1ea / Line-Out 1ea
Alarm In / Out	Input 1ea / Output 1ea	Input 1ea / Output 1ea
Vandal Proof Casing	-	-
Outdoor Ready	-	-
Operating Temperature	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)	-10°C ~ +50°C (+14°F ~ +122°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D) - Main Module	153 x 36.5 x 132.7mm (6.02" x 1.44" x 5.22")	153 x 36.5 x 132.7mm (6.02" x 1.44" x 5.22")
Dimensions (W x H x D) - Camera Module	[Main Unit] 153 x 36.5 x 132.7mm (6.02" x 1.44" x 5.22") [Camera Unit] 37 x 37 x 26.3mm (1.46" x 1.46" x 1.04") - Body Only 58 x 45 x 55.3mm (2.28" x 1.77" x 2.18") - With Bracket	[Main Unit] 153 x 36.5 x 132.7mm (6.02" x 1.44" x 5.22") [Camera Unit] 37 x 37 x 26.3mm (1.46" x 1.46" x 1.04") - Body Only 58 x 45 x 55.3mm (2.28" x 1.77" x 2.18") - With Bracket
Weight	[Main Unit] 0.47kg (1.04lb) [Camera Unit] 0.06kg (0.13lb)	[Main Unit] 0.47kg (1.04lb) [Camera Unit] 0.06kg (0.13lb)
Power Source	12VDC, PoE, IEEE 802.3at (Class 4)	12VDC, PoE, IEEE 802.3at (Class 4)
Power Consumption	12V=, 0.42A, 5.04W PoE, IEEE 802.3at (Class 4), 6.3W	12V=, 0.42A, 5.04W PoE, IEEE 802.3at (Class 4), 6.3W

IDIS Modular Camera

Modular IP camera designed for discreet surveillance—ideal for ATMs, kiosks, and luxury retail counters. Installs inside fixtures, ceilings, or walls with a small, flexible form factor.

- Ultra-compact lens with 2MP clarity
- Modular body for flexible positioning
- Multiple focal lengths for tailored views
- Perfect for hidden and low-profile security
- Works seamlessly with IDIS VMS and mobile app




IDIS LITE SERIES

New Cost-Effective Form Factor Cameras

Packed with essential, easy-to-use, and high-performance features, the IDIS Lite Series features 4-64 channel network recorders and a choice of network cameras. The IDIS Lite Protocol provides high-resolution image quality using SONY Starvis sensors and seamless streaming technology for real-time surveillance and recording.



IDIS Lite Protocol



New IDIS Lite Protocol enhances compatibility with IDIS's recording solutions

IDIS Lite Protocol

Using IDIS NVRs, customers can benefit from fast and cost-effective installation and an optimised user-friendly interface. The IDIS Lite Protocol enables easy and rapid installation for installers, and benefits end users with the rich connectivity of IDIS products. This affordable IDIS offering uses an innovative approach to surveillance – one that is click-and-play, single-source, and extends ONVIF compatibility - comprising a robust and high-performance range of cameras with associated brackets and NVRs.



Robust aluminium alloy body,
vandal resistant,
and weatherproof



The IDIS Lite Camera series consists of an aluminium alloy body, vandal proof glass including dome cameras that benefit from a patented design that eliminates IR reflection without bubbles. Certified for the highest levels of durability, the IDIS Lite dome cameras provide reliable surveillance even in the harshest environments.

	FIXED, 2MP	MFZ, 2MP	FIXED, 2MP	MFZ, 2MP
	DC-D2214R	DC-D2234WR	DC-T2214WR	DC-T2234WR
Model Name	 	 	 	 
Image Sensor	1/2.8" SONY IMX 307 Starvis CMOS Sensor	1/2.8" SONY IMX 307 Starvis CMOS Sensor	1/2.8" SONY IMX 307 Starvis CMOS Sensor	1/2.8" SONY IMX 307 Starvis CMOS Sensor
Total Number of Pixels	1945 x 1109	1945 x 1109	1945 x 1109	1945 x 1109
Scanning Mode	Progressive Scan	Progressive Scan	Progressive Scan	Progressive Scan
Lens Type	Fixed-focal	Motorised Vari-focal	Fixed-focal	Motorised Vari-focal
Focal Length	f = 2.8mm	f = 2.7 ~ 13.5mm	f = 2.8mm	f = 2.7 ~ 13.5mm
F No.	F1.6	F1.6 ~ F3.3 ±10%	F1.6	F1.6 ~ F3.3 ±10%
Iris Control	Fixed Iris	Fixed Iris	Fixed Iris	Fixed Iris
Field of View	127.9° (D), 106.9° (H), 56.9° (V)	130.9° (D), 108.1° (H), 56.3° (V)	127.9° (D), 106.9° (H), 56.9° (V)	130.9° (D), 108.1° (H), 56.3° (V)
Shutter Speed Control	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec
Day and Night Mode	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External
Infrared Distance	25m	25m	25m	30m
Auto White Balance Mode	Automatic, Manual	Automatic, Manual	Automatic, Manual	Automatic, Manual
Noise Reduction	2DNR / 3DNR	2DNR / 3DNR	2DNR / 3DNR	2DNR / 3DNR
Backlight Correction	WDR	WDR	WDR	WDR
Video Compression	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG
SDK Support	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant
Video Frame Rate	Up to 30fps @ 1920 x 1080p	Up to 30fps @ 1920 x 1080p	Up to 30fps @ 1920 x 1080p	Up to 30fps @ 1920 x 1080p
Video Resolution	1920 x 1080, 1280 x 720, 1024 x 576, 768 x 432, 704 x 392, 640 x 360, 384 x 216	1920 x 1080, 1280 x 720, 1024 x 576, 768 x 432, 704 x 392, 640 x 360, 384 x 216	1920 x 1080, 1280 x 720, 1024 x 576, 768 x 432, 704 x 392, 640 x 360, 384 x 216	1920 x 1080, 1280 x 720, 1024 x 576, 768 x 432, 704 x 392, 640 x 360, 384 x 216
Video Streaming (3 Streaming)	Simultaneously H.265 and MJPEG (Multi Streaming) or Simultaneously H.264 and MJPEG (Multi Streaming) Independent Frame Rate and Bandwidth Control, VBR/CBR Mode			
Protocols	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf
Security	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Edge Storage	micro SDHC/SDXC	micro SDHC/SDXC	micro SDHC/SDXC	micro SDHC/SDXC
Event In	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion
Event Out Notification	E-mail, FTP	E-mail, FTP	E-mail, FTP	E-mail, FTP
Audio	-	Line in / Line out	-	Line in / Line out
Alarm Control	-	Alarm in 1 / Alarm out 1	-	Alarm in 1 / Alarm out 1
Vandal Proof Casing	-	IK10	IK10	IK10
Outdoor Ready	IP67	IP67	IP67	IP67
Operation Temperature	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C
Operation Humidity	0% ~ 95%	0% ~ 95%	0% ~ 95%	0% ~ 95%
Power Source	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)
Power Consumption	4.6W	5.72W	4.4W	5.93W
Approval	KC, CE, FCC	KC, CE, FCC	KC, CE, FCC	KC, CE, FCC
Dimensions (W x H x D)	Ø111.9 x 88.2mm	Ø130 x 110mm	73.8 x 69.1 x 210.4mm	79.3 x 77.5 x 212mm

Korean-Made Video Tech That Users Can Trust



IDIS Lite Series of click-and-play, video surveillance products come with the assurance of Korean-made high-performance and robust technology that is NDAA-compliant.



TURRET CAMERAS

IDIS Lite Series

	FIXED, 5MP	MFZ, 5MP
	DC-D2511WER	DC-D2531WER
Model Name	 	 
Image Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor
Total Number of Pixels	2704 x 2104	2704 x 2104
Scanning Mode	Progressive Scan	Progressive Scan
Lens Type	Fixed-focal	Motorised Vari-focal
Focal Length	f = 2.8mm	f = 2.7 ~ 13.5mm
F No.	F1.6	F1.6 ~ F3.3 ±10%
Iris Control	Fixed Iris	Fixed Iris
Field of View	127.9° (D), 106.9° (H), 56.9° (V)	130.9° (D), 108.1° (H), 56.3° (V)
Shutter Speed Control	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec
Day and Night Mode	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External
Infrared Distance	20m	25m
Auto White Balance Mode	Automatic, Manual	Automatic, Manual
Noise Reduction	2DNR / 3DNR	2DNR / 3DNR
Backlight Correction	WDR	WDR
Video Compression	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG
SDK Support	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant
Video Frame Rate	Up to 30fps @ 2592 x 1944p	Up to 30fps @ 2592 x 1944p
Video Resolution	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 640 x 480, 480 x 360	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 640 x 480, 480 x 360
Video Streaming (3 Streaming)	Simultaneously H.265 and MJPEG (Multi Streaming) or Simultaneously H.264 and MJPEG (Multi Streaming) Independent Frame Rate and Bandwidth Control, VBR/CBR Mode	
Protocols	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf
Security	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Edge Storage	micro SDHC/SDXC	micro SDHC/SDXC
Event In	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion
Event Out Notification	E-mail, FTP	E-mail, FTP
Audio	Line In / Line Out	Line In / Line Out
Alarm Control	Alarm In 1 / Alarm Out 1	Alarm In 1 / Alarm Out 1
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP67	IP67
Operation Temperature	-10°C ~ +50°C	-10°C ~ +60°C
Operation Humidity	0% ~ 95%	0% ~ 95%
Power Source	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)
Power Consumption	3.82W	6.1W
Approval	KC, CE, FCC	KC, CE, FCC
Dimensions (W x H x D)	Ø125.0 x 90.2mm	Ø128 x 108mm

	FIXED, 5MP	MFZ, 5MP	FIXED, 5MP	MFZ, 5MP
	DC-D2511R	DC-D2531WR	DC-T2511WR	DC-T2531WR
Model Name	 	 	 	 
Image Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor	1/2.8" SONY IMX 335 Starvis CMOS Sensor
Total Number of Pixels	2704 x 2104	2704 x 2104	2704 x 2104	2704 x 2104
Scanning Mode	Progressive Scan	Progressive Scan	Progressive Scan	Progressive Scan
Lens Type	Fixed-focal	Motorised Vari-focal	Fixed-focal	Motorised Vari-focal
Focal Length	f = 2.8mm	f = 2.7 ~ 13.5mm	f = 2.8mm	f = 2.7 ~ 13.5mm
F No.	F1.6	F1.6 ~ F3.3 ±10%	F1.6	F1.6 ~ F3.3 ±10%
Iris Control	Fixed Iris	Fixed Iris	Fixed Iris	Fixed Iris
Field of View	127.9° (D), 106.9° (H), 56.9° (V)	130.9° (D), 108.1° (H), 56.3° (V)	127.9° (D), 106.9° (H), 56.9° (V)	130.9° (D), 108.1° (H), 56.3° (V)
Shutter Speed Control	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec	Min. 1/100,000 sec ~ Max. 1/2 sec
Day and Night Mode	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External	Auto / Day (Colour) / Night (BW) / External
Infrared Distance	25m	25m	25m	30m
Auto White Balance Mode	Automatic, Manual	Automatic, Manual	Automatic, Manual	Automatic, Manual
Noise Reduction	2DNR / 3DNR	2DNR / 3DNR	2DNR / 3DNR	2DNR / 3DNR
Backlight Correction	WDR	WDR	WDR	WDR
Video Compression	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG	H.265 Main profile, H.264 (High, Main, Base line profile), MJPEG
SDK Support	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant	API, ONVIF Profile S/T Compliant
Video Frame Rate	Up to 30fps @ 2592 x 1944p	Up to 30fps @ 2592 x 1944p	Up to 30fps @ 2592 x 1944p	Up to 30fps @ 2592 x 1944p
Video Resolution	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 640 x 480, 480 x 360	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 640 x 480, 480 x 360	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 640 x 480, 480 x 360	2592 x 1944, 2560 x 1920, 2048 x 1536, 1920 x 1440, 1600 x 1200, 1280 x 960, 640 x 480, 480 x 360 480 x 360
Video Streaming (3 Streaming)	Simultaneously H.265 and MJPEG (Multi Streaming) or Simultaneously H.264 and MJPEG (Multi Streaming) Independent Frame Rate and Bandwidth Control, VBR/CBR Mode			
Protocols	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf
Security	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS	Multi User Authority, IP Filtering, HTTPS
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Edge Storage	micro SDHC/SDXC	micro SDHC/SDXC	micro SDHC/SDXC	micro SDHC/SDXC
Event In	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion	On Boot, Trigger, Network Loss, Tampering, Motion
Event Out Notification	E-mail, FTP	E-mail, FTP	E-mail, FTP	E-mail, FTP
Audio	-	Line In / Line Out	-	Line in / Line out
Alarm Control	-	Alarm In 1 / Alarm Out 1	-	Alarm in 1 / Alarm out 1
Vandal Proof Casing	-	IK10	IK10	IK10
Outdoor Ready	IP67	IP67	IP67	IP67
Operation Temperature	-10°C ~ +50°C	-10°C ~ +60°C	-10°C ~ +50°C	-10°C ~ +50°C
Operation Humidity	0% ~ 95%	0% ~ 95%	0% ~ 95%	0% ~ 95%
Power Source	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)	DC12V, PoE, IEEE 802.3af (Class 2)
Power Consumption	5.02W	6.1W	5.05W	6.3W
Approval	KC, CE, FCC	KC, CE, FCC	KC, CE, FCC	KC, CE, FCC
Dimensions (W x H x D)	Ø111.9 x 88.2mm	Ø130 x 110mm	73.8 x 69.1 x 210.4mm	79.3 x 77.5 x 212mm



Powerful IR illumination provides night visibility



IR illumination is automatically focused to ensure the field of view is consistently illuminated, ensuring a clear view of up to 20-30 meters. IDIS

Lite Cameras use SONY Starvis CMOS image sensors to ensure clarity at night and deliver crisp Full-HD resolution even in complete darkness.



IDIS Lite Protocol



Click-and-Play



Aluminium Alloy Body (Dome)



Alarm, Audio In/Out (MFZ)



Reliability with SD Card



NDAA-Compliant Made in South Korea

Rapid installation in varied environments

The IDIS Lite Camera Series has a 3-axis design allowing for easy pan, tilt, and horizontal adjustment in various locations and environments including wall mounting. With the aluminium alloy body, vandal proof glass form factor, and a choice of mounts, brackets and junction boxes, the cameras are ideal for wide-area and high-definition coverage in a range of small to medium sized applications.



Wall Mount Bracket

DA-WM2400

DC-D2214R, DC-D2511R



Wall Mount Bracket

DA-WM2500

DC-D2234WR, DC-D2531WR
DC-T2511WER, DC-D2531WER



Junction Box

DA-JB2500

For All IDIS Lite Cameras

I-MOBILE SOLUTIONS

Next-Generation Vehicle Surveillance System: Unmatched Performance and Integration



From pioneers in mobile systems to leaders in innovation
Experience IDIS' I-Mobile system.

High-Performance 4K Mobile Solution Provides Transit
and Fleet Operators with an Intuitive User Interface and Seamless
System Compatibility.



NDAA
Compliant

★ **TAA** ★
Compliant

| Assembly in United States



The Technology Leader



I-MOBILE CAMERAS

Model Name	Fixed Focal, 12MP
	DC-Y6C17WRX
	 
Image Sensor	1/2.3" CMOS
Max. Resolution	2944 x 2944
Scanning Mode	Progressive Scan
Lens Type	Fixed-focal
Focal Length	f = 1.6mm
Aperture	F2.0
Iris Control	Fixed Iris
Angular Field of View	180° (H), 180° (V), 180° (D)
Min. Illumination	Colour: 0.3 lux @ F2.0 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)
Day and Night	Yes (ICR)
IR Distance (LEDs)	15m / 49.2ft (4ea)
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colours, Brightness Control), 3DNR Level, WDR Level
De-fog	Yes
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone, Heatmap
Viewing Composition	1O, 1P, 1P2R, 2P, 4R, 1O7R
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported
IP Camera Protocol	DirectIP 2.0, ONVIF Profile S/T
Max. Frame Rate	30ips: 2944 x 2944 15ips: 2944 x 2944 (WDR)
Multi-video Streaming	Quadruple Streaming
Security	Digest Authentication, Password Protection, User Access Log, IP Filtering, IEEE802.1 x (EAP-TLS), Chained Fingerprint, SSL Encryption, HTTPS Encryption
Ethernet	RJ45 (10/100 BASE-T)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone, Heatmap
Audio In / Out	1 (Built In MIC) / 0
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Operating Temperature	-30°C ~ 50°C (-22°F ~ 122°F)
Operating Humidity	0% ~ 90%
Vandal Proof Casing	IK10
Power Source	PoE, IEEE 802.3af (Class 3)
Power Consumption	PoE, IEEE 802.3af (Class 3), 10.6W
Dimensions (W x H x D)	Ø135 x 56.9mm (Ø5.31" x 2.24")
Weight	0.67kg (1.47lb)
Approval	FCC, CE, KC

I-MOBILE CAMERAS

Model Name	FIXED, 2MP		
	DC-M4211HRX	DC-M4211WRX (2.8mm, 3.3mm)	DC-M4211WX
	 Full HD 2MP NDAA Compliant	 Full HD 2MP NDAA Compliant	 Full HD 2MP NDAA Compliant
Image Sensor	1/2.8" CMOS	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	1920 x 1080	1920 x 1080	1920 x 1080
Lens Type	Progressive Scan	Fixed-focal	Fixed-focal
Focal Length	f = 3.3mm	f = 2.8mm, f = 3.3mm	f = 2.3mm
Aperture	F2.0	F2.0	F2.2
Iris Control	Fixed Iris	Fixed Iris	Fixed Iris
Angular Field of View	101.3° (H), 54.5° (V), 119.7° (D)	[2.8mm] 111.6° (H), 61.45° (V), 127.3° (D) [3.3mm] 101.3° (H), 54.5° (V), 119.7° (D)	137.7° (H), 75.4° (V), 163° (D)
Min. Illumination	Colour: 0.1 lux @ F2.0, B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F2.0, B/W: 0 lux (IR LED On)	Colour: 0.1 lux @ F2.2 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	20m	10m	-
Backlight Compensation	BLC	BLC	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot	Horizontal / Vertical / Pivot	Horizontal / Vertical / Pivot
Privacy Masking	8 Zones	8 Zones	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	Video Motion Detection, Active Tampering Alarm, Trip Zone	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	1 CVBS	1 CVBS	1 CVBS
Pan / Tilt / Rotate	Pan: ±5°, Tilt: +20° ~ +75°, Rotate: ±90°	Pan: ±5°, Tilt: +20° ~ +75°, Rotate: ±90°	Pan: ±5°, Tilt: +20° ~ +75°, Rotate: ±90°
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported	Supported
IP Camera Protocol	DirectIP 2.0, ONVIF	DirectIP 2.0, ONVIF	DirectIP 2.0, ONVIF
Max. Frame Rate	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)	30ips: 1920 x 1080 (WDR)
Supported Resolution	[16:9] 1920 x 1080, 1280 x 720, 640 x 360, 352 x 240	[16:9] 1920 x 1080, 1280 x 720, 640 x 360, 352 x 240	[16:9] 1920 x 1080, 1280 x 720, 640 x 360, 352 x 240
	[4:3] 1440 x 1080, 960 x 720, 480 x 360, 272 x 240	[4:3] 1440 x 1080, 960 x 720, 480 x 360, 272 x 240	[4:3] 1440 x 1080, 960 x 720, 480 x 360, 272 x 240
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)	micro SD/SDHC/SDXC, Smart Failover (Up to 256GB)
Trigger Event	Motion Detection, Tampering, Trip Zone	Motion Detection, Audio Detection, Tampering, Trip Zone	Motion Detection, Audio Detection, Tampering, Trip Zone
Audio In / Out	-	1 (Internal MIC) / 0	1 (Internal MIC) / 0
Outdoor Ready	IP69K	IP67	IP67
Operating Humidity	0% ~ 90%	0% ~ 90%	0% ~ 90%
Operating Temperature	-40°C ~ +60°C (-40°F ~ +140°F) *Starting up at above -20°C (32°F)	-30°C ~ +55°C (-22°F ~ +122°F) *Starting up at above 0°C (32°F)	-30°C ~ +55°C (-22°F ~ +122°F) *Starting up at above 0°C (32°F)
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	-
Approval	FCC, CE, MIL-STD-810G EN50155 (M12 model only)	FCC, CE, MIL-STD-810G EN50155 (M12 model only)	FCC, CE, MIL-STD-810G EN50155 (M12 model only)
Dimensions (W x H x D)	140 x 73.57 x 126mm (5.51" x 2.9" x 4.96")	104 x 49.44 x 122.17mm (4.09" x 1.95" x 4.81")	104 x 49.44 x 122.17mm (4.09" x 1.95" x 4.81")
Weight	0.66kg (1.46lbs) - Poly Carbonate 0.67kg (1.48lbs) - Tempered Glass	0.36kg (0.79lbs)	0.37kg (0.81lbs)
Power Source	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 2)
Power Consumption	9.5W (Heater on)	8.9W	6.3W

I-MOBILE CAMERAS


Model Name	FIXED, 8MP	
	DC-M4811X (3.07mm, 3.2mm) / Short Bracket	DC-M4811X (3.07mm, 3.2mm) / Long Bracket
	 4K 8MP NDAA Compliant	 4K 8MP NDAA Compliant
Image Sensor	1/2.8" CMOS	1/2.8" CMOS
Max. Resolution	3840 x 2160	3840 x 2160
Lens Type	Progressive Scan	Progressive Scan
Focal Length	f = 3.07mm, f = 3.2mm	f = 3.07mm, f = 3.2mm
Aperture	F1.8	F1.8
Iris Control	Fixed Iris	Fixed Iris
Angular Field of View	[2.8mm] 115° (H), 60° (V), 140° (D) [3.3mm] 104° (H), 58° (V), 121° (D)	[2.8mm] 115° (H), 60° (V), 140° (D) [3.3mm] 104° (H), 58° (V), 121° (D)
Min. Illumination	-	-
Dynamic Range	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	-	-
Backlight Compensation	BLC	BLC
Mirroring / Pivot	Horizontal / Vertical / Pivot	Horizontal / Vertical / Pivot
Privacy Masking	8 Zones	8 Zones
Intelligent Video	Video Motion Detection, Active Tampering Alarm, Trip Zone	Video Motion Detection, Active Tampering Alarm, Trip Zone
Video Out	-	-
Pan / Tilt / Rotate	45° Forward & 35° Backward (80° Total)	45° Forward & 45° Backward (90° Total) on both Upper & Lower Tilt Brackets
Video Compression	H.265, H.264 (MP), M-JPEG	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Supported	Supported
IP Camera Protocol	DirectIP 2.0, ONVIF	DirectIP 2.0, ONVIF
Max. Frame Rate	30ips: 3840 x 2160 15ips: 3840 x 2160 (WDR)	30ips: 3840 x 2160 15ips: 3840 x 2160 (WDR)
Supported Resolution	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360	3840 x 2160, 1920 x 1080, 1280 x 720, 640 x 360
Ethernet	RJ45 (10/100 BASE-T)	RJ45 (10/100 BASE-T)
Edge Storage	-	-
Trigger Event	Motion Detection, Tampering, Trip Zone	Motion Detection, Tampering, Trip Zone
Audio In / Out	-	-
Outdoor Ready	IP67	IP67
Operating Humidity	0% ~ 90%	0% ~ 90%
Operating Temperature	-10°C ~ +50°C	-10°C ~ +50°C
Approval	FCC, MIL-STD-810H	FCC, MIL-STD-810H
Dimensions (W x H x D)	214.9 x 134.6 x 120.4mm (8.46" x 5.30" x 4.74")	[Not Extended] 214.9 x 134.6 x 245.1mm (8.46" x 5.30" x 9.65") [Extended] 214.9 x 134.6 x 308.6mm (8.46" x 5.30" x 12.15") - Vertical Adjustment Range: 63.5mm (2.5")
Weight	1kg (2.2lb)	1.27kg (2.8lb)
Power Source	PoE, IEEE 802.3af (Class 3)	PoE, IEEE 802.3af (Class 3)
Power Consumption	7.9W	7.9W

I-Mobile Network Solution

This setup allows you to have both live and archived video access from multiple locations (the bus and the office) with the flexibility of using internet connectivity to bridge the locations.

Building Access

- **Router on Bus:** Connects to the building's access point (Wi-Fi connection)
- **Computer in Office:** Connects to the building access point to:
 - Retrieve Video: Access stored video footage from the NVR on the bus



On-Bus System

- **Cameras:** Record video footage
- **NVR (Network Video Recorder):** Stores the recorded video on the bus
- **Laptop Access:** You can retrieve video footage from the NVR using a laptop connected to the NVR on the bus

Office Access

- **Server with Internet Access:** Connects to the bus's router via the internet
- This setup allows you to:
- View Cameras Live: Stream live video footage from the cameras on the bus
 - Retrieve Stored Video: Access previously recorded footage from the NVR on the bus

I-MOBILE RECORDER

Model Name	Mobile H.265 4K Recorder	
	DR-M208P	DR-M216P
		
VIDEO		
Video Inputs	8 IP Channels	16 IP Channels
Video Outputs	1 HDMI	1 HDMI
Display Resolution	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200	HDMI: 3840 x 2160, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200
RECORDING		
Max. Throughput	90Mbps, 240ips @ 4K (HQ) + 240ips @ nHD (LT)	180Mbps, 480ips @ 4K (HQ) + 480ips @ nHD (LT)
Recording Resolution	Up to 12MP (Depending on IP Camera)	Up to 12MP (Depending on IP Camera)
Recording Mode	Time-Lapse / Event, Pre-Event, Panic	Time-Lapse / Event, Pre-Event, Panic
Trigger Event	Alarm In, Motion Detection, Trip-Zone, Tampering, Video Loss, Text-In, Recording Fail, Network Alarm	Alarm In, Motion Detection, Trip-Zone, Tampering, Video Loss, Text-In, Recording Fail, Network Alarm
STORAGE		
HDD	SATA 3.5" x 1 (Hot Swappable) + 1 eSATA	SATA 3.5" x 1 (Hot Swappable) + 1 eSATA
NETWORK		
Video In Connection	Gigabit Ethernet (IP Camera) x 8 + Gigabit Ethernet (Ext.) x 2	Gigabit Ethernet (IP Camera) x 16 + Gigabit Ethernet (Ext.) x 2
PSE Power	48V Legacy, Total 172.8W (8ch)	48V Legacy, Total 172.8W (16ch)
INTERFACE		
Audio In / Out	Local: 2 Line In (4-Pin Dual Row Microfit) / 1 HDMI IP Camera: 8 / 8 (Depending on IP Camera)	Local: 2 Line In (4-Pin Dual Row Microfit) / 1 HDMI IP Camera: 16 / 16 (Depending on IP Camera)
Alarm In / Out	Local: 16 / 2	Local: 16 / 2
Serial Interface	2 RS232 (6-Pin Dual Row Microfit) + 1 CAN (6-Pin Dual Row Microfit)	2 RS232 (6-Pin Dual Row Microfit) + 1 CAN (6-Pin Dual Row Microfit)
USB	1 USB3.0 + 1 USB2.0	1 USB3.0 + 1 USB2.0
Event Connection	1 Heartbeat + 1 Recording status + 2 Alarm Status (12-Pin Dual Row MicroFit)	1 Heartbeat + 1 Recording status + 2 Alarm Status (12-Pin Dual Row MicroFit)
User Interface	Mouse	Mouse
Aux Power Output	1 Output (2A @ 12VDC, 4-Pin Mini-Fit Jr.)	1 Output (2A @ 12VDC, 4-Pin Mini-Fit Jr.)
Etc. Interface	1 GPS internal (SMA) + 1 mini PCI-e (WiFi)	1 GPS internal (SMA) + 1 mini PCI-e (WiFi)
Backup Power	Connector for SuperCap (Mini-Fit)	Connector for SuperCap (Mini-Fit)
BUILT-IN SENSOR		
3-axis	Yes	Yes
Temperature	Yes	Yes
Battery Voltage	Yes	Yes
ENVIRONMENTAL		
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F) / -30°C ~ 50°C (-22°F ~ 122°F) with Heater	0°C ~ 50°C (32°F ~ 122°F) / -30°C ~ 50°C (-22°F ~ 122°F) with Heater
Operating Humidity	0% ~ 90%	0% ~ 90%
ELECTRICAL		
Power Input	Bat/Acc: 9 ~ 36DC Heater: 12V/24V, 110W (5-Pin Mini-Fit Sr)	Bat/Acc: 9 ~ 36DC Heater: 12V/24V, 110W (5-Pin Mini-Fit Sr)
Power Consumption	Power: 9 ~ 36V=, 26A / HEATER: 12V/24V, 110W	Power: 9 ~ 36V=, 26A / HEATER: 12V/24V, 110W
Approval	CE, FCC (Class A), MIL-STD-810G (Shock & Vibration only)	CE, FCC (Class A), MIL-STD-810G (Shock & Vibration only)
MECHANICAL		
Dimensions (W x H x D)	285 x 100.37 x 320.2mm (11.22" x 3.95" x 12.6")	285 x 100.37 x 320.2mm (11.22" x 3.95" x 12.6")
Weight	5.01kg (11.05lb)	5.01kg (11.05lb)

I-MOBILE MONITORS

	Premium Wide In-Vehicle LCD Monitor		
	LCD Monitor - 19Inch	LCD Monitor - 10Inch	LCD Monitor - 8Inch
Model Name	 	 	 
PANEL			
Screen Size	19Inch	10.1Inch	8Inch
Max. Resolution	1280 x 1024 @ 75Hz	1280 x 800 @ 60Hz	1024 x 768 @ 60Hz
Pixel Pitch	0.294 x 0.294mm	0.1695 x 0.1695mm	0.192 x 0.192mm
Brightness	250cd / m²	350cd / m²	300cd / m²
Contrast Ratio	1000:1	800:1	500:1
Aspect Ratio	5:4	16:10	4:3
Viewing Angle (H/V)	178° / 178°	170° / 170°	160° / 160°
Display Colour	8bits / 16.7Million	8bits / 16.7Million	8bits / 16.7Million
Response Time	<14ms (Gray to Gray)	<15ms (Gray to Gray)	<20ms (Gray to Gray)
Video System	NTSC / PAL	NTSC / PAL	NTSC / PAL
LifeTime (Typ.)	40,000Hrs	30,000Hrs	30,000Hrs
INTERFACE			
Video In (BNC Type)	1 / 1	1 / 1	4In (CVBS or Analogue HD)
RTSP (LAN)	1 / 1	RJ45 (2ch Input)	-
VGA In (15Pin D-Sub)	-	-	-
Audio In (RCA Type)	-	-	-
PC Stereo In	-	-	-
TRANSMITTER			
Remote Control	Yes	Yes	Yes
AUDIO			
Filter Type	3D Comb Filter	3D Comb Filter	3D Comb Filter
Deinterlacing	Yes	Yes	Yes
Advanced Auto Power Recovery	Yes	Yes	Yes
Noise Reduction Control (NR)	Yes	Yes	Yes
LCD Protection Glass	N/A	N/A	N/A
Auto Pixel Shift	Yes	Yes	Yes
Auto Source Sequencing	Yes	Yes	Yes
Trigger Sensor	-	2In	2In
Multi Language	English, Spanish, French, German, Italian	English, Spanish, French, German, Italian	English, Spanish, French, German, Italian
GENERAL			
Outline Dimension (W x H x D)	412.2 x 340.78 x 45mm (16.2" x 13.3" x 1.73")	260.6 x 177 x 70mm (10.2" x 6.9" x 2.75")	212.8 x 136.4 x 50mm (8.37" x 5.37" x 1.96")
Net Weight	6.25kg (13.78lbs)	Appx. 4kg	-
Material / Colour	Metal / Black	Electronic Galvanized Iron / Black	Metal / Black
Consumption: < On	DC9 ~ 36V	DC9 ~ 36V / <11W	DC9 ~ 36V / <11W
Operating Temperature	0° ~ 40°C / 32° ~ 104°F	0° ~ 40°C / 32° ~ 104°F	0°C ~ 40°C / 32° ~ 104°F
Storage Temperature	-20° ~ 60°C / -4° ~ 140°F	-20° ~ 60°C / -4° ~ 140°F	-20°C ~ 60°C / -4° ~ 140°F
MOUNTS			
VESA Mount Size	100 x 100mm (3.9" x 3.9")	75 x 75 mm (2.9" x 2.9")	75 x 75mm (2.9" x 2.9")

I-MOBILE ACCESSORIES

	GNSS Ceramic Active Antenna	
	GPS Antenna	
Model Name		
VIDEO		
Parameters	GNSS Ceramic Active Antenna	
Standards	GPS / QZSS / Galileo	GLONASS
Band (MHz)	1575	1602
Frequency (Mhz)	1575.42	1598-1606
Patch Size (mm)	25 x 25 x 4	
VSWR	≤1.4:1dB	
Impedance (Ohms)	50	
Radiation Pattern	Hemispherical	
Polarization	RHCP	
Active Gain (dB)	28dB @ 2.7V	
Noise Figure (dB)	1.8 @ 2.7V	
Voltage Range (V)	1.5 ~ 3.6	
Current Consumption (mA)	9@2.7V	
Saw Filter Type	Pre-Filter	
Out of Band Rejection (dB)	~ 43	
ESD Protection (kV)	6	
Connector Type	SMA-Male Standard (Other connectors available)	
Cable Length	300cm Standard (Any cable length available)	
Cable Type	LL100 Standard (Other cables available)	
MECHANICAL AND ENVIRONMENTAL		
Mounting Type	Magnetic mount	
Dimensions	Ø54 x 14.7mm	
Operating Temperature	-40°C ~ +85°C	
Storage Temperature	-40°C ~ +85°C	
Certificates	IP67, IP69K	
Substance Compliance	RoHS	

Model Name	Mobile UPS	
	DP-MU2100	
	 	
ELECTRICAL PROPERTIES		
Input Operating Voltage	9 ~ 36VDC	
Battery Charging Voltage	10 ~ 36VDC	
Input Power Consumption	200W	
Output Voltage	Bypass (Normal), 24VDC (Emergency)	
Output Power	100W Maximum	
Quiescent Current	35mA at Knife SW ON 3mA at Knife SW OFF	
Back-up Time	15mins	
Time to Charge	60mins	
INTERFACES		
Power	1, DTF13-12PB, TE Connectivity	
IO	1, 43045-0600, Molex	
MECHANICAL PROPERTIES		
Weight	1.75kg (3.86lb), with Battery Pack 1.16kg (2.56lb), without Battery Pack	
Dimensions	90 x 74 x 203.5mm (3.54" x 2.91" x 8.01")	
ENVIRONMENT		
Operating Temperature	0°C ~ 55°C (32°F ~ 131°F)	
ELECTRICAL		
Approval	FCC, MIL-STD-810G, ISO 16750-2, EN61000-4-2	
BATTERY PACK		
Battery Pack Type	751P, Li-ion	
PROTECTION		
BMS (Battery Management System)	Overcharge Protection, Over Discharge Protection, Over Current Protection, Short Circuit Protection, Over Temperature Protection	
ACCESSORY		
Mounting Bracket	Included	

	Anti-vandal Driver Event Button	
	Driver Event Button	
Model Name		
Electrical Rating	2A, 48VDC	
Mechanical Life	1000000 Cycles	
Electrical Life	50000 Cycles	
Contact Resistance	50mΩ Max.	
Insulation Resistance	1000MΩ Min.	
Dielectric Strength	2000VAC	
Operating / Storage Temperature	-20°C ~ 55°C	
Travel	1.80mm (Non-Illuminated), 2.20mm (Illuminated)	
Moisture Protection	IP65	
Contact Arrangement	SPST Off-(On)	
Actuation Force	400gf	
Mounting Nut Torque	1 ~ 10mm	
Newtork Connection	5 ~ 14Nm	

	High Preamplification, 25' Directional Microphone	
	External Microphone	
Model Name		
Pickup Pattern	Omni-directional 25' pickup pattern	
Pre-amplifier Type	Low noise MOSFET pre-amplifier	
Gain Control	Adjustable gain	
Output Level	Line Level (0dbm) Output	
Frequency Response	500Hz-16KHz Frequency Response	
Output Impedance	1000Ω unbalanced Output	
Power	12VDC @ 20ma	
S/N Ratio	60dB	
Sensitivity	44dB	
Temperature Range	40°C ~ 85°C	
Voltage Regulation & RFI Filtering	On-board voltage regulator and RFI filtering	
Encapsulation	Potted Electronics	
IP Rating	IP67	
Housing	Powder Coated, Aluminium, Tamper Resistant Housing	
Dimensions	2.45" x 1.04" x 0.72"	
Weight	0.05bs	

Your ONLY Transit Safety Solution
I-Mobile Solutions

EDGE AI MULTI-DIRECTIONAL CAMERA

Seamless Sight, Intelligent Insight

The IDIS Multi-Imager brings one camera, four high-definition realities together in a single, distortion-free panoramic solution with built-in AI functions.

From line crossing to face and object detection, it delivers intelligent, proactive security with total situational awareness.



MULTI-DIRECTIONAL CAMERAS



Model Name	AI MFZ, 5MP	
	NEW DC-U6K31WRA	
	    	
Image Sensor	1/2.8" CMOS	
Max. Resolution	2592 x 1944	
Scanning Mode	Progressive Scan	
Lens Type	Motorised Vari-focal	
Focal Length	f = 3.3 ~ 7.02mm	
Aperture	F1.8 ~ F2.74	
Iris Control	Fixed Iris	
Angular Field of View	Wide: 96° (H), 69.8° (V), 127.8° (D) Tele: 42.4° (H), 31.8° (V), 53.2° (D)	
Min. Illumination	Colour: 0.1 lux @ F1.8 B/W: 0 lux (IR LED On)	
Dynamic Range	120dB (True WDR)	
Day and Night	Yes (ICR)	
IR Distance (LEDs)	25m / 82ft (3ea per unit)	
Image Setting	Exposure, White Balance, Self-Adjusting Video Mode (Sharpness, Contrast, Colors, Brightness Control)	
De-fog	Yes	
Intelligent Video	Object Metadata: Human, Vehicle, Face IDLA: Object Detection, Intrusion, Loitering, Line Crossing, Face Detection ETC: Video Motion Detection, Active Tampering Alarm	
Video Compression	H.265, H.264 (MP), M-JPEG	
Intelligent Codec	Supported	
IP Camera Protocol	DirectIP 2.0	
Max. Frame Rate	4:3 mode: 30fps: 2592 x 1944 (WDR) 16:9 mode: 30fps: 2592 x 1456 (WDR)	
Multi-video Streaming	Quadruple Streaming	
Security	FIPS 140-3 Level 3, Digest Authentication, Password Protection, Brute Force Delay Protection, User Access Log, IP Filtering, IEEE802.1 x (EAP-TLS), Chained Fingerprint, SSL Encryption, HTTPS Encryption	
Ethernet	RJ45 (10/100/1000 BASE-T)	
Edge Storage	micro SD/SDHC/SDXC, UHS Speed Class 3, Smart Failover (Up to 512GB)	
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Object Detection, Intrusion, Loitering, Line Crossing, Face Detection	
Audio In / Out	1 / 1	
Vandal Proof Casing	IK10	
Outdoor Ready	IP67, NEMA4X	
Operating Temperature	-40°C ~ +55°C (-40°F ~ +131°F) *Starting up at above -20°C (-4°F)	
Operating Humidity	0% ~ 90%	
Dimensions (W x H x D)	Ø258 x 112mm (Ø10.2" x 4.4")	
Weight	2.8kg (6.2lb)	
Approval	FCC, CE, KC, UL	
Power Source	PoE, IEEE 802.3at (Class 4)	
Power Consumption	PoE, IEEE 802.3at (Class 4), 21W	

IDIS VIDEO INTERCOM

Beyond the Front Door: A Critical Edge in Your Security Network

- **Built for Surveillance**
Seamlessly integrates with IDIS Solution Suite (ISS), IDIS Center, and the IDIS Mobile App
- **Unified Communication**
Supports SIP (VoIP) and PBX—enabling direct calls to personnel
- **Smart Access Control**
Opens doors and unlocks locks via system integration
- **Focused Coverage**
Optimized for close-range facial ID at entry points



IDIS Mobile +





INTERCOM CAMERAS

	Intercom, 2MP
	DC-I6212WRX
Model Name	 
Image Sensor	1/2.8" CMOS Sensor
Max. Resolution	1920 x 1080
Lens Type	Fixed-focal
Focal Length	f = 1.85mm
Aperture	F2.3
Iris Control	Fixed Iris
Angular Field of View	180° (H)
Pan / Tilt Range	-
Min. Illumination	Colour: 0.1 lux @ F2.3 B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)
Day and Night	Yes (ICR)
IR Distance (LEDs)	5m / 16ft (1ea)
Image Stabilizer	-
De-fog	Supported
Video Out	-
Video Compression	H.265, H.264 (MP), M-JPEG
Intelligent Codec	Yes
Audio Compression	G.726, G.711 u-Law, G.711 a-Law, G.722
Max. Frame Rate	30ips: 1920 x 1080 (WDR)
Ethernet	RJ45 (10/100 BASE-T)
Recording Session Buffer (NLTSrec)	Yes (Up to 60MB)
Edge Storage	micro SD/SDHC/SDXC, Smart Failover (Up to 512GB)
Trigger Event	Motion Detection, Alarm In, Audio Detection, Tampering, Trip Zone
Audio In / Out	1 (Built In MIC with Echo Cancellation) / 1 (Built In SPK)
Alarm In / Out	1 / 2
Vandal Proof Casing	IK10
Outdoor Ready	IP66, NEMA 4X
Operating Temperature	-30°C ~ +55°C (-22°F ~ +131°F) *Starting up at above 0°C (32°F)
Dimensions (W x H x D)	52 x 165 x 46mm (2.05" x 6.50" x 1.81")
Weight	0.52kg (1.15lb)
Power Source	DC12V, PoE, IEEE 802.3af (Class 3)
Power Consumption	12V=, 1.87A, 22.4W PoE, IEEE 802.3af (Class 3), 9.5W (DC Output: 12V=, 1A MAX with Adaptor)

IDIS SPECIALTY CAMERAS

Explosion Proof Cameras

Video Technology Designed for Hazardous
and High-Risk Environments






SPECIALTY CAMERAS

	Explosion Proof Mini-Dome	Explosion Proof Fisheye	Explosion Proof PTZ
	DC-SP6531EXD	DC-SP6C11EXY	DC-S3283EX
Model Name			
CAMERA			
Image Sensor	1/2.8" Progressive 5M CMOS	1/2.3" Progressive Sony CMOS	1/3" Progressive 2M CMOS
Resolution	2592 x 1944	2944 x 2944	1920 x 1080
Electronic Shutter Speed	Auto / Manual (1/30 ~ 1/10,000sec) Anti-Flicker Slow Shutter (1 ~ 1/5, 1/7.5, 1/15)	Auto / Manual (1/30 ~ 1/10,000sec) Slow Shutter (1 ~ 1/5, 1/7.5, 1/15) Anti-Flicker	Auto / Manual (1/30 ~ 1/10,000sec) Slow Shutter (1 ~ 1/5, 1/7.5, 1/15) Anti-Flicker
Angular Field of View	Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D)	180° (H), 180° (V), 180° (D)	Wide: 64.7° (H), 38.6° (V), 72.7° (D) Tele: 2.3° (H), 1.4° (V), 2.6° (D)
Focal Length	f = 3.0 ~ 13.5mm (Motorised Vari-focal lens)	f = 1.6mm (Fixed-focal)	f = 4.3 ~ 129mm (Optical 30x)
De-fog	On / Off	-	-
Dynamic Range	120dB (True WDR)	120dB (True WDR)	-
AI Analytics	Video Motion Detection, Active, Tampering Alarm, Trip Zone	-	-
Digital Zoom	-	-	-
VR Mode	-	360° VR Mode, Option Mode, Spot Mode, Drag and Drop	-
Min. Illumination	-	-	Colour: 0.1 lux @ F1.6, B/W: 0.01 lux @ F1.6
PAN / TILT			
Rotation Speed	-	-	Pan: 0.02 ~ 180°/sec (preset 420°/sec) Tilt: 0.02 ~ 180°/sec (preset 420°/sec)
Preset	-	-	256ea
IR			
IR Distance	30m	30m	-
LED	6ea	4ea	-
IR Operation	Auto On / Off (Photo Sensor)	Auto On / Off (Photo Sensor)	-
NETWORK			
Ethernet	RJ45 (10/100 Base-T)	RJ45 (10/100/1000 Base-T)	RJ45 (10/100/1000 Base-T)
Video Compression	H.265, H.264, M-JPEG	H.265, H.264 (MP), M-JPEG	H.265, H.264, M-JPEG
Audio Compression	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	ADPCM 16K, G.726, G.711 u-Law, G.711 a-Law	-
IP Camera Protocol	DirectIP 2.0, ONVIF	DirectIP 2.0, ONVIF	DirectIP 2.0, ONVIF Profile S
Max. Frame Rate	4:3 mode: 2592 x 1944 (WDR) 16:9 mode: 2592 x 1456 (WDR)	30ips: 2944 x 2944	30ips: 1920 x 1080
Network Protocols	DirectIP 2.0 Protocol, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, Upnp	DirectIP 2.0 Protocol, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, Upnp	DirectIP 2.0 Protocol, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/UDP, RTSP/TCP, HTTP, HTTPS, FTP, SNMP, SMTP, FEN, mDNS, Upnp
etc	Remote Access, AI Analytics, Image Stabilizer	-	-
GENERAL			
Explosion Proof Rate	Ex db IIC T6 Gb Ex tD A21 T80°C	Ex db IIC T6 Gb Ex tD A21 T80°C	Ex db IIC T6 Gb Ex tD A21 T80°C
Operating Temperature	-40°C ~ +60°C	-40°C ~ +55°C	-40°C ~ +60°C
Power Source	PoE (48Vdc)	PoE (48Vdc)	PoE (48Vdc)
Power Consumption	≤11W	≤10.6W	≤15.3W (Heater, Fan)
Materials	Stainless Steel 316L	Stainless Steel 316L	Stainless Steel 316L
Dimensions (W x H x D)	Ø156 x 134mm	Ø180 x 64mm	Ø245 x 386mm
Weight	3.7kg	3.7kg	12.7kg
Outdoor Ready	IP67	IP67	IP67

IDIS SPECIALTY CAMERAS

Explosion Proof Cameras

Video Technology Designed for Hazardous
and High-Risk Environments





SPECIALTY BRACKET ACCESSORY

	Ceiling Mount	Wall Mount
	DA-CM1100EX	DA-WM1100EX
Model Name		
Compatible Model	DC-S3283	DC-S3283
Material	SUS316L	SUS316L
Dimensions (W x H x D)	151 x 151 x 162mm	151 x 151 x 236mm
Weight	2.5kg	2.5kg

SPECIALTY BOX HOUSING

	Box Housing
	DA-BH1100EX
Model Name	
ENVIRONMENT	
Explosion-Proof Rating	Ex d IIC T6 / Ex td A21 T85°C
Dust and Waterproof Rating	IP66
Operating Ambient Temperature	-20°C ~ +60°C
Design Compliance Standards	Ministry of Employment and Labor Notification No. 2020-33
Installation Standard	KS C IEC 60079-14
Applicable Camera Models	DC-Z6292XL, DC-Z6291X, DC-Z6282X, DC-Z6281XL
EXTERNAL DESIGN	
External Dimensions	152 x 164 x 400mm
Internal Dimensions	78 x 78 x 275mm
Cable Inlet Size	PF1/2"
Weight	5kg
Material	Aluminium
POWER SUPPLY	
Power Source	Camera PoE (DC12V), FAN (DC12V)-Optional
Power Consumption	5W



ConteralP® Camera Series

Affordable. Advanced Features.

Contera® by AV Costar™ introduces a brand-new lineup of high-end megapixel (MP) IP cameras at an affordable price point. Contera brings in new advanced technologies such as H.265 compression with our brand new SNAPstream+™ bandwidth reduction technology, Smart IR LEDs with variable illumination, Enhanced WDR™ wide dynamic range up to 120dB, and an onboard storage capacity up to 256GB.

New programmable features such as Defog technology can further enhance the quality of raw megapixel surveillance footage while Analytics available in the EX Series can increase situational awareness.

ConteraIP cameras come in several distinct body styles to cover most project solution needs, including our unique installer-friendly housing designs with the ConteraIP LX Remote Setup, ConteraIP Outdoor Dome, and ConteraIP MicroDome LX first introduced in our MegaIP® camera line. ConteraIP cameras come with a choice of 1080p and 5MP resolutions at a full 30fps for all single-sensor models, 8MP or 20MP resolution with our quad-sensor models, up to 16MP resolution for dual-sensor models and 12MP for the ConteraIP Fisheye.



Two in One

Contera IP MicroDome Duo LX Camera

The ConteraIP MicroDome Duo features twin multi-megapixel cameras in a compact IK10/IP66 outdoor-ready housing, ideal for a variety of professional indoor/outdoor surveillance requirements. Applications include coverage of a hallway or walkway, monitoring POS terminals or ATMs, or for viewing of a single wide area or two distinct regions. ConteraIP MicroDome Duo is available with a choice of 4-, 10-, or 16-megapixel (MP) resolutions and supports interchangeable lenses from 2.4mm-16mm.

MICRO DOME DUO CAMERAS

Model Name	Micro Dome Duo		
	AV4956DN-28	AV10956DN-28	AV16956DN-28
	 Full HD 2MP x 2 NDAA Compliant	 5MP x 2 NDAA Compliant	 4K 8MP x 2 NDAA Compliant
Image Sensor	1080p (2.1MP) CMOS Progressive Sensor x 2	5MP CMOS Progressive Sensor x 2	8MP CMOS Progressive Sensor x 2
Max. Resolution	4MP (1920 x 1080) x 2	10MP (2592 x 1944) x 2	16MP (3840 x 2160) x 2
Lens Type	Fixed-focal	Fixed-focal	Fixed-focal
Focal Length	f = 2.8mm	f = 2.8mm	f = 2.8mm
Aperture	F1.6	F1.6	F1.6
Iris Control	Auto / Manual	Auto / Manual	Auto / Manual
Angular Field of View	106.7° (H)	98° (H)	106.7° (H)
Pan / Tilt Range	3 Axis Camera Adjustment w / 359° pan and 90° tilt and 360° z-axis	3 Axis Camera Adjustment w / 359° pan and 90° tilt and 360° z-axis	3 Axis Camera Adjustment w / 359° pan and 90° tilt and 360° z-axis
Min. Illumination	Colour: 0.04 lux, B/W: 0.004 lux	Colour: 0.15 lux, B/W: 0.015 lux	Colour: 0.18 lux, B/W: 0.018 lux
Dynamic Range	100dB	100dB	100dB
Day and Night	Auto / Manual	Yes	Yes
IR	No	No	No
IR Distance (LEDs)	NA	NA	NA
Image Stabilizer	No	No	No
De-fog	No	No	No
Video Out	NA	NA	NA
Video Compression	H.265, H.264, M-JPEG	H.265, H.264, M-JPEG	H.265/H.264/M-JPEG
Intelligent Codec (SNAPstream+)	Yes	Yes	Yes
Audio Compression	NA	NA	NA
Max. Frame Rate	30fps	15fps	15fps
Ethernet	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45
Recording Session Buffer (NLTsrec)	NA	NA	NA
Edge Storage	micro SDXC slot up to 1TB (card not included)	micro SDXC slot up to 1TB (card not included)	micro SDXC slot up to 1TB (card not included)
Trigger Event	Motion Detection, Tampering Aetection, Alarm In	Motion Detection, Tampering Aetection, Alarm In	Motion Detection, Tampering Aetection, Alarm In
Audio	Yes	Yes	Yes
Audio In / Out	Line In (with Amplification) / Line Output	Line In (with Amplification) / Line Output	Line In (with Amplification) / Line Output
Alarm In / Out	1 Input (Wet Contact) / 1 Output (Wet Contact)	1 Input (Wet Contact) / 1 Output (Wet Contact)	1 Input (Wet Contact) / 1 Output (Wet Contact)
Vandal Proof Casing	IK10	IK10	IK10
Outdoor Ready	IP66	IP66	IP66
Operating Temperature	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)
Dimensions (W x H x D)	[Unit] 71.9 x 103 x 163mm (2.83" x 4.06" x 6.42") [Packaged] 95 x 120 x 180mm (3.74" x 4.72" x 7.09")	[Unit] 71.9 x 103 x 163mm (2.83" x 4.06" x 6.42") [Packaged] 95 x 120 x 180mm (3.74" x 4.72" x 7.09")	[Unit] 71.9 x 103 x 163mm (2.83" x 4.06" x 6.42") [Packaged] 95 x 120 x 180mm (3.74" x 4.72" x 7.09")
Weight	[Unit] 1.0kg (2.2lbs) [Packaged] 1.2kg (2.6lbs)	[Unit] 1.0kg (2.2lbs) [Packaged] 1.2kg (2.6lbs)	[Unit] 1.0kg (2.2lbs) [Packaged] 1.2kg (2.6lbs)
Power Source	PoE, 12 ~ 48VDC, 24VAC	PoE, 12 ~ 48VDC, 24VAC	PoE, 12 ~ 48VDC, 24VAC
Power Consumption	10.5W max	10.5W max	10.5W max
Multi sensor	2 Sensor Camera	2 Sensor Camera	2 Sensor Camera
IP Camera Protocol	Onvif Profile S, G, and T conformant	Onvif Profile S, G, and T conformant	Onvif Profile S, G, and T conformant
PTZ	NA	NA	NA
Remote Zoom	No	No	No
Remote Focus	Yes	Yes	Yes
Analytics	No	No	No

MULTI-IMAGER CAMERAS

Model Name	Multi-Imager (Omni LX Remote Setup)		
	AV20576RS	AV20576RS-QDRJ45	AV20576RSIR
	 	 	 
Image Sensor	5MP CMOS Progressive Sensor x 4	5MP CMOS Progressive Sensor x 4	5MP CMOS Progressive Sensor x 4
Max. Resolution	20MP (2592 x 1944) x 4	20MP (2592 x 1944) x 4	20MP (2592 x 1944) x 4
Lens Type	Motorised Lens	Motorised Lens	Motorised Lens
Focal Length	f = 3.6 ~ 6.6mm	f = 3.6 ~ 6.6mm	f = 2.7 ~ 13.5mm
Aperture	F1.6	F1.6	F1.6
Iris Control	Auto / Manual	Auto / Manual	Auto / Manual
Angular Field of View	42° ~ 96° (H)	42° ~ 96° (H)	30° ~ 101° (H)
Pan / Tilt Range	2 Axis Motorised	2 Axis Motorised	2 Axis Motorised
Min. Illumination	Colour: 0.15 lux, B/W: 0.015 lux	Colour: 0.15 lux, B/W: 0.015 lux	Colour: 0.15 lux, B/W: 0.015 lux
Dynamic Range	120dB DOL	120dB DOL	120dB DOL
Day and Night	Yes	Yes	Yes
IR	No	No	Yes
IR Distance (LEDs)	NA	NA	98.4ft (30m)
Image Stabilizer	No	No	No
De-fog	No	No	No
Video Out	NA	NA	NA
Video Compression	H.265, H.264, M-JPEG	H.265, H.264, M-JPEG	H.265, H.264, M-JPEG
Intelligent Codec (SNAPstream+)	Yes	Yes	Yes
Audio Compression	G.711 PCM 8 kHz/8 bit	G.711 PCM 8 kHz/8 bit	G.711 PCM 8 kHz/8 bit
Max. Frame Rate	30fps	30fps	30fps
Ethernet	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45
Recording Session Buffer (NLTsrec)	NA	NA	NA
Edge Storage	micro SDXC slot up to 1TB (card not included)	micro SDXC slot up to 1TB (card not included)	2 x micro SDXC slots up to 1TB each (cards not included)
Trigger Event	Motion Detection, Tampering Aetction, Alarm In, AI Video	Motion Detection, Tampering Aetction, Alarm In, AI Video	Motion Detection, Tampering Aetction, Alarm In, AI Video
Audio	Yes	Yes	Yes
Audio In / Out	Line In (with Amplification) / Line Output	Line In (with Amplification) / Line Output	Line In (with Amplification) / Line Output
Alarm In / Out	3 Input (Wet Contact) / 1 Output (Wet Contact)	4 Input (Wet Contact) / 1 Output (Wet Contact)	5 Input (Wet Contact) / 1 Output (Wet Contact)
Vandal Proof Casing	IK10	IK10	IK10
Outdoor Ready	IP66	IP66	IP66
Operating Temperature	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)
Dimensions (W x H x D)	[Unit] Ø223.4 x 125.4mm (Ø8.8" x 4.9") [Bubble Only] Ø183.3 x 59.3mm (Ø7.2" x 2.3") [Packaged] 281 x 281 x 188mm (11.1" x 11.1" x 7.4")	[Unit] Ø223.4 x 125.4mm (Ø8.8" x 4.9") [Bubble Only] Ø183.3 x 59.3mm (Ø7.2" x 2.3") [Packaged] 281 x 281 x 188mm (11.1" x 11.1" x 7.4")	[Unit] Ø247 x 202mm (9.72" x 7.95") [Bubble Only] Ø214.3 x 76.3mm (Ø8.44" x 3") [Packaged] 725 x 370 x 330mm (28.54" x 14.57" x 12.99")
Weight	[Unit] 2.36kg (5.2lbs) [Packaged] 2.68kg (5.9lbs)	[Unit] 2.36kg (5.2lbs) [Packaged] 2.68kg (5.9lbs)	[Unit] 3.43kg (7.55lbs) [Packaged] 4.58kg (10.09lbs)
Power Source	PoE+ / 24 ~ 48VDC / 24VAC	PoE+ / 24 ~ 48VDC / 24VAC	PoE++ / 24VDC / 24VAC
Power Consumption	25.W max	25.W max	40W max
Multi sensor	4 Sensor Camera	4 Sensor Camera	4 Sensor Camera
IP Camera Protocol	Onvif Profile S, G, M, and T conformant	Onvif Profile S, G, M, and T conformant	Onvif Profile S, G, M, and T conformant
PTZ	NA	NA	NA
Remote Zoom	Yes	Yes	Yes
Remote Focus	Yes	Yes	Yes
Analytics	Std-Included Advanced-Optional	Std-Included Advanced-Optional	Std-Included Advanced-Optional

MULTI-IMAGER CAMERAS

Model Name	Multi-Imager (Omni LX Remote Setup)		
	AV20576RSIR-QDRJ45	AV32576RSIR	AV32576RSIR-QDRJ45
	 5MP x 4 NDAA Compliant	 4K 8MP x 4 NDAA Compliant	 4K 8MP x 4 NDAA Compliant
Image Sensor	5MP CMOS Progressive Sensor x 4	8MP CMOS Progressive Sensor x 4	8MP CMOS Progressive Sensor x 4
Max. Resolution	20MP	32MP	32MP
	(2592 x 1944) x 4	(3840 x 2160) x 4	(3840 x 2160) x 4
Lens Type	Motorised Lens	Motorised Lens	Motorised Lens
Focal Length	f = 2.7 ~ 13.5mm	f = 4 ~ 10mm	f = 4 ~ 10mm
Aperture	F1.6	F1.6	F1.6
Iris Control	Auto / Manual	Auto / Manual	Auto / Manual
Angular Field of View	30° ~ 101° (H)	45° ~ 110° (H)	45° ~ 110° (H)
Pan / Tilt Range	2 Axis Motorised	2 Axis Motorised	2 Axis Motorised
Min. Illumination	Colour: 0.15 lux, B/W: 0.015 lux	Colour: 0.15 lux, B/W: 0.015 lux	Colour: 0.15 lux, B/W: 0.015 lux
Dynamic Range	120dB DOL	120dB DOL	120dB DOL
Day and Night	Yes	Yes	Yes
IR	Yes	Yes	Yes
IR Distance (LEDs)	98.4ft (30m)	98.4ft (30m)	98.4ft (30m)
Image Stabilizer	No	No	No
De-fog	No	No	No
Video Out	NA	NA	NA
Video Compression	H.265, H.264, M-JPEG	H.265, H.264, M-JPEG	H.265, H.264, M-JPEG
Intelligent Codec (SNAPstream+)	Yes	Yes	Yes
Audio Compression	G.711 PCM 8 kHz/8 bit	G.711 PCM 8 kHz/8 bit	G.711 PCM 8 kHz/8 bit
Max. Frame Rate	30fps	30fps	30fps
Ethernet	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45
Recording Session Buffer (NLTsrec)	NA	NA	NA
Edge Storage	2 x micro SDXC slots up to 1TB each (cards not included)	2 x micro SDXC slots up to 1TB each (cards not included)	2 x micro SDXC slots up to 1TB each (cards not included)
Trigger Event	Motion Detection, Tampering Aetction, Alarm In, AI Video	Motion Detection, Tampering Aetction, Alarm In, AI Video	Motion Detection, Tampering Aetction, Alarm In, AI Video
Audio	Yes	Yes	Yes
Audio In / Out	Line In (with Amplification) / Line Output	Line In (with Amplification) / Line Output	Line In (with Amplification) / Line Output
Alarm In / Out	6 Input (Wet Contact) / 1 Output (Wet Contact)	7 Input (Wet Contact) / 1 Output (Wet Contact)	8 Input (Wet Contact) / 1 Output (Wet Contact)
Vandal Proof Casing	IK10	IK10	IK10
Outdoor Ready	IP66	IP66	IP66
Operating Temperature	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)
Dimensions (W x H x D)	[Unit] Ø247 x 202mm (9.72" x 7.95") [Bubble Only] Ø214.3 x 76.3mm (Ø8.44" x 3") [Packaged] 725 x 370 x 330mm (28.54" x 14.57" x 12.99")	[Unit] Ø247 x 202mm (9.72" x 7.95") [Bubble Only] Ø214.3 x 76.3mm (Ø8.44" x 3") [Packaged] 725 x 370 x 330mm (28.54" x 14.57" x 12.99")	[Unit] Ø247 x 202mm (9.72" x 7.95") [Bubble Only] Ø214.3 x 76.3mm (Ø8.44" x 3") [Packaged] 725 x 370 x 330mm (28.54" x 14.57" x 12.99")
Weight	[Unit] 3.43kg (7.55lbs) [Packaged] 4.58kg (10.09lbs)	[Unit] 3.43kg (7.55lbs) [Packaged] 4.58kg (10.09lbs)	[Unit] 3.43kg (7.55lbs) [Packaged] 4.58kg (10.09lbs)
Power Source	PoE++ / 24VDC / 24VAC	PoE++ / 24VDC / 24VAC	PoE++ / 24VDC / 24VAC
Power Consumption	40W max	40W max	40W max
Multi sensor	4 Sensor Camera	4 Sensor Camera	4 Sensor Camera
IP Camera Protocol	Onvif Profile S, G, M, and T conformant	Onvif Profile S, G, M, and T conformant	Onvif Profile S, G, M, and T conformant
PTZ	NA	NA	NA
Remote Zoom	Yes	Yes	Yes
Remote Focus	Yes	Yes	Yes
Analytics	Std-Included Advanced-Optional	Std-Included Advanced-Optional	Std-Included Advanced-Optional



Low-Profile, Multi-Sensor Versatility

Omni LX

Omni LX packs four remote focus 3-axis gimbals into a low-profile and compact housing.

With 70+ possible sensor placements, including standard and custom configurations, and supports interchangeable lenses from 2.4mm-16mm with remote focus, the possibilities are almost endless.

MULTI-IMAGER CAMERAS

Model Name	Multi-Imager (Omni LX)	
	AV8576DN-28	AV20576DN-28
	 Full HD 2MP x 4 NDA Compliant	 5MP x 4 NDA Compliant
Image Sensor	2MP CMOS Progressive Sensor x 4	5MP CMOS Progressive Sensor x 4
Max. Resolution	8MP (1920 x 1080) x 4	20MP (2592 x 1944) x 4
Lens Type	Fixed-focal	Fixed-focal
Focal Length	f = 2.8mm	f = 2.8mm
Aperture	F1.6	F1.6
Iris Control	Auto / Manual	Auto / Manual
Angular Field of View	98° (H)	98° (H)
Pan / Tilt Range	3 Axis Adjustable	3 Axis Adjustable
Min. Illumination	Colour: 0.15 lux, B/W: 0.015 lux	Colour: 0.15 lux, B/W: 0.015 lux
Dynamic Range	100dB	100dB
Day and Night	Yes	Yes
IR	No	No
IR Distance (LEDs)	NA	NA
Image Stabilizer	No	No
De-fog	No	No
Video Out	NA	NA
Video Compression	H.265, H.264, M-JPEG	H.265, H.264, M-JPEG
Intelligent Codec (SNAPstream+)	Yes	Yes
Audio Compression	G.711 PCM 8 kHz/8 bit	G.711 PCM 8 kHz/8 bit
Max. Frame Rate	30fps	15fps
Ethernet	10/100 Base-T Ethernet network interface, RJ45	10/100 Base-T Ethernet network interface, RJ45
Recording Session Buffer (NLTsrec)	NA	NA
Edge Storage	micro SDXC slot up to 1TB (card not included)	micro SDXC slot up to 1TB (card not included)
Trigger Event	Motion Detection, Tampering Detection, Alarm In	Motion Detection, Tampering Detection, Alarm In
Audio	Yes	Yes
Audio In / Out	Line in (with Amplification) / Line Output	Line In (with Amplification) / Line Output
Alarm In / Out	9 Input (Wet Contact) / 1 Output (Wet Contact)	10 Input (Wet Contact) / 1 Output (Wet Contact)
Vandal Proof Casing	IK10	IK10
Outdoor Ready	IP66	IP66
Operating Temperature	-40°C ~ +50°C (-40°F ~ 122°F)	-40°C ~ +50°C (-40°F ~ 122°F)
Dimensions (W x H x D)	[Unit] Ø196 x 78.5mm (Ø7.7" x 3.1") [Bubble Only] Ø169.2 x 33.4mm (Ø6.7" x 1.3") [Packaged] 203 x 203 x 102mm (8" x 8" x 4")	[Unit] Ø196 x 78.5mm (Ø7.7" x 3.1") [Bubble Only] Ø169.2 x 33.4mm (Ø6.7" x 1.3") [Packaged] 203 x 203 x 102mm (8" x 8" x 4")
Weight	[Unit] 1.7kg (3.8lbs) [Packaged] 2.0kg (4.4lbs)	[Unit] 1.7kg (3.8lbs) [Packaged] 2.0kg (4.4lbs)
Power Source	PoE+ / 12 ~ 48VDC / 24VAC	PoE+ / 12 ~ 48VDC / 24VAC
Power Consumption	14W max	14W max
Multi sensor	4 Sensor Camera	4 Sensor Camera
IP Camera Protocol	Onvif Profile S, G, and T conformant	Onvif Profile S, G, and T conformant
PTZ	NA	NA
Remote Zoom	No	No
Remote Focus	Yes	Yes
Analytics	No	No



The Most Advanced HD Analogue Over Coax Solution

IDIS DirectCX, the industry's most advanced Analogue HD over coax solution. Based on High Definition Transfer Video Interface (HD-TVI) technology, IDIS incorporates its expertise in image processing to provide unrivaled HD recording performance at a lower cost.



HD ANALOGUE RECORDERS & CAMERAS

Overlapped Recording

When a user changes the HD Analogue system time to the past point, video data for the overlapped time will be recorded in different segments. This enables video data for the overlapped time to be searched in different time sets and prevents any possible loss of video data or discrepancy on time-based search.



TR-4000 SERIES

Model Name	DirectCX 16 channel H.265 Recorder	DirectCX 8 channel H.265 Recorder
	TR-4516(R)	TR-4508(R)
		
VIDEO		
Video Inputs	16BNC	8BNC
Supported Camera	HD Analog: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL	HD Analog: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL
Video Outputs	1 HDMI, 1 VGA, 1 BNC (Spot)	1 HDMI, 1 VGA, 1 BNC (Spot)
Display Resolution	HDMI: 3840 x 2160, 1920 x 1080, 1440 x 900, 1280 x 1024 VGA: 1920 x 1080, 1440 x 900, 1280 x 1024	HDMI: 3840 x 2160, 1920 x 1080, 1440 x 900, 1280 x 1024 VGA: 1920 x 1080, 1440 x 900, 1280 x 1024
Display Speed	Up to 480ips	Up to 240ips
RECORDING		
Recording Resolution	2560 x 1920, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 480, 720 x 480, 960 x 240, 720 x 240, 480 x 240, 360 x 240	2560 x 1920, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 480, 720 x 480, 960 x 240, 720 x 240, 480 x 240, 360 x 240
Frame Rate	480ips @ 1080p, 288fps @ 3MP, 240ips @ 4MP, 160ips @ 5MP	240ips @ 1080P, 144ips @ 3MP, 120ips @ 4MP, 80ips @ 5MP
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Events	Motion, Tampering, Video Loss, Alarm In, Text-In, System	Motion, Tampering, Video Loss, Alarm In, Text-In, System
PLAYBACK		
Performance	16ch 1080p Synchronous Playback	8ch 1080p Synchronous Playback
Search Mode	Time-Lapse, Event Log, Text-In	Time-Lapse, Event Log, Text-In
Digital Zoom	x 2 ~ x 7	x 2 ~ x 7
STORAGE		
HDD	[TR-4516] SATA x 4, eSATA x 1 [TR-4516R] SATA x 4, eSATA x 1, RAID 1 Supported	[TR-4508] SATA x 4, eSATA x 1 [TR-4508R] SATA x 4, eSATA x 1, RAID 1 Supported
Data Export Device	USB HDD, USB Stick	USB HDD, USB Stick
NETWORK		
Client Connection	Gigabit Ethernet x 1	Gigabit Ethernet x 1
Transmission Speed	30ips @ Full HD per channel, same as recording stream	30ips @ Full HD per channel, same as recording stream
INTERFACE		
Audio In / Out	4 RCA / 1 RCA + 1 HDMI	4 RCA / 1 RCA + 1 HDMI
Alarm In / Out	16 In / 4 Relay Out	8 In / 4 Relay Out
Alarm Reset In	1	1
Serial Interface	RS232 / RS485 (Terminal Block)	RS232 / RS485 (Terminal Block)
GENERAL		
Operating System	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	430 x 88 x 427mm (16.9" x 3.5" x 16.8")	430 x 88 x 427mm (16.9" x 3.5" x 16.8")
Unit Weight	6.2kg (13.7lbs) (with 2 x 4TB HDD)	6.2kg (13.7lbs) (with 2 x 4TB HDD)
Operating Humidity	0 % ~ 90 %	0% ~ 90%
Power Input	100 ~ 240V~, 50/60Hz, ≤2.0A	100 ~ 240V~, 50/60Hz, ≤2.0A
Power Consumption	100 ~ 240V~, 50/60Hz, 1.0 ~ 0.5A, 80W	100 ~ 240V~, 50/60Hz, 1.0 ~ 0.5A, 80W
Approvals	FCC, CE, KC, CB, UL, PSE	FCC, CE, KC, CB, UL, PSE

TR-4000 SERIES


Model Name	DirectCX 16 channel H.265 Recorder	DirectCX PoC 8 channel H.265 Recorder	DirectCX 8 channel H.265 Recorder
	TR-2516	TR-2508P	TR-2508
	 NDA Compliant	 NDA Compliant	 NDA Compliant
VIDEO			
Video Inputs	16BNC	8BNC	8BNC
Supported Camera Types	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL
Video Outputs	1 HDMI, 1 VGA	1 HDMI, 1 VGA	1 HDMI, 1 VGA
Display Resolution	HDMI: 3840 x 2160, 1920 x 1080, 1280 x 1024 VGA: 1920 x 1080, 1280 x 1024	HDMI: 3840 x 2160, 1920 x 1080, 1280 x 1024 VGA: 1920 x 1080, 1280 x 1024	HDMI: 3840 x 2160, 1920 x 1080, 1280 x 1024 VGA: 1920 x 1080, 1280 x 1024
Display Speed	Up to 480ips	Up to 240ips	Up to 240ips
RECORDING			
Recording Resolution	2560 x 1920, 1280 x 1920, 2560 x 1440, 1280 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 576, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240	2560 x 1920, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 576, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240	2560 x 1920, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 576, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240
Frame Rate	240ips @ 1080P, 160ips @ 3MP, 240ips @ 4MHALF, 112ips @ 4MP, 160ips @ 5MHALF, 112ips @ 5MP	240ips @ 1080P, 144ips @ 3MP, 120ips @ 4MP, 80ips @ 5MP	240ips @ 1080P, 144ips @ 3MP, 120ips @ 4MP, 80ips @ 5MP
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Events	Motion, Video Loss, Video Blind, Alarm In, Text-In, System	Motion, Video Loss, Video Blind, Alarm In, Text-In, System	Motion, Video Loss, Video Blind, Alarm In, Text-In, System
PLAYBACK			
Performance	16ch Synchronous Playback	8ch Synchronous Playback	8ch Synchronous Playback
Search Mode	Time-Lapse, Event Log, Text-In, Thumbnail	Time-Lapse, Event Log, Text-In, Thumbnail	Time-Lapse, Event Log, Text-In, Thumbnail
Digital Zoom	x2 ~ x7	x2 ~ x7	x2 ~ x7
STORAGE			
HDD	SATA x2	SATA x2	SATA x2
Data Export Device	USB HDD, USB Stick	USB HDD, USB Stick	USB HDD, USB Stick
NETWORK			
Client Connection	Gigabit Ethernet x1	Fast Ethernet x1	Fast Ethernet x1
Transmission Speed	15ips @ Full HD per channel, same as recording stream	30ips @ Full HD per channel, same as recording stream	30ips @ Full HD per channel, same as recording stream
INTERFACE			
Audio In / Out	4 RCA / 1 RCA + 1 HDMI	4 RCA / 1 RCA + 1 HDMI	4 RCA / 1 RCA + 1 HDMI
Alarm In / Out	4 In / 1 Relay Out	8 In / 1 Relay Out	8 In / 1 Relay Out
Alarm Reset In	-	-	-
Serial Interface	RS232 / RS485 (Terminal Block)	RS232 / RS485 (Terminal Block)	RS232 / RS485 (Terminal Block)
GENERAL			
Operating System	Embedded Linux	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	340 x 46.5 x 315.5mm (13.4" x 1.8 x 12.4")	340 x 44 x 302.3mm (13.4" x 1.7" x 11.9")	300 x 67 x 243.6mm (11.8" x 2.6 x 9.6")
Unit Weight	3.1kg (6.83lb) (with 4TB 2HDDs)	2.9kg (6.39lb) (with 2 2TB HDD)	3.0kg (with 2 2TB HDD)
Operating Humidity	0% ~ 90%	0% ~ 90%	0% ~ 90%
Power Input	Adaptor Input: 100 ~ 240V AC, 50/60Hz, 1.5A, Output: 12V DC, 5A	Adaptor Input: 100 ~ 240V AC, 50/60Hz, 2.5A, Output: 42V DC, 3A	Adaptor Input: 100-240V AC, 50/60Hz, 1.5A, Output: 12V DC, 5A
Power Consumption	12V=, 1.72A, 20.64W	42V=, 2.5A, 105W	12V=, 1.84A, 22.1W
Approvals	FCC, CE, KC	FCC, CE, KC	FCC, CE, KC

TR-2000 SERIES

Model Name	DirectCX PoC 4 channel H.265 Recorder	DirectCX 4 channel H.265 Recorder
	TR-2504P	TR-2504
		
VIDEO		
Video Inputs	4BNC	4BNC
Supported Camera Types	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL
Video Outputs	1 HDMI, 1 VGA	1 HDMI, 1 VGA
Display Resolution	HDMI: 3840 x 2160, 1920 x 1080, 1280 x 1024 VGA: 1920 x 1080, 1280 x 1024	HDMI: 3840 x 2160, 1920 x 1080, 1280 x 1024 VGA: 1920 x 1080, 1280 x 1024
Display Speed	Up to 120ips	Up to 120ips
RECORDING		
Recording Resolution	2560 x 1920, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 576, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240	2560 x 1920, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 576, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240
Frame Rate	120ips @ 1080P, 72ips @ 3MP, 60ips @ 4MP, 40ips @ 5MP	120ips @ 1080P, 72ips @ 3MP, 60ips @ 4MP, 40ips @ 5MP
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Events	Motion, Video Loss, Video Blind, Alarm In, Text-In, System	Motion, Video Loss, Video Blind, Alarm In, Text-In, System
PLAYBACK		
Performance	4ch Synchronous Playback	4ch Synchronous Playback
Search Mode	Time-Lapse, Event Log, Text-In, Thumbnail	Time-Lapse, Event Log, Text-In, Thumbnail
Digital Zoom	x2 ~ x7	x2 ~ x7
STORAGE		
HDD	SATA x2	SATA x2
Data Export Device	USB HDD, USB Stick	USB HDD, USB Stick
NETWORK		
Client Connection	Fast Ethernet x1	Fast Ethernet x1
Transmission Speed	30ips @ Full HD per channel, same as recording stream	30ips @ Full HD per Channel, Same as Recording Stream
INTERFACE		
Audio In / Out	4 RCA / 1 RCA + 1 HDMI	4 RCA / 1 RCA + 1 HDMI
Alarm In / Out	4 In / 1 Relay Out	4 In / 1 Relay Out
Alarm Reset In	-	-
Serial Interface	RS232 / RS485 (Terminal Block)	RS232 / RS485 (Terminal Block)
GENERAL		
Operating System	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	340 x 44 x 302.3mm (13.4" x 1.7" x 11.9")	300 x 67 x 243.6mm (11.8" x 2.6 x 9.6")
Unit Weight	2.68kg (5.91lb) (with 2 2TB HDD)	3.0kg (with 2 2TB HDD)
Operating Humidity	0% ~ 90%	0% ~ 90%
Power Input	Adaptor Input: 100 ~ 240V AC, 50/60Hz, 2.5A, Output: 42V DC, 2A	Adaptor Input: 100 ~ 240V AC, 50/60Hz, 1.5A, Output: 12V DC, 5A
Power Consumption	42V=, 1.57A, 66W	12V=, 1.7A, 20.4W
Approvals	-	FCC, CE, KC

TR-1000 SERIES IDIS Compact Solution

Quality Compact Solution Packed with
Essential and Easy-To-Use Features



	DirectCX 8 channel H.265 Recorder	DirectCX 4 channel H.265 Recorder
	TR-1508	TR-1504
Model Name	 	 
VIDEO		
Video Inputs	8BNC	4BNC
Supported Camera Types	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL	HD-TVI: 5MP, 4MP, 3MP, 1080P, 720P AHD: 5MP, 4MP, 3MP, 1080P, 720P CVBS: NTSC / PAL
Video Outputs	1 HDMI, 1 BNC (Spot)	1 HDMI, 1 VGA, 1 BNC (Spot)
Display Resolution	HDMI / VGA: 1920 x 1080, 1280 x 1024 Composite: 720x480 (NTSC), 720 x 576 (PAL)	HDMI / VGA: 1920 x 1080, 1280 x 1024 Composite: 720x480 (NTSC), 720 x 576 (PAL)
Display Speed	Up to 120ips	Up to 120ips
RECORDING		
Recording Resolution	2560 x 1944, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240	2560 x 1944, 2560 x 1440, 1920 x 1536, 1920 x 1080, 1280 x 720, 960 x 480, 720 x 576, 720 x 480, 960 x 288, 960 x 240, 640 x 360, 720 x 288, 720 x 240, 480 x 288, 480 x 240, 360 x 288, 360 x 240
Frame Rate	240ips @ 1080P, 144ips @ 3MP, 120ips @ 4MP, 80ips @ 5MP	120ips @ 1080P, 72ips @ 3MP, 60ips @ 4MP, 40ips @ 5MP
Recording Mode	Time-Lapse, Event, Pre-Event, Panic	Time-Lapse, Event, Pre-Event, Panic
Trigger Events	Motion, Video loss, Alarm in, System	Motion, Video loss, Alarm in, System
PLAYBACK		
Performance	8ch Synchronous Playback	4ch 1080p Synchronous Playback
Search Mode	Time-Lapse, Event Log	Time-Lapse, Event Log
Digital Zoom	x2 ~ x7	x2 ~ x7
STORAGE		
HDD	SATA x1	SATA x1
Data Export Device	USB HDD, USB Stick	USB HDD, USB Stick
NETWORK		
Client Connection	Fast Ethernet x1	Fast Ethernet x1
Transmission Speed	30ips @ Full HD per channel, same as recording stream	30ips @ Full HD per channel, same as recording stream
INTERFACE		
Audio In / Out	1 RCA / 1 RCA + 1 HDMI	1 RCA / 1 RCA + 1 HDMI
Alarm In / Out	4 In / 1 Relay Out	4 In / 1 Relay Out
Alarm Reset In	-	-
Serial Interface	-	-
GENERAL		
Operating System	Embedded Linux	Embedded Linux
Dimensions (W x H x D)	230 x 46.5 x 241.1mm (9.1" x 1.8" x 9.5")	205 x 44.5 x 223.4mm (8.07" x 1.75" x 8.80")
Unit Weight	1.65kg (3.6lb) (with 4TB HDD)	1.3kg (0.7lb) (with 2TB HDD)
Operating Humidity	0% ~ 90%	0% ~ 90%
Power Input	(a) US/JP Adaptor Input: 100 ~ 240VAC, 50/60Hz, 1.0A, Output: 12VDC, 3A (b) UK, ETC Adaptor Input: 100 ~ 240VAC, 50/60Hz, 1.2A, Output: 12VDC, 3A (c) KR Adaptor Input: 100 ~ 240VAC, 50/60Hz, 0.8A, Output: 12VDC, 3A	(a) US/JP Adaptor Input: 100 ~ 240VAC, 50/60Hz, 1.0A, Output: 12VDC, 3A (b) UK, ETC Adaptor Input: 100 ~ 240VAC, 50/60Hz, 1.2A, Output: 12VDC, 3A (c) KR Adaptor Input: 100 ~ 240VAC, 50/60Hz, 0.8A, Output: 12VDC, 3A
Power Consumption	12V=, 1.1A, 13.2W	12V=, 0.75A, 9W
Approvals	FCC, CE, KC	FCC, KC

HD-TVI BULLET CAMERAS

Model Name	DirectCX 5MP IR Dome Camera		
	TC-D5532WRX	TC-D5532RX	TC-D5511RX
	 5MP	 5MP	 5MP
VIDEO			
Image Sensor	1/2.8" CMOS Sensor	1/2.8" CMOS Sensor	1/2.8" CMOS Sensor
Max. Resolution	2592 x 1944	2592 x 1944	2592 x 1944
Scanning Mode	Progressive Scan	Progressive Scan	Progressive Scan
Frame Rate	TVI: 20ips @ 5MP, 12.5ips @ 5MP, 30ips @ 4MP, 30ips @ 2MP AHD: 20ips @ 5MP, 12.5ips @ 5MP, 30ips @ 4MP, 30ips @ 2MP CVBS: NTSC / PAL (for previewing video)	TVI: 20ips @ 5MP, 12.5ips @ 5MP, 30ips @ 4MP, 30ips @ 2MP AHD: 20ips @ 5MP, 12.5ips @ 5MP, 30ips @ 4MP, 30ips @ 2MP CVBS: NTSC / PAL (for previewing video)	TVI: 20ips @ 5MP, 12.5ips @ 5MP, 30ips @ 4MP, 30ips @ 2MP AHD: 20ips @ 5MP, 12.5ips @ 5MP, 30ips @ 4MP, 30ips @ 2MP CVBS: NTSC / PAL (for previewing video)
Lens Type	Motorised Vari-focal	Motorised Vari-focal	Fixed-focal
Focal Length	f = 3.0 ~ 13.5mm	f = 3.0 ~ 13.5mm	f = 2.0mm
Iris Control	DC Iris	DC Iris	Fixed Iris
Angular Field of View	Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D)	Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D)	104.8° (H), 76.9° (V), 130° (D)
Pan / Tilt Range	Pan: -175° ~ 175°, Tilt: 0° ~ 67°, Rotate: -177° ~ 177°	Pan: -175° ~ 175°, Tilt: 0° ~ 67°, Rotate: -177° ~ 177°	Pan: -170° ~ 170°, Tilt: -5° ~ 67.5°, Rotate: -109° ~ 109°
Min. Illumination	Colour: 0.13 lux @ F1.4, B/W: 0 lux (IR LED On)	Colour: 0.13 lux @ F1.4, B/W: 0 lux (IR LED On)	Colour: 0.15 lux @ F 2.0, B/W: 0 lux (IR LED On)
Dynamic Range	120dB (True WDR)	120dB (True WDR)	120dB (True WDR)
Day and Night	Yes (ICR)	Yes (ICR)	Yes (ICR)
IR Distance (LEDs)	30m / 98.4ft (4ea)	30m / 98.4ft (4ea)	20m / 65.6ft (4ea)
Video Out	1 HD BNC (Signal Switchable)	1 HD BNC (Signal Switchable)	1 HD BNC (Signal Switchable)
FUNCTION			
Sens-Up	Off / x2 ~ x32	Off / x2 ~ x32	Off / x2 ~ x32
Wide Dynamic Range (WDR)	Off / Frame / Line (Low, Middle, High) ROI Mode Availbale	Off / Frame / Line (Low, Middle, High) ROI Mode Availbale	Off / Frame / Line (Low, Middle, High) ROI Mode Availbale
Backlight Compensation (BLC)	Off / On	Off / On	Off / On
HLC	1 ~ 20 Level Adjustable (All Day / Night Only)	1 ~ 20 Level Adjustable (All Day / Night Only)	1 ~ 20 Level Adjustable (All Day / Night Only)
Privacy Masking	Off / On (24 Zone) BOX:16 POLYGON:8	Off / On (24 Zone) BOX:16 POLYGON:8	Off / On (24 Zone) BOX:16 POLYGON:8
Smart IR (IR Optimizer)	0 ~ 20 Level Adjustable	0 ~ 20 Level Adjustable	0 ~ 20 Level Adjustable
Digital Noise Reduction	Off / Low / Middle / High	Off / Low / Middle / High	Off / Low / Middle / High
De-fog	Off / On	Off / On	Off / On
Language	ENG / CHN / CHN(S) / JPN / KOR	ENG / CHN / CHN(S) / JPN / KOR	ENG / CHN / CHN(S) / JPN / KOR
Menu Control	OSD Button, TVI / AHD Coaxial Protocol	OSD Button, TVI / AHD Coaxial Protocol	OSD Button, TVI / AHD Coaxial Protocol
ENVIRONMENTAL			
Vandal Proof Casing	IK10	-	-
Outdoor Ready	IP67	-	-
Operating Temperature	-10°C ~ +55°C (14°C ~ +131°C) (Humidity: 0% ~ 90%)	-10°C ~ +50°C (+14°F ~ +122°F) (Humidity: 0% ~ 90%)	-10°C ~ +50°C (+14°F ~ +122°F) (Humidity: 0% ~ 90%)
MECHANICAL			
Dimensions (W x H x D)	Ø155 x 105mm (6.1" x 4.13")	Ø122 x 103.4mm (4.8" x 4.07")	Ø110 x 78mm (4.33" x 3.07")
Weight	0.815kg (1.8lb)	0.3kg (0.66lb)	0.177kg (0.39lb)
ELECTRICAL			
Power Source	DC12V, AC24V	DC12V, AC24V	DC12V
Power Consumption	DC 12V/8W, AC 24V/8.3W	DC 12V/8W, AC 24V/8.3W	3.4W

HD-TVI BULLET CAMERAS

DirectCX 5MP IR Bullet Camera	
TC-T5532WRX	
Model Name	 5MP
VIDEO	
Image Sensor	1/2.8" CMOS Sensor
Max. Resolution	2592 x 1944
Scanning Mode	Progressive Scan
Frame Rate	TVI: 20ips@5MP, 12.5ips@5MP, 30ips@4MP, 30ips@2MP AHD: 20ips@5MP, 12.5ips@5MP, 30ips@4MP, 30ips@2MP CVBS: NTSC/PAL (for previewing video)
Lens Type	Motorised Vari-focal
Focal Length	f = 3.0 ~ 13.5mm
Aperture	F 1.4 ~ 3.2
Iris Control	DC IRIS
Angular Field of View	Wide: 91° (H), 66° (V), 120° (D) Tele: 31° (H), 23° (V), 38° (D)
Min. Illumination	Colour: 0.13 lux @ F1.4, B/W: 0 lux (IR LED On)
Day and Night	Yes (ICR)
IR Distance (LEDs)	30m / 98.4ft (4ea)
Video Out	1 HD BNC (Signal Switchable)
FUNCTION	
Sens-Up	Off / x2 ~ x32
Wide Dynamic Range (WDR)	Off / Frame / Line (Low, Middle, High) ROI Mode Available
Backlight Compensation (BLC)	Off / On
HLC	1 ~ 20 Level Adjustable (All Day / Night Only)
Smart IR (IR Optimizer)	0 ~ 20 Level Adjustable
Digital Noise Reduction	Off / Low / Middle / High
De-Fog	Off / On
Language	ENG / CHN / CHN(S) / JPN / KOR
Menu Control	OSD Button, TVI / AHD Coaxial Protocol
ENVIRONMENTAL	
Vandal Proof Casing	IK10
Outdoor Ready	IP67
Storage Temperature	-20°C ~ +60°C (-4°F ~ +140°F) (Humidity: 0% ~ 95%)
Operating Temperature	-10°C ~ +55°C (+14°F ~ +131°F) (Humidity: 0% ~ 90%)
MECHANICAL	
Dimensions (W x H x D)	80 x 75 x 237mm (3.15" x 2.95" x 9.33")
Weight	0.87kg (1.92lb)
ELECTRICAL	
Power Source	DC12V, AC24V
Power Consumption	DC12 V/8W, AC 24 V/8.3W

ACCESS CONTROL SOLUTION

Our integrated access control and video surveillance management solution provides advanced system control for strengthened security and convenience. Users can manage people flow and access to facilities effectively by monitoring the real-time status of staff and visitors on-site. Historical data analysis provides comprehensive management reports and audit trails to satisfy industry, state and federal government specific regulations.



ACCESS CONTROL

Model Name	UBio-X Iris
	Premium Card & Fingerprint Recognition Terminal
	
OS	Embedded LINUX 3.4
Fingerprint Sensor Type	Slim / Flat Optical
CPU	Cortex-A9 Quad Core 1.4GHz
Memory	8Gbyte Flash DDR3 2GB RAM (512MB x 4)
Display	5" Colour TFT LCD with Touch
RF / Smart Card Option	13.56MHz Samrt Card Reader, 125KHz-EM, HID Prox / iClass (Optional) RF Card Reader
Capacity	Max User: 500,000 Fingerprint 1: 200,000 Templates <1sec> Event Logs: 10,000,000 Photo Logs: 50,000
Interface	RS-232 / RS-485 Wiegand IN / OUT Wifi (Optional) USB 2.0 OTG
Dimensions (W x H x D)	80 x 195.6 x 23.5mm (Upper) / 54.67 (Lower)
Approvals	KC, CE, FCC

Model Name	UBio-X Iris
	Multi-Biometric Iris & Fingerprint Recognition Terminal
	
Biometric	Iris & Fingerprint
CPU	Cortex-A9 Quad Core 1.0GHz
Memory	eMMC 16GByte DDR3 533MHz 2GB (512MB x 4)
Display	5" Touch LCD
RF / Smart Card Option	13.56MHz Samrt Card Reader (Module), ISO 14443A/B, MiFare, Felica, 125KHz RF Card Reader (Module), EM, 125KHz HID Prox Card Reader (Optional)
Image Standard	ISO/IEC 19794-6 2011 ISO/IEC 29794-6
Capacity	Up to 200,000 (1 Iris / 1 User) Up to 200,000 (1 Finger / 1 User) Iris 1: 40,000 <1> Fingerprint 1: 100,000 <1sec> Event Logs: 10,000,000 Photo Logs: 20,000
Dimensions (W x H x D)	160.6 x 214 .1 x 45.7mm
Approvals	KC, CE, FCC, IEC62471

Model Name	UBio-X Face Pro
	Face-to-Fingerprint & Card & QR & Password Recognition Terminal
	
Biometric	Face & FingerPrint
CPU	Quad Core 1.8GHz
Memory	16GB eMMC Flash +4GB (LPDDR4) Ram
Display	5" Colour Touch Screen
Interface	Externa 10 / 100M / 1000M 1 Port, RS-485, RS-232 2 Port, Wiegand IN / OUT 1 Port, Relay 2 Port, USB 2.0 1Port
Capacity	Face = 1: N: 30,000 / 1:1 30,000 FingerPrint = 1: N: 50,000 / 1:1 500,000 Event Log: 10,000,000 Picture Log: 20,000
Dimensions (W x H x D)	92 x 200 x 21mm
IP Rating	IP55
Approvals	KC, CE, FCC

Model Name	UBio-X Pro
	Advanced Face & Fingerprint Recognition Terminal
	
Biometric	Face / Fingerprint / Card
CPU	Cortex-A9 Quad Core 1.0GHz
Memory	eMMC 16GByte DDR3 2GB RAM (512MB x 4)
Display	5" Colour TFT LCD with Touch
RF / Smart Card Option	13.56MHz Smart Card Reader, 125KHz-EM, HID Prox / iClass (Optional) RF Card Reader
Interface	RS232/RS485, Wiegand In/Out, Wifi (Optional), SD Card Scket
Capacity	Max User: 500,000 Fingerprint 1: 200,000 Templates < 1sec Face 1: 150,000 Templates < 1sec Event Logs: 10,000,000 Photo Logs: 20,000
Dimensions (W x H x D)	149.3 x 202.2 x 129.2mm
Approvals	KC, CE, FCC

NETWORK ACCESSORIES

Uncompromising Connectivity

Establish the ultimate network backbone with our comprehensive lineup: from encoders bridging analog and digital worlds to Long Reach PoE Extenders surpassing physical boundaries, and switches mastering traffic control. We ensure your security system achieves optimal performance in any setting.

	SFP Transceiver	
	FTLF1318P3BTL	FTLF8519P3BNL
Model Name		
Key Features	- Up to 10km on 9/125µm SMF - Up to 1.25Gb/s bi-directional data links - Hot-pluggable SFP footprint 1310nm Fabry-Perot laser transmitter - Compatibility with DH series and DA-MC1101	- Up to 500m on 50/125µm MMF, 300m on 62.5/125µm MMF - Up to 2.125Gb/s bi-directional data links - Hot-pluggable SFP footprint 850nm Oxide VCSEL laser transmitter - Compatibility with DH series and DA-MC1101

NETWORK ACCESSORIES

	Network Keyboard	
	NK-1200	
Model Name		
Key Features	- Remote control of NVRs, network video transmitters, network video receivers and network cameras via network connection - Control of NVRs by using a USB mouse via network connection - Two-way audio communication - Convenient firmware upgrades via either the USB port or ethernet - Firmware duplication and auto-recovery functions to enhance system stability - Management of multiple network keyboards via network connection - Programmable by using the LCD screen - Supports PoE (IEEE 802.3af class 0)	

	4 Bay eSATA Storage			
	DA-ES1104A	DA-ES1104B-A	DA-ES1104C-A	DA-ES1104D-A
Model Name				
Interface	eSATA x 1			
HDD	SATA x 4			
HDD Size	3.5"			
RAID	RAID 1, 5, 10 Supported			
Supported Device	TR-4408(R) / 16(R)	Up to 4TB: TR-4408(R) / 4416(R) Up to 12TB: DR-2504P(-A) / 2508P / 2516P / 3516P / 6508P / 6516P / 6532P / 8516 / 8532(D), TR-4508(R)/4516(R)	Up to 6TB: IR-100, IR-300 Up to 10TB: DR-8364(F)(D)	IR-300A, IR-310(-A)(D)(D-A)
Operation Temperature	0°C ~ 40°C (32°F ~ 104°F)			
Operating Humidity	0% ~ 90%			
Power Input	100V ~ 240VAC, 0.6 ~ 0.3A, 50/60Hz			
Power Consumption	100 ~ 240V~, 50/60Hz, 0.6 ~ 0.3A, 40W			
Approvals	FCC, CE, CB, KC, UL			

	Long Range PoE Extender	Single Port PoE Injector	Single Port High-PoE Injector
	DA-LP1101R / DA-LP1101T	DA-PI2101	PoE400
Model Name			
Key Features	• Up to 500m PoE transmission between devices using UTP cabling • Up to 700m data transmission between devices using UTP cabling • Plug-and-play without any required PC setting • Supports 1Gbps / IEEE802.3at for PoE Injector • Supports 1Gbps / IEEE802.3at / 100m for PoE Repeater	• Up to 30W of PoE power feeding on two pairs • Compatibility with IEEE 802.3af, IEEE 802.3at • Protects low power devices to receive only the power they need • Parallel slide-in design for easy installation	• Up to 90W of PoE power • Compatibility with IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt • Protects low power devices to receive only the power they need • Support 10/100/1000 Base-T LAN environment • Compatibility with DC-S6286HRXL (-A), DC-S6881HRX (-A), DC-S6681HRX (-A)

	DirectIP Gigabit PoE Switch				
	DH-2328PF-A	DH-2026PF	DH-2212PF	DH-2018P	DH-2010P
Model Name					
Key Features	• Individual port data transmission to DirectIP NVR • PoE (IEEE 802.3af, IEEE 802.3at) compliant • Maximum per-device PoE delivery of 370W available for 1 to 24 RJ45 ports • Central power control for greater network utility • Supports 24 RJ45 ports and 4 SFP slots	• Individual port data transmission to DirectIP NVR • PoE (IEEE 802.3af, IEEE 802.3at) compliant • Maximum per-device PoE delivery of 360W available for 1 to 24 RJ45 ports • Central power control for greater network utility • Supports 24 FE RJ45 ports and Uplink 2 GbE RJ45 / 2 GbE SFP combo slots	• Individual port for data transmission to DirectIP NVR • PoE (IEEE 802.3af, IEEE 802.3at) compliant • Maximum per-device PoE delivery of 140W available for 1 to 8 RJ45 ports • Central power control for greater network utility • Supports 8+2 RJ45 ports and 2 SFP slots	• Individual port for data transmission to DirectIP NVR • PoE (IEEE 802.3af, IEEE 802.3at) compliant • Maximum per-device PoE delivery of 140W available for 1 to 16 RJ45 ports • Central power control for greater network utility • Supports 16 RJ45 ports	• Individual port for data transmission to DirectIP NVR • PoE (IEEE 802.3af, IEEE 802.3at) compliant • Maximum per-device PoE delivery of 70W available for 1 to 8 RJ45 ports • Central power control for greater network utility • Supports 10 RJ45 ports

NETWORK ACCESSORIES

	HDMI/VGA Video Encoder
	DP-HE1201
Model Name	 
Video codec	H.265, H.264, MJPEG, Intelligent Codec
Max. Framerate	3840 x 2160 @ 30ips
Bitrate	Up to 18MP
Max Resolution	3840 x 2160
Streaming	Quadruple Streaming
Max. Network Throughput	50Mbps
Built-in OSD	English, Korean
Input	1 x HDMI, 1 x VGA
Output	1 x HDMI (Input Bypass) 1 x VGA (Input Bypass)
Audio Input / Output	1 x Line In (3.5mm) / 1 x Line Out (3.5mm)
Network Interface	1 x RJ45 (10/100)
IP Camera Protocol	DirectIP 2.0, ONVIF
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)
Power Consumption	12V= 0.95A, 11.4W PoE, IEEE 802.3af (Class 3)
Approvals	FCC, CE, KC

	Alarm Box
	AL-1112
Model Name	
Alarm Input	8 Digital-Input -Dry Contact, Wet Contact High: Open or DC 5V ~ DC 30V Low: Short or DC 0V ~ DC 1.8V
Alarm Output	4 Relay-Out - NC, NO, COMMON
Power Output	12VDC (300mA), 5VDC (400mA)
Ethernet	10/100Mbps
DirectIP Yes	Yes
USB	Yes (Spare)
PoE (Class)	Yes, IEEE 802.3at (Class 4)
Power Source	12VDC, 24VAC, PoE
Power Consumption	20W
Approvals	FCC, CE, KC



	Encoder
	DP-DE2108
Model Name	 
Video Input	8 BNC
Max Resolution	2560 x 1920
Video Compression	H.265, H.264
Max Frame Rate	240ips @ 1080P, 144ips @ 3MP, 120ips @ 4MP, 80ips @ 5MP
Multi-video Streaming	Quadruple Streaming
Ethernet	RJ45 (10/100 BASE-T)
Trigger Event	Motion Detection, Tampering, Trip Zone, Video Loss
Audio In / Out	4 / -
Operating Temperature	0°C ~ 40°C (+32°F ~ +104°F)
Operating Humidity	0% ~ 90%
Power Source	12VDC, PoE, IEEE 802.3af (Class 3)
Power Consumption	12V=, 0.8A, 10W PoE, IEEE 802.3af (Class 3), 10W
Approvals	FCC, CE, KC
Dimensions	200 x 44 x 165.2mm (7.9" x 1.7" x 6.5")
Weight	0.81kg (1.79lb)

	Decoder
	DP-DD1316
Model Name	 
Video Compression	H.264, H.265
Video Input	16ch IP
Video Input Resolution	Up to 12MP
Yes Devices	DirectIP NVR, IDIS IP Camera
Video Outputs	1 HDMI, 1 VGA, 1 CVBS
Display Resolution	HDMI: 3840 x 2160, 2560 x 1440, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200 VGA: 2560 x 1440, 1920 x 1200, 1920 x 1080, 1680 x 1050, 1600 x 1200 CVBS: 720 x 480 (NTSC), 720 x 576 (PAL)
Display Speed	Up to 480ips
Max. Network Throughput	90Mbps
Network Connection	Gigabit Ethernet x1
PoE (Class)	Yes, IEEE 802.3af (Class 3)
Power Source	12VDC, PoE
Power Consumption	12V=, 1.4A, 16.8W PoE, IEEE 802.3at (Class 4)
Approvals	FCC, CE, KC



IDIS SOLUTION SUITE

MODULAR & SCALABLE

Next Generation Video Management

SOFTWARE SOLUTIONS

Modular & Scalable

Find out about our latest software release and specialized functionality that take IDIS solutions to another level.



SOFTWARE SOLUTIONS - VMS

IDIS SOLUTION SUITE

Enterprise-Class and Multi-Site VMS



IDIS SOLUTION SUITE®

IDIS Solution Suite Expert is a program that manages multiple NVRs and IP cameras for large-scale applications.

How IDIS Solution Suite Service Modules Are Designed and Operated?

IDIS Solution Suite can work together with network cameras, DirectIP® NVRs, and DirectCX® TVRs while providing superior image quality and extensive coverage. IDIS Solution Suite allows you to manage an unlimited number of devices and to customize your surveillance system cost effectively.

IDIS Solution Suite has been designed using a deep understanding of market requirements and customer needs. With our market-proven products like NVRs and TVRs, network cameras, and encoders and decoders, IDIS Solution Suite offers one of the best value enterprise-class video management surveillance solutions on the market.





Administration

The IDIS Solution Suite Administration service module defines an IDIS Solution Suite system, whereby all other service modules are registered to this module to enable centralized management of access privileges and device management, such as device firmware upgrades, remote device configuration, and configuration of all other IDIS Solution Suite service modules in use.

Monitoring

The IDIS Solution Suite Monitoring service module allows centralized event dispatch services, enabling you to route a specific set of events to a specific user or group of users based on event types, schedules, and user groups. For example, system health-related events can be routed to maintenance department operators, while other events can be routed to loss prevention managers.

Streaming

The IDIS Solution Suite Streaming service module allows up to 64 remote users to access live video streams.

Recording

The IDIS Solution Suite Recording service module records video directly from IP cameras or IP video encoders. This module, running on a PC server platform, can be configured to utilize a centralized storage solution with significantly larger storage capacity, such as SAS or iSCSI/SAN. Additionally, it allows you to add up to 64 IDIS Solution Suite Recording service modules to your IDIS Solution Suite System.

Redundancy

The IDIS Solution Suite Redundant Recording module allows users to provide tandem recording. Users can create redundant video recording on a separate server, which can be located in a remote location. In the event the primary IDIS Solution Suite recording server is destroyed, your data remains protected remotely.

Backup

The IDIS Solution Suite Backup service module can be used to provide offline backup of video. This service module allows you to select a set of cameras to archive on a pre-programmed schedule, enabling you to archive your video while minimizing network traffic during peak hours of operation. Additionally, the IDIS Solution Suite Backup service provides two additional options to maximize the data retention period of your offline backup storage: summary backup and event-video-only backup mode.

VideoWall

The IDIS Solution Suite VideoWall service allows operators to manage and control any camera from DirectIP NVRs, DirectCX HD Analog, or DirectIP cameras recording on an IDIS Solution Suite server. Operators also benefit from a single interface and unified experience using the network keyboard, NK-1100. Additionally, the VideoWall service allows users to expand their surveillance capability by supporting up to 384 monitors.

Federation

The IDIS Solution Suite Federation module operates similarly to the IDIS Solution Suite Administration service module by enabling you to create a federation of multiple IDIS Solution Suite systems. This service module allows centralized management of access privilege control over devices registered to multiple IDIS Solution Suite systems.

The IDIS Solution Suite Federation also enables your video surveillance system to grow practically to an unlimited number of cameras. For example, each IDIS Solution Suite system can manage up to 1,024 devices, and each device can handle up to 64 IP cameras (DR-8364). Each IDIS Solution Suite system can handle up to 64,000 cameras, and the IDIS Solution Suite Federation allows multiples of these systems.

Failover

IDIS Solution Suite Failover service modules provide service-grade redundancy. The Failover services can be applied to different service modules, such as Administration, Federation, Recording, Streaming, or VideoWall services.

If one of the PC servers fails or if one of the services is interrupted, the corresponding Failover module will take over operations with minimal interruption. Once the failed servers or services are recovered, the operation will recover and return to normal operation.

SOFTWARE SOLUTIONS

Scalable Control, Smart Investment

Take full command of your security operations, no matter where you are. Our solution empowers you with remote surveillance of live video and playback, ensuring complete visibility 24/7. Stay proactive with real-time notifications of detected events, and instantly capture critical evidence using the panic recording feature.



SOFTWARE SOLUTIONS - VMS

IDIS CENTER

License-Free Video Management Software



IDIS CENTER

IDIS Center is a central management software solution that supports live monitoring, video Playback, as well as advanced management tools, including event monitoring, e-maps, and condition monitoring devices.

- Remote surveillance of live video and remote playback of recordings
- Real-time notification of detected events and remote monitoring of events
- Panic recording of live videos and playback recordings
- Registration of up to 1,024 devices
- Simultaneous remote software upgrades and multiple system setup
- Displays for device system logs
- Monitoring live e-map
- SSL support to ensure secure communication
- Authority settings by individual or user groups
- Intuitive and user-oriented GUI
- Supports Removable HDD (or SD Card)
- Live viewing, searches, e-maps, and condition monitoring executed simultaneously by displaying distinctly different panels across four monitors.

SOFTWARE SOLUTIONS - VMS

IDIS WEB

Web Client



IDIS WEB

IDIS Web is a program that allows you to view and search video from remote locations over the Internet and can be accessed on a regular web browser such as Internet Explorer. IDIS Web can be downloaded from web browsers in ActiveX format.

- Supports 32 divided screen surveillance
- Controls PTZ, color, alarm out feature
- Supports 32 divided screen playback
- Supports video back-up with IDIS Player, AVI, BMP
- Supports storage and print-out of current image on screen

Connection Method

- <http://IP Address: Port Number>
(NVR system's IP address and IDIS Web port number configured under Network > General (Default Value: 12088))
- <http://fen.idisglobal.com/FEN Name>
(FEN Name: NVR name configured on the FEN server)
- <http://web.idisglobal.com>
(Will be prompted to enter NVR's IP address or FEN name registered to the FEN server upon login)



SOFTWARE SOLUTIONS


SOFTWARE SOLUTIONS - CLOUD

IDIS CLOUD MANAGER

Manage All Your Sites in The Cloud



IDIS Cloud Manager (ICM) makes it simple, easy, and secure to access and manage video remotely. By connecting your sites to the cloud enables centralized management of surveillance for every level of user, whether that's senior managers and general administrators, or front-line security operators from web browsers and mobile devices. ICM comes with an intuitive interface making configuration and network changes hassle-free.



SOFTWARE SOLUTIONS



SOFTWARE SOLUTIONS - MOBILE

IDIS MOBILE

Smart Security at Your Fingertips!



From high-definition live streaming to powerful PTZ control and push notifications – complete security management is now in the palm of your hand.

Various Viewing Modes

- Simultaneous 1/4/9/16 split screen live monitoring
- Enables up to 2 x 2 split screens for searching recorded video
- Supports iPad split view, dark mode, while users can choose portrait or landscape viewing options



- Operates with all IDIS DirectIP NVR, DitectCX TVR and IP cameras
- Supports seamless viewing of full-HD live streaming video on mobile devices from remote locations and provides 1/4/9/16 split screen monitoring
- PTZ Control, Enables pan, tilt, zoom control of DirectIP, DirectCX, and IP cameras directly from mobile device
- Supports highest image quality with H.264/MJPEG, H.265 formats
- Provides calendar search, playback and bookmark functions
- Quick and easy access with various mobile connections over 3G, LTE, 5G and WiFi
- Supports push alarm, event/time lapse query, 2-way audio and image capture


CAMERA CONFIGURATION TREE

- Adapter Plate · Mount Adapter · Box Housing · Sun Shield
- Junction Box · Flush Mount · Tilt Mount · Wall Mount
- Ceiling Mount · Pole Mount · Corner Mount





SPEED DOME (1)




SPEED DOME (2)




SPEED DOME (3)



SPEED DOME (4)




DOME (1)



- DC Series DC-D4217RX
- TC Series TC-D4211RX

DOME (3)




- TC Series TC-D4222RX, TC-D4221RXP

DOME (2)




- DC Series DC-D4537RXA, DC-D4536RX, DC-D4237RX, DC-D4236RX, DC-D4236X
- TC Series TC-D5532RX, TC-D5531RX, TC-D5531RXP-A

DOME (4)




- DC Series DC-D4532WERA

DOME (4-1)




DOME (4-2)



DOME (5)




DOME (6)



DOME (7)




DOME (9)




DOME (8)




MULTI-IMAGER




FISHEYE (1)



FISHEYE (2)




FISHEYE (3)




INTERCOM




BULLET (1)




BULLET (1-1)



BULLET (2)



BULLET (2-1)



BULLET (3)



Built-In Junction Box

Corner Mount



DA-RM2000

Pole Mount



DA-LM2000

DC Series

DC-T8871WRA, DC-T8831WRA, DC-T8671WRA, DC-T8631WRA, DC-T6831WRA, DC-T6631WRA

BULLET (4)



Wall Mount



DA-WM3200

DC Series

DC-T6222HRL, DC-T6224HRXL,DC-T6223HRL

BOX / ZOOM



Box Housing



BA-BH1100EX

Wall Mount



DA-WM3200

DC Series

DC-B6206XL, DC-B4501X

TC Series

TC-B5502X, TC-B5501X, TC-B5501XP-A, TC-B4201X, TC-B4202X, TC-B4201XP



INDOOR DOME



CID-FMA



CID-WMT-CDM



CHG2501



CHG2511




CID-CMT-W

Here are the options available based on your situation:

Models		Type
		Cap

Models AV02CID-200, AV02CID-201, AV05CID-200, AV05CID-201

OUTDOOR DOME



Models AV02CLD-200, AV05CLD-200

Here are the options available based on your situation:


Models	Type	
	AV-EBAPR	Electrical Box Adapter Plate
	DA-JB130A	Wall Mount Junction Box w Cover
	DA-JB131A	4S Weathertight Junction Box Cover w/ gasket
	DA-MA110A	Mount Ring Adapter

* DA-WM2050 can be used with a junction box
If a junction box is required: use DA-JB130A
If a junction box already exists: use DA-JB131A
* DA-MA110A (Mount Ring Adapter) is used with DA-WM2050

MICRO DOME



CID-FMA



MCD-WMT-W



CHG2501



CHG2511



MCD-CMT-W

Here are the options available based on your situation:

Models		Type
	MCD-EBA *	Corner Mount
	MCD-JBAS-W *	Junction Box Adapter
	MCD-CRMT *	Electrical Box Adapter
	MCD-4S *	Electrical Box Adapter
	AV-JBA-W	Junction Box

Models AV2856DNIR-S, AV2856DNIR-F, AV5856DNIR-S, AV5856DNIR-F
AV8856DNIR-S, AV8856DNIR-F
* Compatible with Surface Mounted Cameras


MICRO DOME DUO



Here are the options available based on your situation:

Models	Type	
	AV-JBA-W	Junction Box

Models AV4956DN-28, AV10956DN-28, AV16956DN-28




Here are the options available based on your situation:


Models	Type	
	AV-EBAPR	Electrical Box Adapter Plate
	DA-JB130A	Wall Mount Junction Box w Cover
	DA-JB131A	4S Weathertight Junction Box Cover w/ gasket
	DA-MA110A	Mount Ring Adapter

* DA-WM2050 can be used with a junction box
If a junction box is required: use DA-JB130A
If a junction box already exists: use DA-JB131A
* DA-MA110A (Mount Ring Adapter) is used with DA-WM2050

MULTI-IMAGER OMNI RS



MULTI-IMAGER OMNI RSIR




Models AV20576RSIR, AV32576RSIR

When installing a Multi-Imager Omni RS/RSIR camera,
Here are the options available based on your situation:

Models	Type
	AV-JBA-W Junction Box
	7412007-006 PoE Injector
	DA-JB130A Wall Mount Junction Box w Cover
	DA-JB131A 4S Weathertight Junction Box Cover w/ gasket
	DA-MA110A Mount Ring Adapter

* DA-WM2050 can be used with a junction box
If a junction box is required: use DA-JB130A
If a junction box already exists: use DA-JB131A
* DA-MA110A (Mount Ring Adapter) is used with DA-WM2050

MULTI-IMAGER OMNI RS/RSIR
with 1.5" NPT IP67 Quick Disconnect




When installing a Multi-Imager Omni RS/RSIR camera,
Here are the options available based on your situation:

Models	Type	
	AV-JBA-W	Junction Box
	7412007-006	PoE Injector
	DA-JB130A	Wall Mount Junction Box w Cover
	DA-JB131A	4S Weathertight Junction Box Cover w/ gasket
	DA-MA110A	Mount Ring Adapter

* DA-WM2050 can be used with a junction box
If a junction box is required: use DA-JB130A
If a junction box already exists: use DA-JB131A
* DA-MA110A (Mount Ring Adapter) is used with DA-WM2050

MULTI-IMAGER OMNI LX



Models AV8576DN-28, AV20576DN-28

LENS for MULTI-IMAGER OMNI LX,
DUO LX and Microdome LX

Models	Type	Accessory PN
	Lens 2.4mm	MPM2.4d
	Lens 2.8mm	MPM2.8C
	Lens 4mm	MPM4.0d
	Lens 6mm	MPM6.0d
	Lens 8mm *	MPM8.0d
	Lens 12mm *	MPM12.0d
AV2856DNIR-S, AV2856DNIR-F AV5856DNIR-S, AV5856DNIR-F AV8856DNIR-S, AV8856DNIR-F AV4956DN-28, AV10956DN-28 AV16956DN-28 AV8576DN-28 / AV20576DN-28 *	Lens 16mm *	MPM16.0d

* MPM8.0d, MPM12.0d, MPM16.0d require SO-BUBBLE
* 8/12/16 millimeter lenses only

When installing a Multi-Imager Omni LX camera,
Here are the options available based on your situation:

Models	Type
	SO-BUBBLE *
Bubble With Gasket	
	AV-JBA-W
Junction Box	
	7412007-006
PoE Injector	
	DA-JB130A
Wall Mount Junction Box w Cover	
	DA-JB131A
4S Weathertight Junction Box Cover w/ gasket	
	DA-MA110A
Mount Ring Adapter	

* DA-WM2050 can be used with a junction box
If a junction box is required: use DA-JB130A
If a junction box already exists: use DA-JB131A
* DA-MA110A (Mount Ring Adapter) is used with DA-WM2050

MEMO



One Solution. One Company.

IDIS HQ

IDIS Tower, 344 Pangyo-ro
Bundang-gu, Seongnam-si
Gyeonggi-do, 13493
Republic of Korea

T +82 (0)31 723 5400
F +82 (0)31 723 5100
E sales@idisglobal.com

IDIS Americas

101 Wrangler Drive
Ste.201
Coppell, TX 75019
U.S.A.

T +1 469 635 6800
E sales@idisamericas.com

IDIS Europe

1000 Great West Road
Brentford, Middlesex
TW8 9HH
United Kingdom

T +44 (0)203 657 5678
F +44 (0)203 697 9360
E uksales@idisglobal.com

IDIS Middle East

P.O. Box 341037
D-308, DSO HQ Bldg
Dubai Silicon Oasis
Dubai, U.A.E.

T +971 4 501 5434
F +971 4 501 5436
E sales_mena@idisglobal.com

Türkiye Liaison Office

T +90 533 696 7780
E sales_mena@idisglobal.com

IDIS Tokyo

1633 W16F,
Shibuya Mark City,
1-12-1 Dogenzaka Shibuya-ku
Tokyo 150-0043, Japan

T +81 3 4360 5612
E sales_japan@idisglobal.com

IDIS Netherlands

De Slof 9
5107 RH
Dongen
The Netherlands

EU Distribution Center
T +31 (0)162 387 217
E sales_eu@idisglobal.com

IDIS Benelux

T +31 (0)162 387 247
F +31 (0)162 311 915
E sales@bnl.idisglobal.com

IDIS and identifying product names and numbers herein are registered trademarks of IDIS Co., Ltd. All non-IDIS brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status, and/or specifications are subject to change without notice. Copyright © IDIS Co., Ltd. All rights reserved.

* Product specifications in this brochure are subject to change. Please confirm details on our website.

* The images in this brochure are for illustrative purposes only.

For more information, please visit www.idisglobal.com

Made in **KOREA**

